



OMADA ES220GP network switch Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Modelis: ES220GP

Gamintojas: TP-LINK

EAN: 1210002609746

Prekės kodas: 375820

184.98€

Product colour: Black | Web-based management: Yes | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.1ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3af | AC input frequency: 50/60 Hz | Ethernet LAN data rates: 10,100,1000 Mbit/s | AC input voltage: 100 - 240 V | SFP module slots quantity: 2 | Number of VLANs: 32 | Power over Ethernet (PoE): Yes | Height: 44 mm | Power consumption (max): 182.43 W | Storage relative humidity (H-H): 5 - 90% | Switching

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

capacity: 40 Gbit/s | Power source: AC | Housing material: Metal | Depth: 180 mm | VLAN support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power connector: AC-in jack | 10G support: No | Multicast support: Yes | User guide: Yes | Width: 294 mm | Operating relative humidity (H-H): 10 - 90% | Noise level: 20.1 dB | MAC address table: 8000 entries | Auto MDI/MDI-X: Yes | Packet buffer memory: 4 MB | Cables included: AC | DHCP features: DHCP client | Jumbo frames support: Yes | Operating temperature (T-T): -5 - 40 °C | Total Power over Ethernet (PoE) budget: 150 W | Rack mounting: Yes | Basic switching RJ-45 Ethernet ports quantity: 18 | Input current: 2.5 A | Mean time between failures (MTBF): 320156 h | IGMP snooping: Yes | Port mirroring: Yes | Power over Ethernet plus (PoE+) ports quantity: 16 | Forwarding rate: 29.76 Mpps | Store-and-forward: Yes | Link aggregation: Yes | Broadcast storm control: Yes | Gigabit Ethernet (copper) ports quantity: 18 | Power over Ethernet (PoE) type supported: PoE+ | Fanless: Yes | Virtual LAN features: Tagged VLAN | Virtual LAN features: Port-based VLAN | Auto-negotiation: Yes | Cloud-managed: Yes | Virtual LAN features: MTU VLAN | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Compliance certificates: Federal Communications Commission (FCC) | Number of queues: 8 | Switch type: Managed | Compliance certificates: RoHS | Compliance certificates: CE

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903