



Epson EcoTank M1120 inkjet printer 1440 x 720 DPI A4 Wi-Fi



Modelis: C11CG96403

Gamintojas: EPSON

EAN: 8715946655444

Prekės kodas: 375909

189.99€

Hazard pictogram(s): GHS09: Environmental hazard | Warnings: In the event of an ink spill, avoid inhaling vapours. | Warnings: The product contains environmentally hazardous components. Dispose of in accordance with local regulations and do not dispose of in the rubbish. | Hazard pictogram(s): GHS07: Harmful | Warnings: Avoid contact with ink. May cause skin and eye irritation. | Product colour: Black | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows 8 | Weight: 3.5 kg | Package weight: 4.67 kg | Built-in display: No | Package width: 337 mm | Power consumption (off): 0.3 W | USB 2.0 ports quantity: 1 | AC input voltage: 100 - 240 V | Windows operating systems supported: Windows 10 | Power consumption (PowerSave): 0.7 W | Package depth: 438 mm | Number of print cartridges: 1 | Market positioning: Home & office | Wi-Fi standards: 802.11b | Mobile printing technologies: Epson Email Print | Package height: 288 mm | Windows operating systems supported: Windows Vista | Height: 161 mm | Depth: 267 mm | Mobile printing technologies: Epson Remote Print | Mobile printing technologies: Google Cloud Print | Wi-Fi standards: 802.11g | Windows operating systems supported: Windows 7 | Mobile printing

technologies: Epson iPrint | Windows operating systems supported: Windows XP | Wi-Fi standards:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Wi-Fi 4 (802.11n) | Card reader integrated: No | Supported network protocols: TCP/IPv4, TCP/IPv6, SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD | Wi-Fi: Yes | USB port: Yes | Width: 375 mm | Manual: Yes | Maximum print size: 216 x 1200 mm | Colour: No | Server operating systems supported: Windows Server 2008 x64 | Server operating systems supported: Windows Server 2003 R2 | Server operating systems supported: Windows Server 2012 R2 | Server operating systems supported: Windows Server 2016 | Power consumption (standby): 3 W | Server operating systems supported: Windows Server 2008 R2 | Server operating systems supported: Windows Server 2008 | Server operating systems supported: Windows Server 2012 x64 | ISO A-series sizes (A0...A9): A6 | ISO B-series sizes (B0...B9): B6 | ISO B-series sizes (B0...B9): B5 | Paper input type: Paper tray | ISO A-series sizes (A0...A9): A5 | Print speed (black, normal quality, A4/US Letter): 32 ppm | Maximum ISO A-series paper size: A4 | Non-ISO print media sizes: Hagaki card | Non-ISO print media sizes: Letter | Ink type: Pigment-based ink | Printing colours: Black | Non-ISO print media sizes: 16K | ISO A-series sizes (A0...A9): A4 | Sound pressure level (printing): 53 dB | Non-ISO print media sizes: Legal | Paper tray media types: Plain paper | Print speed (ISO/IEC 24734) mono: 15 ipm | Wi-Fi Direct: Yes | Maximum duty cycle: 15000 pages per month | Maximum resolution: 1440 x 720 DPI | Envelopes sizes: 10 | Time to first page (black, normal): 8 s | Paper tray media types: Photo paper | Page description languages: ESC/P-R | Ink tank system: Yes | Pallet gross length: 120 cm | Envelopes sizes: C6 | Power consumption (printing): 14 W | Print margins (top, bottom, right, left): 3 mm | Page description languages: GDI | Paper tray media weight: 64 - 90 g/m² | Total number of input trays: 1 | Total output capacity: 30 sheets | Total input capacity: 150 sheets | Duplex printing: No | Page description languages: ESC P | Pallet length (UK): 120 cm | Envelopes sizes: DL