



Skaner 3D Crealty Sermoon X1



Modelis: 4008050064

Gamintojas: CREALITY

EAN: 6977905742240

Prekės kodas: 375943

6,300.99€

Crealty Sermoon X1 3D Scanner

If your goal is to digitally reproduce real objects with the highest possible accuracy, the Creality Sermoon X1 3D Scanner is the tool for you. This advanced 3D scanner was created for professionals—engineers, designers, reverse engineering specialists, as well as industrial and design applications where every detail matters. With its extremely precise measurements and extensive operating modes, it is the ideal choice when you need high-quality 3D data and work efficiency.

Unmatched scanning accuracy and stability

At the heart of the Sermoon X1 is a high-precision scanning system that achieves accuracy of up to 0.02 mm, and with the use of built-in scaled photogrammetry, volumetric precision reaches 0.02 mm + 0.03 mm/m. These results meet the expectations of many technical and professional applications. In practice, this means that the scans faithfully reproduce the shape and actual dimensions of the object, which is crucial in quality control, CAD design, and reverse engineering.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Wide working field

The use of proprietary optimization algorithms allows the Sermoon X1 scanner to offer an extremely large scanning field. Such a wide working area significantly reduces the need for markers, which translates into a faster, smoother, and more efficient scanning process. In line laser mode, the maximum field of view is 650 × 531 mm, while in infrared mode it reaches an impressive 1300 × 935 mm. Thanks to a hybrid system combining blue laser lines and structured infrared light, the Sermoon X1 supports a wide range of scanning sizes, from small 5 × 5 × 5 mm³ to large 4000 × 4000 × 4000 mm³.

With details in mind

The X1's single-laser deep hole scanning mode allows you to easily capture 3D data from hard-to-reach areas such as deep holes, narrow gaps, and recesses. Support for scanning narrow holes with a depth-to-diameter ratio of up to 6:1 ensures more accurate 3D data acquisition, which is ideal for design, inspection, analysis, and more. The scanner is equipped with a high-performance Qualcomm ISP chip, a 2 MP full-color RGB camera, and additional lighting for richer and more realistic textures.

Versatile operating modes

The Creality Sermoon X1 scanner offers several operating modes tailored to different tasks. Single laser lines are ideal for deep and narrow spaces that other systems cannot capture. The NIR mode with structured light allows for tagless scanning of even large items. Seven parallel laser lines are great for detailed scanning of technical surfaces, while 34 intersecting laser lines speed up the scanning of medium and large objects. This makes the X1 an extremely versatile tool in a professional workshop.

Efficient work without compromise

Professional projects require both precision and speed. The X1 achieves a scanning speed of up to 90 frames per second, and the system can capture millions of measurements per second in various operating modes. This means that even larger parts or complex geometries can be scanned in less time without losing detail quality. With advanced Wi-Fi 6 technology, the X1 scanner delivers fast, cable-free scanning and uncompromising battery life. It easily adapts to different measurement

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

environments, giving you the freedom to scan anywhere.

Compact design and comfortable to use

The one-piece optoelectronic body and lens mount, made of CNC-machined metal, combine high durability with a lightweight, refined design (weighing only 530 g). Its compact dimensions (216 × 74 × 51 mm) make the scanner mobile and easy to use, facilitating work in all conditions. The mechanical locking system effectively eliminates backlash and the risk of component dispersion, which has a direct impact on the repeatability and accuracy of scans. High-strength materials ensure excellent rigidity and vibration resistance, so that every scanning process is stable, precise, and reliable, even in demanding working conditions.

Wide compatibility

The Sermoon X1 scanner works with the advanced CrealityScan 4.0 scanning software, which facilitates the import of scans, their processing, and export to popular formats (STL, OBJ, PLY). This allows the prepared data to be used without hindrance in CAD/CAM programs for further design, analysis, or production. The intuitive interface and automatic point registration tools mean that even complex 3D models can be prepared with minimal time and effort.

Safe operation in all conditions

The scanner is designed for reliable operation in both workshop and outdoor conditions. The device works efficiently even in sunlight – in single or 7-line laser beam mode at light intensities up to 50,000 lux, and in 34 cross-line mode up to 100,000 lux. Importantly, scanning of black and metal surfaces can be performed without the need for matting sprays, which significantly speeds up work and increases comfort of use, especially in field applications.

Intelligent stabilization

An advanced stabilization system ensures smooth and precise scanning even during prolonged operation. Thanks to an AI-controlled temperature compensation algorithm and an efficient heat management system, the Sermoon X1 maintains stable output parameters throughout its operation. Combined with One-Shot 3D imaging technology, this solution increases object tracking stability,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

effectively reducing frame drops and data connection errors resulting from vibrations or movements, which translates into higher quality and consistency of scans.

Included in the set

- scanner
- high-precision glass calibration plate
- x2 measuring scale
- power adapter
- USB 3.0 cable (Type-C to Type-A)
- data cable
- charging cable
- reflective marking points (D6 mm*40 sheets, D3 mm*40 sheets)
- manually tightened quick release card
- magnetic phone holder
- Wi-Fi 6 adapter
- Type-C power adapter
- cleaning cloth
- headband
- waterproof box
- user manual

General

Manufacturer Creality

Model Sermoon X1

Scanning modes Deep hole scanning, detailed scanning, fast scanning, markerless scanning

Marker

recognition 12 blue LEDs

enhancement

Laser safety Class II (safe for the eyes)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Weight	530 g
Dimensions	216mm*74mm*51mm
Mechanical structure	Optoelectronic bracket and lens base, CNC integrated molding, complete mechanical locking (better stability, longer service life)
Calibration plate	High-precision glass calibration plate
Wireless operation	Supported
Computer configuration	Windows: i7-Gen10 processor, Nvidia graphics card (8 GB VRAM), 32 GB RAM, Windows 10/11 (64-bit); Minimum requirements: i7-Gen7 processor, Nvidia graphics card (6 GB VRAM), 16 GB RAM, Windows 10/11 (64-bit); macOS: M1/M2/M3/M4 series processor, 16 GB RAM
Interface mode	USB 3.0 × 1
Input power	12V, 3A
Operating temperature	-10°C to 40°C
Operating humidity	10-90%RH
Certifications	CE, RoHS, REACH, WEEE, FDA, FCC, UL, IC, RCM, PSE, SRRC, GB 4943.1

Single line scanning mode

Accuracy	Up to 0.02 mm
Volume accuracy	0.02 mm + 0.04 mm/m 0.02 mm + 0.03 mm/m (with scale)
Scanning speed	84,000 measurements per second
Scanning speed	Up to 90 frames per second
3D resolution	0.05-2mm
Photogrammetry	Photogrammetry mode (with 2x magnetic carbon fiber scale)
Minimum scanning volume	5mm x 5mm x 5mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Single capture range	215mm x 167mm@200mm, 325mm x 323mm@300mm, 434mm x 394mm@400mm, 542mm x 463mm@500mm, 650mm x 531mm@600mm
Working distance	200mm-600mm
Color mapping	Supported
Alignment mode	Marker / Global marker
Colored supplementary light	12 white LEDs
Outdoor scanning	Below 100,000 lux

Scanning in 7 parallel laser line mode

Accuracy	Up to 0.02 mm
Volume accuracy	0.02 mm + 0.04 mm/m 0.02 mm + 0.03 mm/m (with scale)
Scanning speed	756,000 measurements per second
Scanning rate	Up to 90 frames per second
3D resolution	0.05-2mm
Photogrammetry	Photogrammetry mode (with 2x magnetic carbon fiber scale)
Minimum scanning volume	5mm x 5mm x 5mm
Single capture range	215mm x 167mm@200mm, 325mm x 323mm@300mm, 434mm x 394mm@400mm, 542mm x 463mm@500mm, 650mm x 531mm@600mm
Working distance	150mm-400mm
Color mapping	Supported
Alignment mode	Marker / Global marker
Colored supplementary light	12 white LEDs
Outdoor scanning	Below 50,000 lux

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Scanning in 34 intersecting laser line mode

Accuracy	Up to 0.02 mm
Volume accuracy	0.02 mm + 0.04 mm/m 0.02 mm + 0.03 mm/m (with scale)
Scanning speed	1,734,000 measurements per second
Scanning rate	Up to 85 frames per second
3D resolution	0.05-2mm
Photogrammetry	Photogrammetry mode (with 2x magnetic carbon fiber scale)
Minimum scanning volume	5mm x 5mm x 5mm
Single capture range	215mm x 167mm@200mm, 325mm x 323mm@300mm, 434mm x 394mm@400mm, 542mm x 463mm@500mm, 650mm x 531mm@600mm
Working distance	200mm-600mm
Color mapping	Supported
Alignment mode	Marker / Global marker
Colored fill light	12 white LEDs
Outdoor scanning	Below 100,000 lux

Markerless scanning (NIR)

Accuracy	Up to 0.05 mm
Volume accuracy	0.05 mm + 0.1 mm/m
Scanning speed	5,000,000 measurements per second
Frame rate	Up to 30 frames per second
3D resolution	0.1-2 mm
Photogrammetry	Photogrammetry mode (with 2x magnetic carbon fiber scale)
Minimum scan volume	150mm x 150mm x 150mm
Single capture range	650mm x 531mm at 600mm; 1300mm x 935mm at 1200mm
Working distance	170mm-1200mm
Color mapping	Supported

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsijyant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Alignment mode Marker / Global marker / Geometry / Texture

Color supplementary light 12 white LEDs

Outdoor scanning Below 30,000 lux

Minimum scanning range (mm): 5mm x 5mm x 5mm, Accuracy (mm): 0.02, Maximum scanning range (mm): 650mm x 531mm przy 600mm, GPSR Link: https://psr-assets.innpro.pl/creative_technologies/sg_creative_technologies_3d_scanners.pdf, Gross weight: 6600, Box length: 47,00, Box width: 18,00, Box height: 35,50, Net weight: 530

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903