

Allied Telesis AT-IE048-480-20 nepertraukiamo maitinimo resursai (UPS) 480 W

Gamintojas: **ALLIED TELESIS** · Modelis: **AT-IE048-480-20** · EAN: **4511427185417** · Prekės kodas: **375950**



284,89 €

Kaina su PVM

Be PVM: **235,45 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ ☐ Electromagnetic immunity for industrial environments
- ✓ ☐ High efficiency
- ✓ ☐ Active PFC
- ✓ ☐ Stable output power with 150% peak current capability
- ✓ ☐ Wide input voltage range
- ✓ ☐ Protections: peak-current, over-current and over-temperature
- ✓ ☐ Remote ON/OFF
- ✓ ☐ Output power confirmation relay (DC_OK)
- ✓ ☐ Extended operating temperature range
- ✓ ☐ Air convection cooling

Aprašymas

The ruggedized IE048-480 industrial power supply is a functional accessory for Allied Telesis products to build a solution suitable for Smart Cities (e.g. Surveillance & Security), Industrial Ethernet, Transportation or any application requiring systems that function in harsh environment with extended operating temperature.

The IE048-480 is a power supply delivering reliable 480W output power at 48Vdc; it was fully tested and validated to operate with Allied Telesis Industrial products.

Housed in compact metal case with DIN-rail clip, it takes special account of the mechanical robustness, electromagnetic compatibility and thermal characteristics to exhibit the required strengths to work satisfactorily in harsh environment where it will be exposed

Its highly efficient and stable output power has the capability to support 150% of peak load. The nominal output voltage of 48Vdc can be adjusted to match the application requirements.

The AC/DC rectifier operates over the full range of AC input voltage to fit worldwide power grids. The included active Power Factor Correction circuit (PFC) reduces energy costs by eliminating reactive power and harmonics from power lines. Besides the increment of efficiency, PFC is to comply with

international regulations, which established limits on harmonic currents that can appear on the AC main line.

Techninė specifikacija

Savybės	
Išvesties galia	480 W
Išvesties eksploatacinė įtampa (min.)	90 V
Išvesties eksploatacinė įtampa (maks.)	350 V
Įėjimo dažnis	50/60 Hz
Išvesties darbinė įtampa (maks.)	48 V
Maksimali srovė	15 A
Efektyvumas	94%
Galios koeficientas	0,98
Maitinimo apsaugos ypatybės	Viršijus nuolatinę srovę, Apsauga nuo per didelės įtampos, Apsauga nuo perkaitimo
Ryšys	
AC išėjimo tipai	Hardwire
Konstrukcija	
Forma	Tower
Produkto spalva	Balta
Korpuso medžiaga	Metalas
Aušinimo tipas	Aktyvus
LED indikatoriai	Aliarmas, Būsena
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	-20 - 70 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 85 °C
Darbo santykinės drėgmės diapazonas	20 - 90%
Sandėliavimo santykinis drėgmės diapazonas	20 - 90%
Sertifikatai	
Atitikties sertifikatai	RoHS, WEEE
Svoris ir matmenys	
Plotis	70 mm
Ilgis	117 mm
Aukštis	124 mm
Svoris	1,2 kg
Logistikos duomenys	

Eksporto kontrolės klasifikacijos numeris (ECCN)	5A992C
Darniosios sistemos (DS) kodas	8504,40,8500

Kitos savybės

Nominalioji išėjimo įtampa	48 V
Nominali įėjimo įtampa	90 - 264; 98 - 350 V

Matmenys ir svoris

Matmenys (I × P × A)	29,00cm × 22,00cm × 20,00cm
Svoris	1,38kg