



**Mainboard ASUS
Intel B760
Express
LGA1700 Micro-
ATX Memory
DDR4 Memory
slots 2 2xPCI-
Express 4.0 1x
1xPCI-Express
4.0 16x 2xM.2
1x15pin D-sub
1xHDMI 4xUSB
2.0 4xUSB 3.2
1xOptical S/PDIF
3xAudio port
PRIMEB760M-
RD4**

Modelis: PRIMEB760M-RD4

Gamintojas: ASUS

EAN: 4711387423769

Prekės kodas: 375977

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

108.98€

ASUS Prime series motherboards are expertly engineered to unleash the full potential of 14th & 13th Gen Intel® Core™ Processors. Boasting a robust power design, comprehensive cooling solutions and intelligent tuning options, PRIME B760M-R D4 provides users and PC DIY builders with a range of performance optimizations via intuitive software and firmware features.

FLEXIBILITY

Comprehensive controls form the foundation of the ASUS PRIME series. The PRIME B760 motherboard packs flexible tools to tune every aspect of your system, enabling performance tweaks to perfectly match the way you work to maximize productivity.

Intelligent Control

ASUS Intelligent Control makes your PC smart. Along with taking care of complex tuning and dynamically optimizing essential aspects of your system, it offers intelligently simplified options for newcomers to PC DIY, as well as more comprehensive features for seasoned veterans.

All-Around Energy Efficiency

The Power Saving function contains several settings can easily optimize power consumption and maximize energy savings. You can enable a CPU power limit, darken Aura lighting, and set the fan profile to a power saving mode. You can also toggle the Power Saver plan that is built into Microsoft Windows.

Flexible Air-Cooling Controls

ASUS Fan Xpert 2+ software provides comprehensive control over fan. There's an Extreme Quiet mode that reduces fan speeds to below the default minimum to keep your system whisper-quiet when performing light tasks. Fan can also be controlled via the UEFI BIOS.

Precise Digital Power Control

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

The Digi+ voltage-regulator module (VRM) delivers real-time control over voltage droop, automatically switching frequency and power-efficiency settings. It also allows you to fine-tune your CPU for ultimate stability and performance.

UEFI BIOS

The renowned ASUS UEFI BIOS provides everything you need to configure, tweak and tune your system. It offers intelligently simplified options for PC DIY beginners, as well as comprehensive features for seasoned veterans.

Advanced Tuning for Serious Tweakers

An intuitive Advanced mode offered via the UEFI lets you take complete control. A built-in search feature makes it easy to find options, and various advanced functions let you intelligently make nuanced adjustments so you can dial in performance just the way you want.

Quick and Simple Setup

EZ mode displays vital settings and stats and also offers guided wizards, drag-and-drop functionality, and one-click application of important settings — all to help you get your rig up and running in no time.

Intuitive Graphical Fan Control

Fine-tune individual fan settings simply by dragging a curve with the mouse.

Aura On/Off Mode (Stealth)

Easily enable or disable Aura RGB lighting or every onboard LED, for a subdued aesthetic touch.

COOLING

PRIME B760 series are engineered with multiple onboard heatsink and an array of hybrid fan headers to ensure your rig stays cool and stable under intense workloads.

Heatsink

VRM Heatsink and Thermal Pad

VRM heatsink and thermal pad improve heat transfer from the MOSFETs and chocks for better

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

cooling performance.

Cooler by Design

PRIME B760 series features comprehensive cooling controls that are configurable via FAN Xpert 2+ software or via the UEFI BIOS.

Multiple Temperature Sources

Each header can dynamically reference three thermal sensors. FAN Xpert 2+ allows you to map the temperature of supported ASUS graphics cards to optimize cooling for GPU- and CPU-intensive tasks.

4-Pin PWM/DC Fan

Chassis fan headers support auto-detection of PWM or DC fans.

PERFORMANCE

The PRIME B760 series are built to handle the high core counts and bandwidth demands of 14th & 13th Gen Intel® Core™ Processors. ASUS B760 motherboard provides all the fundamentals to boost daily productivity, so your system will be ready for action with stable power, intuitive cooling and flexible data transfer options.

Robust Power Design

Stable power is essential to extract every last bit of performance out of Intel® processors. The PRIME B760M-R D4 is geared to cater to the demands of these high-core-count CPUs.

Memory

DDR4 Support

Improvements to trace routing design provide the latest Intel® processors with enhanced access to memory bandwidth. ASUS technology carefully maps memory signal pathways across different PCB layers to reduce path distance, and it adds shielding zones that significantly reduce crosstalk.

Storage

Two M.2 Slots (up to 64 Gbps)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

The PRIME B760 motherboard offers a total of two M.2 slots that support data-transfer speeds of up to 64 Gbps via PCIe 4.0, enabling quicker boot-up and app load times with OS or application drives.

*Actual transmission speeds will be lower than the theoretical maximum speed.

Connectivity

PCIe 4.0 Slot

The PRIME B760 motherboard is designed specifically for 14th, 13th and 12th Gen Intel® CPUs and offer PCIe 4.0 connectivity for the latest GPUs.

Realtek 2.5 Gb Ethernet

Realtek 2.5 Gb Ethernet reduces CPU overhead and offers exceptionally high TCP and UDP throughput for faster, smoother data transfers.

LANGuard

ASUS LANGuard is a hardware-level network protection feature that integrates advanced signal-coupling technology and premium anti-EMI surface-mounted capacitors to improve throughput and ensure a more reliable connection.

Combined onboard features deliver elevated audio

Intelligent design and premium hardware create audio quality unlike anything you've ever experienced.

Audio Shielding

Audio shielding ensures precision analog/digital separation and greatly reduced multi-lateral interference.

Dedicated Audio PCB Layers

Separate layers for left and right tracks ensures both channels deliver consistent, equal quality.

Premium Audio Capacitors

Provides warm, natural, and immersive sound with exceptional clarity and fidelity.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Aura Sync

Outshine the Competition

A well-tuned enthusiast system deserves a matching aesthetic. ASUS Aura offers full RGB lighting control with a variety of functional presets for the built-in RGB LEDs as well as strips and devices connected to the onboard RGB headers — and it can all be synced with an ever-growing portfolio of Aura-capable hardware.

Addressable Gen 2 Headers

Three Addressable Gen 2 headers are capable of detecting the number of LEDs on second-gen addressable RGB devices, allowing the software to automatically tailor lighting effects to specific devices. The new headers also offer backward-compatibility with existing Aura RGB gear.

TWO-WAY AI NOISE CANCELATION

This utility leverages a massive deep-learning database to reduce background noise from the microphone and incoming audio, while preserving vocals at the same time. This removes distracting keyboard clatter, mouse clicks and other ambient noises so you can hear and be heard with crystal clarity while gaming or in calls.

Armoury Crate

Within a single intuitive interface, Armoury Crate offers easily customized Aura Sync RGB settings for every compatible device in your arsenal, plus controls for an ever-growing family of ASUS products, including keyboard and mouse preferences. Armoury Crate also integrates product registration and a news feed so that you never miss updates of interest to the ASUS community

Q-LED Core

The Q-LED Core display produces light patterns by power LED during the Power-On Self-Test (POST) that can help users troubleshoot potential issues.

SafeSlot Core

SafeSlot Core is the ASUS-exclusive PCIe® slot. Featuring a fortified design that's anchored to the motherboard by a special hook, SafeSlot Core provides 1.6X-stronger retention and 1.3X-greater shearing resistance than standard expansion slots.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Overvoltage Protection

World-class circuit-protecting power design

An exclusive circuit design with built-in voltage regulators to protect your motherboard from damage caused by unexpected high-level voltages from unstable or inferior power supplies.

Stainless-Steel Back I/O

3X corrosion-resistance for greater durability

Corrosion-resistant stainless-steel back I/O panels bonded with chromium oxide have a lifespan that's three times longer than ordinary panels.

- Intel LGA 1700 Socket: Ready for 14th,13th and 12th Gen Intel processors
- Ultrafast Connectivity: PCIe 4.0, two PCIe 4.0 M.2 slots, Realtek 2.5Gb Ethernet and front USB 5Gbps support
- Comprehensive Cooling: VRM heatsink, PCH heatsink, hybrid fan headers and Fan Xpert 2+
- Aura Sync RGB Lighting: Onboard Addressable Gen 2 headers for RGB LED strips, easily synced with Aura Sync-capable hardwares
- Two-Way AI Noise Cancelation: Reduces background noise from the microphone and audio output for crystal-clear communication in games or video conferences

Summary: ASUS PRIME B760M-R D4. Processor manufacturer: Intel, Processor socket: LGA 1700, Compatible processor series: Intel Core i9 14th Gen, Intel Core i3 12th Gen, Intel Core i3 13th Gen, Intel Core i5 12th Gen,.... Supported memory types: DDR4-SDRAM, Maximum internal memory: 64 GB, Memory slots type: DIMM. Supported storage drive interfaces: M.2, SATA III, Supported storage drive types: HDD & SSD, RAID levels: 0, 1, 5, 10. Ethernet interface type: 2.5 Gigabit Ethernet. Component for: PC, Motherboard form factor: micro ATX, Motherboard chipset family: Intel | Vendor Homepage: <https://www.asus.com/motherboards-components/motherboards/prime/prime-b760m-r-d4/> | Audio output channels: 7.1 | Component for: PC | Cooling type: Passive | Motherboard chipset: Intel B760 | Motherboard chipset family: Intel | Motherboard form factor: micro ATX | Power source type: ATX | Product colour: Black | Windows operating systems supported: Windows 10/Windows 11 | Compatible processor series: Intel Core i3 12th Gen/Intel Core i3 13th Gen/Intel Core i5 12th Gen/Intel Core i5 13th Gen/Intel Core i7 12th Gen/Intel Core i7 13th Gen/Intel Core i9 12th Gen/Intel Core i9 13th Gen/Intel Core i9 14th Gen | Processor manufacturer: Intel | Processor socket: LGA 1700 | Supported processor sockets: LGA 1700 | ECC compatibility: Non-ECC | Maximum internal memory: 64 | Memory channels: Dual-channel | Memory slots type: DIMM | Number of memory slots: 2 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Supported memory clock speed (max): 5333 | Supported memory clock speeds: 2133/2400/2666/2800/2933/3000/3200/3333/3400/3466/3600/3733/4000/4266/4400/4600/4800/5000/5066 | Supported memory types: DDR4-SDRAM | Unbuffered memory: Yes | Number of HDDs supported: 4 | Number of storage drives supported: 6 | RAID levels: 0/1/10/5 | RAID support: Yes | Supported storage drive interfaces: M.2,SATA III | Supported storage drive types: HDD & SSD | Parallel processing technology support: Not supported | 12V power connector: Yes | ATX Power connector (24-pin): Yes | CPU fan connector: Yes | EPS power connector (8-pin): Yes | Front panel audio connector: Yes | Number of chassis fan connectors: 2 | Number of COM connectors: 1 | Number of SATA III connectors: 4 | RGB LED pin header: Yes | TPM connector: Yes | USB 2.0 connectors: 2 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 1 | Ethernet LAN (RJ-45) ports: 1 | HDMI ports quantity: 1 | HDMI version: 2.1 | Headphone outputs: 1 | Line-in: Yes | USB 2.0 ports quantity: 4 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Ethernet interface type: 2.5 Gigabit Ethernet | Ethernet LAN: Yes | Wi-Fi: No | Number of M.2 (M) slots: 2 | PCI Express x1 (Gen 4.x) slots: 2 | PCI Express x16 (Gen 4.x) slots: 1 | BIOS memory size: 128 | BIOS type: UEFI AMI | Package depth: 263 | Package height: 51.5 | Package weight: 903 | Package width: 270 | Depth: 211 | Width: 244 | Cables included: SATA | Model: PRIME B760M-R D4 | Units per Shipping Box: 10 | Unit Calculated Volume: 0.003869 | Unit Calculated Weight: 0.98

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903