



Zyxel GS1200-8V3 Managed L2 Gigabit Ethernet (10/100/1000) Desktop Grey



Modelis: GS1200-8V3-EU0101F

Gamintojas: ZYXEL

EAN: 4718937649945

Prekės kodas: 376072

30.00€

Certification: CE-LVD, BSMI CE, EAC, FCC, BSMI Class B | Form factor: Desktop | Switch type: Managed | IGMP snooping: Yes | Width: 193 mm | AC input voltage: 100 - 240 V | Heat dissipation: 13 BTU/h | Weight: 268 g | Rack mounting: No | Switching capacity: 16 Gbit/s | Switch layer: L2 | LED indicators: Yes | Mean time between failures (MTBF): 1266805 h | Power over Ethernet (PoE): No | Power consumption (max): 3.81 W | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | DHCP features: DHCP client | Operating temperature (T-T): 0 - 50 °C | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Storage relative humidity (H-H): 10 - 95% | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Product colour: Grey | Networking standards: IEEE 802.3u | Power connector: DC-in jack | Virtual LAN features: Port-based VLAN | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Port mirroring: Yes | Web-based management: Yes | MAC address table: 4000 entries | 10G support: No | AC input frequency: 50/60 Hz | Networking standards: IEEE 802.3az

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| Full duplex: Yes | Copper ethernet cabling technology: 1000BASE-T | Power source: AC | Depth: 85 mm | Multicast support: Yes | Height: 26 mm | Password protection: Yes | VLAN support: Yes | Number of multicast groups filtered: 128 | Stackable: No | Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Basic switching RJ-45 Ethernet ports quantity: 8 | Packet buffer memory: 0.192 MB | Forwarding rate: 11.9 Mpps | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Networking standards: IEEE 802.3ad | Fanless: Yes | Jumbo frames: 15 | Jumbo frames support: Yes | Broadcast storm control: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903