



Zyxel GS1200-5HPV3 Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Desktop Grey



Modelis: GS1200-5HPV3-EU0101F

Gamintojas: ZYXEL

EAN: 4718937649815

Prekės kodas: 376074

54.99€

Certification: CE-LVD, BSMI CE, EAC, FCC, BSMI Class B | Power connector: DC-in jack | Rack mounting: No | Form factor: Desktop | Depth: 85 mm | Power over Ethernet (PoE): Yes | Weight: 274 g | Switching capacity: 10 Gbit/s | Packet buffer memory: 0.192 MB | Jumbo frames support: Yes | Password protection: Yes | Power consumption (max): 4.153 W | Width: 155 mm | MAC address table: 4000 entries | Broadcast storm control: Yes | Total Power over Ethernet (PoE) budget: 68 W | Power over Ethernet (PoE) ports quantity: 4 | IGMP snooping: Yes | Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Basic switching RJ-45 Ethernet ports quantity: 5 | DHCP features: DHCP client | Forwarding rate: 7.44 Mpps | Fanless: Yes | Operating temperature (T-T): 0 - 50 °C |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

10G support: No | Copper ethernet cabling technology: 1000BASE-T | Power source: AC/PoE | VLAN support: Yes | Number of multicast groups filtered: 128 | Multicast support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Switch type: Managed | Full duplex: Yes | Mean time between failures (MTBF): 1730334 h | Heat dissipation: 44.788 BTU/h | Height: 26 mm | Port mirroring: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Jumbo frames: 15 | Storage relative humidity (H-H): 10 - 95% | Virtual LAN features: Port-based VLAN | Switch layer: L2 | Stackable: No | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | AC input frequency: 50/60 Hz | Product colour: Grey | LED indicators: Yes | AC input voltage: 100 - 240 V | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3az | Web-based management: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ad

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903