



Zyxel GS1200-8HPV3 Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Desktop Grey



Modelis: GS1200-8HPV3-EU0101F

Gamintojas: ZYXEL

EAN: 4718937649907

Prekės kodas: 376075

58.99€

Certification: CE-LVD, BSMI CE, EAC, FCC, BSMI Class B | Weight: 337 g | Power over Ethernet (PoE): Yes | LED indicators: Yes | Product colour: Grey | AC input voltage: 100 - 240 V | Storage temperature (T-T): -40 - 70 °C | AC input frequency: 50/60 Hz | MAC address table: 4000 entries | Switch layer: L2 | Form factor: Desktop | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3at | Packet buffer memory: 0.192 MB | IGMP snooping: Yes | Width: 193 mm | Power source: AC/PoE | Virtual LAN features: Port-based VLAN | Depth: 85 mm | Multicast support: Yes | Operating temperature (T-T): 0 - 50 °C | Power consumption (max): 81.27 W | Fanless: Yes | DHCP features: DHCP client | Rack mounting: No | Switching capacity: 16 Gbit/s | Height: 26 mm | Full duplex: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Stackable: No | Web-based management: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Mean time between failures (MTBF): 1749682 h | Heat dissipation: 45.279 BTU/h | Switch type: Managed | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Power over Ethernet (PoE) ports quantity: 4 | Networking standards: IEEE 802.3ad | VLAN support: Yes | Number of multicast groups filtered: 128 | Password protection: Yes | Power connector: DC-in jack | Quality of Service (QoS) support: Yes | Port mirroring: Yes | Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | 10G support: No | Networking standards: IEEE 802.3az | Jumbo frames support: Yes | Copper ethernet cabling technology: 1000BASE-T | Forwarding rate: 11.9 Mpps | Storage relative humidity (H-H): 10 - 95% | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Jumbo frames: 15 | Total Power over Ethernet (PoE) budget: 68 W | Broadcast storm control: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903