



# HIKVISION DS- 2CD2087G3- LI2UY/SL 2.8mm IP CAMERA



Modelis: DS-2CD2087G3-LI2UY/SL 2.8mm

Gamintojas: HIKVISION

EAN: 6936422132965

Prekės kodas: 376383

## 300.99€

Operating temperature (T-T): -30 - 60 °C | Ethernet LAN (RJ-45) ports: 1 | Total megapixels: 8 MP |  
Built-in microphone: Yes | Detect distance (wide): 89 m | Bit rate control: Constant Bit Rate  
(CBR)/Variable Bit Rate (VBR) | Quality of Service (QoS) support: Yes | Ethernet LAN data rates:  
10,100 Mbit/s | Optical sensor size: 25.4 / 1.8 mm (1 / 1.8") | Maximum resolution: 3840 x 2160  
pixels | Ethernet LAN: Yes | Angle of rotation: 360° | Type: IP security camera | Package width: 234  
mm | Progressive scan: Yes | Product colour: White | Package depth: 120 mm | Compatible memory  
cards: MicroSD (TransFlash) | Package weight: 815 g | Highlight Compensation (HLC): Yes |  
Compatible memory cards: MicroSDXC | Signal-to-Noise Ratio (SNR): 52 dB | Form factor: Bullet | Bit  
rate: 32 Kbps - 16 Mbps | Camera shutter speed: 1/3 - 1/100000 s | Ethernet interface type: Fast  
Ethernet | International Protection (IP) code: IP67 | Length: 176.3 mm | Power over Ethernet (PoE):  
Yes | Housing material: Metal | Tilt angle range: 0 - 90° | Operating relative humidity (H-H): 0 - 95% |  
Package height: 117 mm | Diameter: 7.44 cm | Number of cameras: 1 | Night vision distance: 40 m |  
Storage relative humidity (H-H): 0 - 95% | Storage temperature (T-T): -30 - 60 °C | Wide Dynamic  
Range (WDR): 130 dB | Compatible memory cards: MicroSDHC | Pan range: 0 - 360° | Weight: 530 g |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

LED type: IR | Warnings: The product contains electronic components do not dispose of with the normal household waste. | Placement supported: Outdoor | Night vision: Yes | Sustainability certificates: RoHS | Lens viewing angle, vertical: 56.4° | DC output current: 1.25 A | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Mounting type: Ceiling/wall | Region of Interest (ROI) encoding: Yes | Number of lenses: 1 | IP address filtering: Yes | Infra-red wavelength: 850 nm | Identify distance (wide): 8 m | Lens viewing angle, horizontal: 108.8° | Recognize distance (wide): 17 m | Password protection: Yes | Maximum memory card size: 512 GB | Mirror: Yes | Sample rate: 8 kHz /16 kHz /32 kHz / 48 kHz | Heartbeat: Yes | Number of users: 32 user(s) | Video motion detection: Yes | Observe distance (wide): 35 m | Video compression formats: H.265 | Lens viewing angle, diagonal: 134.3° | Noise filter: Y | Behavior analysis: Intrusion detection, Line crossing detection, Region entrance detection, Region exiting detection | PoE standard: IEEE 802.3af | Maximum aperture number: 1 | Video compression formats: H.265+ | Video compression formats: H.264+ | Sensor type: CMOS | Power management: DC 12 V | Video compression formats: H.264 | Day/night mode: Yes | Video compression formats: M-JPEG | Number of sensors: 1

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903