



MSI B550M PRO-VDH AMD B550 Socket AM4 micro ATX

Modelis: 7C95-017R

Gamintojas: MSI

EAN: 4719072758417

Prekės kodas: 376636

93.99€

Compatible processor series: 3rd Generation AMD Ryzen™ 9 | DisplayPorts quantity: 1 | Supported memory clock speeds: 1866 | Motherboard form factor: micro ATX | Supported memory clock speeds: 3200 MHz | Supported memory clock speeds: 4266 | Maximum resolution: 4096 x 2160 pixels | Supported memory clock speeds: 2667 | Supported memory clock speeds: 3733 | Supported memory clock speeds: 4400 | Supported memory clock speeds: 3066 | Supported memory clock speeds: 3000 | VGA (D-Sub) ports quantity: 1 | Number of memory slots: 4 | Unbuffered memory: Yes | Processor socket: Socket AM4 | USB 2.0 ports quantity: 2 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 1 | Compatible processor series: AMD Ryzen™ 5 | LAN controller: Realtek 8111HN | Compatible processor series: AMD Ryzen™ 7 | Serial port headers: 1 | Processor manufacturer: AMD | Supported memory clock speeds: 3466 | Supported memory clock speeds: 2400 | Supported memory clock speeds: 2800 | Supported memory types: DDR4-SDRAM | RAID levels: 0 | Chassis intrusion connector: Yes | HDMI ports quantity: 1 | Supported memory clock speeds: 2933 | Supported memory clock speeds: 3600 | Wi-Fi: No | Number of M.2 (M) slots: 2 | 12V power connector: Yes |

Motherboard chipset: AMD B550 | RAID levels: 1 | Ethernet LAN (RJ-45) ports: 1 | Drivers included:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be

išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Yes | ATX Power connector (24-pin): Yes | Supported storage drive interfaces: Serial ATA III | USB 2.0 connectors: 2 | PCI Express x1 (Gen 3.x) slots: 2 | RAID levels: 10 | PCI Express x16 (Gen 4.x) slots: 1 | Parallel processing technology support: Not supported | Number of SATA III connectors: 4 | RGB LED pin header: Yes | Memory channels: Dual-channel | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Cables included: SATA | Supported memory clock speeds: 4133 | Supported memory clock speeds: 4000 | Supported memory clock speeds: 3866 | Maximum internal memory: 128 GB | Audio output channels: 7.1 channels | Supported memory clock speeds: 2133 | Ethernet LAN: Yes | Ethernet interface type: Gigabit Ethernet | Depth: 244 mm | Clear CMOS jumper: Yes | HDMI version: 2.1 | TPM connector: Yes | Memory slots type: DIMM | Front panel connector: Yes | CPU fan connector: Yes | Front panel audio connector: Yes | Motherboard chipset family: AMD | Number of chassis fan connectors: 3 | Width: 244 mm | Supported storage drive types: HDD & SSD | Maximum number of SMP processors: 1