Foscam D4Z Bulb IP security camera Indoor & outdoor 2304 x 1536 pixels Ceiling

Modelis: D4Z-B

Gamintojas: FOSCAM

EAN: 6954836045961

Prekės kodas: 376662

152.99€

Maximum memory card size: 128 GB | Number of lenses: 1 | Motion sensor: Yes | Number of illumination LEDs: 2 | Night vision distance: 20 m | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Intelligent Video Surveillance (IVS) system features: Human detection | PTZ control: Yes | Web browser: Yes | Frame rate: 20 fps | Pan range: 0 - 350° | Maximum aperture number: 2.8 | Optical zoom: 4x | Video compression formats: H.264 | LED type: IR | Height: 102 mm | Number of cameras: 1 | IK code: IK10 | Built-in HDD: No | Total megapixels: 4 MP | DC output voltage: 12 | Wi-Fi: Yes | Weatherproof: Yes | Focal length range: 12 mm | Video streaming: Yes | Wide Dynamic Range (WDR): Yes | Zoom capability: Yes | Placement supported: Indoor & outdoor | Audio input channels: 2.0 channels | Camera pan control: Yes | Mounting type: Ceiling | Minimum illumination: 0 lx | Minimum aperture number: 1.4 | Camera tilt control: Yes | IP address filtering: Yes | Sensor type: CMOS | Depth: 108 mm | Ethernet LAN: Yes | DC output current: 2 A | Night vision: Yes | Supported

network protocols: IP, TCP, UDP, HTTP, HTTPS, SMTP, FTP, DHCP, RTSP, ONVIF | Warnings: The product contains electronic components do not dispose of with the normal household waste. | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Lens viewing angle, horizontal: 32 - 100° | Lens viewing angle, vertical: 40 - 130° | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 2304 x 1296 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Power consumption (typical): 20 W | Maximum resolution: 2304 x 1536 pixels | Product colour: Black | Operating temperature (T-T): -20 - 50 °C | Web-based management: Yes | Reset button: Yes | Weight: 518 g | Ethernet LAN (RJ-45) ports: 1 | Type: IP security camera | Security algorithms: WPA2 | Security algorithms: WPA | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11b | Storage relative humidity (H-H): 0 - 90% | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Operating relative humidity (H-H): 20 - 85% | Storage temperature (T-T): -20 - 50 °C | Compatible memory cards: MicroSD (TransFlash) | Width: 108 mm | Connectivity technology: Wired & Wireless | Power source type: DC | Form factor: Bulb | Tilt angle range: 0 - 85° | International Protection (IP) code: IP66