



Cloud Router Switch CRS310- 1G-5S-4S+IN No Wi-Fi 10/100/1000 Mbit/s Ethernet LAN (RJ-45) ports 1 Mesh Support No MU- MiMO No No mobile broadband

Modelis: CRS310-1G-5S-4S+IN

Gamintojas: MIKROTIK

EAN: 4752224007827

Prekės kodas: 377231

165.99€

Gross depth (mm): 240.00 | Gross height (mm): 60.00 | Gross weight: 1.68 | Gross width (mm):

320.00 | Net weight: 1.20 | Packing quantity: 1.00 | Paper/Pasteboard: 427.00 | Plastic (No PET):

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be

išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

48.00 | Tare weight (kg): 0.48 | Volume (m3): 0.00 | Embeeded battery: No | WEEE tax: Yes | WEE classification: CL109:6:2017-04-01 | Switch type: Managed L3 | Form factor: Rackmountable | Producer product name: CRS310-1G-5S-4S+IN | Producer product family: Cloud Router Switch | POE: PoE passive | Predominant port type: 10/100/1000 Mbps (RJ-45) | SFP+ ports quantity: 4 | Ethernet LAN data rates: 10/100/1000 | Ethernet LAN (RJ-45) ports: 1 | Wi-Fi band: No Wi-Fi | Mesh Support: No | Mobile Broadband: No mobile broadband | MU-MIMO: No | Operating system installed: RouterOS | Other features: This switch is an indoor variation of the prominent netFiber 9 switch – used by many small and medium ISPs for reliable 10 Gigabit fibre connections stretching over a 100 meters. With five 1G SFP ports, four 10G SFP+ ports, and an additional Gigabit Ethernet port, this is the perfect upgrade for existing CRS212 setups. You're getting the modern ARM v7 CPU, 256 MB of RAM, and better cooling. The new Marvell switch-chips bring phenomenal performance to the table! The Gigabit Ethernet port has a direct connection to the switch chip – so you can enjoy full gigabit speed there. And it supports PoE-in, giving you an additional powering option in tricky spots. You can mount this switch in a standard 1U rack to keep everything organized. And it has all the power you would expect from a rackmount device: CRS310 supports hardware offloaded VLAN- filtering. And even some hardware offloaded Layer-3 routing. CRS310-1G-5S-4S+IN is a fantastic tool for anyone working with indoor connections over 100 meters while keeping data loss and ping low. Optical fiber can be a great alternative to copper if you are worried about electromagnetic interference, tampering or eavesdropping. | SFP ports quantity: 5 | Voltage: 18-57 | Processor model: 98DX226S | PoE in: 802.3af/at | CPU frequency: 800 MHz | Software type: RouterOS | Power consumption (max): 20 | Storage capacity: 16 | Operating temperature (T-T): -40°C to 70°C | Palette Qty: 188 | Producer: MikroTik | Warranty: 12

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903