

HP ScanJet Pro 4200 s1 ADF skeneris 600 x 600 DPI A4 Mėlyna, Balta

Gamintojas: **HP INC.** · Modelis: **8Q4W2A#B19** · EAN: **198701401049** · Prekės kodas: **377533**



573,90 €

Kaina su PVM

Be PVM: **474,30 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ ADF; Sheetfed
- ✓ Up to 600 dpi
- ✓ Paper (banner, brochure, inkjet, plain), photo paper (borderless, HP premium, panoramic, plus tab), envelopes, labels, cards (greeting, index), ID cards, passport
- ✓ 1 light (Error); 3 button (Power, Scan, Cancel)
- ✓ 4.6 watts (ready), 1.15 watts (sleep), 0.065 watts (off)
- ✓ Recommended daily duty cycle: 4500 pages
- ✓ One default scan mode on front-panel for HP scan in Win OS, HP Easy Scan/ICA in Mac OS and third parties applications via TWAIN.

Aprašymas

Compact. Versatile. Pro performance. Stay ahead of the demands of your business using the HP ScanJet Pro 4200 s1. Zip through front-desk paperwork with workflow automation and scan a variety of documents from passports to invoices with exceptional clarity—all in a compact design.

Techninė specifikacija

Scanning

Optical scanning resolution	600 x 600 DPI
Duplex scanning	Yes
Colour scanning	Yes
Greyscale levels	256

Design

Scanner type	ADF scanner
Control type	Buttons
Performance	
Sensor type	CIS
Scan to	USB, File
Scan drivers	ICA, TWAIN
Internal memory	512 MB
Processor frequency	666 MHz
HP segment	Business
Input capacity	
Auto document feeder (ADF) input capacity	50 sheets
Ports & interfaces	
USB port	Yes
Power	
Power consumption (off)	0.065 W
AC input frequency	50/60 Hz
Power consumption (sleep)	1.15 W
Weight & dimensions	
Width	305 mm
Depth	107 mm
Height	128 mm
Weight	2 kg
Packaging data	
Package width	393 mm
Package depth	196 mm
Package height	291 mm
Package weight	4.25 kg
Packaging content	
Cables included	USB
Bundled software	HP Scan Software, HP Scanner Tools Utility, HP Scan Assistant, HP WIA scan driver, HP TWAIN scan driver, ISIS driver ICA driver, HP Easy Scan for Mac OS, HPUI Scan for Linux
Sustainability	
Sustainability certificates	ENERGY STAR, EPEAT, Forest Stewardship Council (FSC)
Total carbon footprint (kg of CO2e)	600

System requirements

Minimum system requirements	Microsoft Windows 11, 10, 8.1, 2008 R2, 2012 R2, 2016, 2019; 2 GB available hard disk space, Internet Required, Web Browser, USB
Compatible operating systems	Windows 11; Windows 10; Windows 8.1; Windows Server; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; macOS 13 Ventura; macOS 14 Sonoma; macOS 15 Sequoia; Linux
Windows operating systems supported	Windows 8, Windows 8.1, Windows 10, Windows 11
Mac operating systems supported	Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma, MacOS

Operational conditions

Operating temperature (T-T)	10 - 35 °C
Storage temperature (T-T)	-40 - 60 °C

Certificates

Electromagnetic compatibility	EN 55032:2015 +A11:2020 EN 55035:2017 +A11:2020 EN 61000-3-2:2014 EN 61000-3-2:2019 +A1:2021 EN 61000-3-3:2013 +A2:2021 CISPR 32:2015 +AMD1:2019 CISPR 32:2019 ED2.1 EN 301 489-1 V2.2.3 EN 301 489-17 V3.2.4 FCC CFR 47 Part 15 ICES-003, Issue 7
-------------------------------	--

Other features

Recommended system requirements	Microsoft Windows 11; 10; 8.1; 2008 R2; 2012 R2; 2016; 2019; 2 GB available hard disk space; Internet Required; Web Browser; USB. macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; macOS 13 Ventura; macOS 14 Sonoma; Internet Required; USB.
Media types supported	Paper (banner, brochure, inkjet, plain), photo paper (borderless, HP premium, panoramic, plus tab), envelopes, labels, cards (greeting, index), ID cards, passport
Image formats supported	BMP, JPEG, PNG, TIFF
Maximum scan resolution	1200 x 1200 DPI
Certification	EN 55032:2015 +A11:2020 EN 55035:2017 +A11:2020 EN 61000-3-2:2014 EN 61000-3-2:2019 +A1:2021 EN 61000-3-3:2013 +A2:2021 CISPR 32:2015 +AMD1:2019 CISPR 32:2019 ED2.1 EN 301 489-1 V2.2.3 EN 301 489-17 V3.2.4 FCC CFR 47 Part 15 ICES-003, Issue 7
Recommended humidity operating range	30 - 70%
Recommended operating temperature range (T-T)	17.5 - 25 °C
UNSPSC-code	43211711
Box contents	Power adapter; USB cable; User Guide; regulatory flyer

Logistics data

Country of origin	China, Taiwan
Master (outer) cases per pallet layer	15 pc(s)
Harmonized System (HS) code	8471608000

Matmenys ir svoris

Matmenys (I × P × A)	39,00cm × 29,00cm × 20,00cm
Svoris	3,86kg