Switch UBIQUITI Type L3 400 Watts USW-PRO-XG-10-POE

Modelis: USW-PRO-XG-10-POE

Gamintojas: UBIQUITI

EAN: 810177160137

Prekės kodas: 379154

680.00€

1U, professional-grade 10-port, Layer 3 Etherlighting™ PoE+++ switch with (10) 10 GbE and (2) 10G SFP+ ports.

Summary: Ubiquiti UniFi Pro XG 10 PoE. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 10. MAC address table: 32000 entries, Switching capacity: 240 Gbit/s. Power connector: AC/DC. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: https://eu.store.ui.com/eu/en/category/switching-professional-max-xg/products/usw-pro-xg-10-poe | Quality of Service (QoS) support: Yes | Switch layer: L2/L3 | Switch type: Managed | 10G Ethernet (copper) ports quantity: 10 | Basic switching RJ-45 Ethernet ports quantity: 10 | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Power connector: AC/DC | SFP+ module slots quantity: 2 | 10G support: Yes | Broadcast storm control: Yes | Flow control support: Yes | IPv4 routes: 12000 | Number of VLANs: 1000 | Port mirroring: Yes | Rate limiting: Yes | Virtual LAN features: Interface-based VLAN/Voice VLAN | VLAN support: Yes | Forwarding rate: 179 | Jumbo

frames support: Yes | MAC address table: 32000 | Packet buffer memory: 2 | Static route: Yes | Switching capacity: 240 | Throughput: 120 | DHCP features: DHCP guarding/DHCP relay/DHCP server/DHCPv6 snooping | IGMP snooping: Yes | Loop protection: Yes | Multicast support: Yes | Backlight display: Yes | Display type: LCM | Form factor: 1U | Housing material: SGCC | LED indicators: System | Product colour: Grey | Rack mounting: Yes | Reset button: Yes | Stackable: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Power consumption (max): 520 | Power source: AC/DC | Power supply included: Yes | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 15.4 | Power over Ethernet (PoE) type supported: PoE++ (4PPoE) | Power over Ethernet 4PPoE (PoE++) ports quantity: 10 | Total Power over Ethernet (PoE) budget: 400 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 40 | Depth: 285 | Height: 44 | Weight: 4600 | Width: 442.4 | Cables included: Power | Manual: Yes | Rack mount kit: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC)/National Defense Authorization Act (NDAA) | Model: USW-PRO-XG-10-POE | Units per Pallet: 0 | Units per Shipping Box: 2 | Unit Calculated Volume: 0.02894 | Unit Calculated Weight: 6.25