CABLE DISPLAY PORT TO HDMI 2M/36922 LINDY

Modelis: 36922

Gamintojas: LINDY

EAN: 4002888369220

Prekės kodas: 37927

16.99€

The Lindy DisplayPort to HDMI Cable is ideal for connecting a DisplayPort equipped source such as a PC or laptop to an HDMI display. Supporting 4K UHD resolutions up to 3840x2160@30Hz, this cable is ideal for ensuring video is displayed in superior clarity. This cable can also be used to add another display to extend the available desktop workspace and increase productivity, great for use in residential or workplace office setups.

The DisplayPort to HDMI Cable supports uncompressed 7.1 Audio and compressed Audio such as DTS-HD Master Audio, Dolby TrueHD. Please note that audio output over HDMI is only supported when the graphics card of the laptop or desktop computer supports audio output over DisplayPort.

- Connects a DisplayPort equipped device to a 4K UHD HDMI display or projector
- Supports resolutions up to 3840x2160@30Hz
- Supports video mirroring and extended desktop modes
- Audio pass-through if supported by the video source

- 2 year warranty

Summary: Lindy 2m DisplayPort to HDMI 10.2G Cable. Cable length: 2 m, Connector 1: DisplayPort, Connector 2: HDMI Type A (Standard). Certification: CE, UKCA, FCC, RoHS, REACH, UL, California. Cable diameter: 7.3 mm, Connector 1 dimensions (WxDxH): 36.4 x 20.5 x 9.4 mm, Connector 2 dimensions (WxDxH): 37.5 x 20.5 x 10.5 mm. Package type: Polybag. Quantity per pack: 1 pc(s) | Vendor Homepage: https://www.lindy.co.uk/2m-displayport-to-hdmi-10-2g-cable-p10038 | AWG wire size: 28 | Bend radius (min): 73 | Cable length: 2 | Cable shielding: Aluminium braid | Cable type: Round cable | Colour depth: 8 | Colour sampling: 4:4:4 | Conductor material: Tinned copper | Connector 1: DisplayPort | Connector 1 form factor: Straight | Connector 1 gender: Male | Connector 2: HDMI Type A (Standard) | Connector 2 form factor: Straight | Connector 2 gender: Male | Connector contacts plating: Gold | Connector housing material: Polyvinyl chloride (PVC) / Acrylonitrile butadiene styrene (ABS) | Connector material: Gold | Contact material: Copper | Data transfer rate: 10.2 | DisplayPort version: 1.2 | HDMI version: 1.4 | Jacket material: Polyvinyl chloride (PVC) | Maximum refresh rate: 30 | Maximum resolution: 3840 x 2160 | Nominal attenuation: 100MHz~450MHz -2.44--5.099dB 450MHz~8100MHz -5.094~32.906dB | Product colour: Black | Supported graphics resolutions: 3840 x 2160 | Supported video modes: 1080p | Operating temperature (T-T): 0 - 45 | Storage temperature (T-T): -10 - 80 | Certification: CE, UKCA, FCC, RoHS, REACH, UL, California | Cable diameter: 7.3 | Connector 1 dimensions (WxDxH): 36.4 x 20.5 x 9.4 | Connector 2 dimensions (WxDxH): 37.5 x 20.5 x 10.5 | Package type: Polybag | Quantity per pack: 1 | Harmonized System (HS) code: 84733080 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.0005437 | Unit Calculated Weight: 0.15