



CABLE USB-C TO DP 1.8M/RVC- DPC AXAGON



Modelis: RVC-DPC

Gamintojas: AXAGON

EAN: 8595247905314

Prekės kodas: 37950

15.98€

Active USB-C -> DisplayPort cable - adapter AXAGON RVC-DPC for connecting a DisplayPort monitor/TV/projector to a notebook or mobile phone using USB type C connector.

A hardware converter ensures quality image up to 4K/60Hz Ultra HD resolution without any installation. Video and audio transfer from a computer, laptop, phone or Apple MacBook will now be easy.

Compact dimensions provide the possibility to use the cable in insufficient space. The converter dimensions are almost identical to the standard cable connectors. You have an ideal solution - you don't need a cable and converter, with this active cable everything is integrated into one compact unit.

The cable is only oneway, i.e. USB-C to DP, not otherwise . A USB-C port with DisplayPort Alternate Mode (DP Alt Mode) support of a device with Thunderbolt 3 port is required for the cable to function

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

properly.

Input:

- USB-C
- USB type C (M) male connector

Output:

- DisplayPort 1.2
- DP connector with latch (M) male
- connector latch control button

Supported resolutions:

- max. 4096 x 2160 (19:10) @60Hz DCI 4K
- 3840 x 2160 (16:9) @60Hz UHD-1 4K (UHDTV)
- 3840 x 1600 (21:9) UW 4K (Ultrawide 1600p)
- 3840 x 1200 (32:10) 29:9 4K (Super ultrawide 1200p)
- 3840 x 1080 (32:9) 32:9 4K (Super ultrawide 1080p)
- 3440 x 1440 (21:9) UWQHD (Ultrawide 1440p)
- 2560 x 2048 (5:4) QSXGA
- 2560 x 1920 (4:3)
- 2560 x 1600 (16:10) WQXGA
- 2560 x 1440 (16:9) QHD
- 2560 x 1080 (21:9) UWFHD (Ultrawide 1080p)
- 2048 x 1536 (4:3) QXGA
- 2048 x 1152 (16:9) QWXGA
- 1920 x 1440 (4:3)
- 1920 x 1200 (16:10) WUXGA
- 1920 x 1080 (16:9) Full HD/1080p
- 1856 x 1392 (4:3)
- 1792 x 1344 (4:3)
- 1680 x 1050 (16:10) WSXGA+
- 1600 x 1200 (4:3) UXGA
- 1600 x 900 (16:9) HD+

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- 1536 x 864 (16:9)
- 1440 x 900 (16:10) WXGA+
- 1400 x 1050 (4:3) SXGA+
- 1366 x 768 (16:9) HD
- 1360 x 768 (16:9) HD
- 1280 x 1024 (5:4) SXGA
- 1280 x 960 (4:3) SXGA-
- 1280 x 800 (16:10) WXGA
- 1280 x 768 (5:3) WXGA
- 1280 x 720 (16:9) HD/WXGA/720p
- 1280 x 600
- 1152 x 864 (4:3) XGA+
- 1024 x 768 (4:3) XGA
- 800 x 600 (4:3) SVGA

* the resolution depends on monitor/TV/projector and graphics adapter parameters.

Other features:

- Supported modes: mirroring the desktop (default setting), extending the desktop,
- HPD (Hot-Plug-Detect) support - communication sequence controlling the connection/disconnection of the device while running,
- Support up to 8-channel sound - 96 kHz at 24 bits,
- Compliant with USB Type-C Cable and Connector Specification Revision 1.1 specification,
- Compliant with VESA DisplayPort Alt Mode on USB Type-C Standard Version 1.0 specification,
- Compliant with USB Device Class Definition for Billboard Devices Revision 1.0 specification,
- HDCP 2.2 (High-bandwidth Digital Content Protection) support - a mechanism used to protect the digital contents,
- Support of power saving modes with spinning down controlled by a source device (PC) and a viewing device (monitor/TV),
- Power supply via USB-C - no external power is needed,
- Dimensions of converter body 47 x 22 x 10 mm,
- Total length cable incl. connector 185 cm,
- Weight only 71 g,
- Operating temperature: 0 ~ 45°C,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Storage temperature: -10 ~ 70°C.

Supported OSs:

- Microsoft Windows 10, macOS, Android and Chrome OS – updated.
- Compatibility depends on the operating system and device manufacturer support.

Package contains:

- USB-C > DP cable 1.8m length,
- printed multilingual manual CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / BG / CN / TR / ARA,
- packed in a cardboard box.

Summary: Axagon RVC-DPC USB-C -> DisplayPort cable 1.8m 4K/60Hz. Cable length: 1.8 m, Connector 1: USB Type-C, Connector 2: DisplayPort. Compliance certificates: RoHS, CE, Certification: CE, RoHS. Weight: 71 g. Package width: 180 mm, Package depth: 90 mm, Package height: 30 mm. Quantity per pack: 1 pc(s) | Vendor Homepage: <https://www.axagon.eu/en/produkty/rvc-dpc> | Cable length: 1.8 | Connector 1: USB Type-C | Connector 1 form factor: Straight | Connector 1 gender: Male | Connector 2: DisplayPort | Connector 2 form factor: Straight | Connector 2 gender: Male | Converter type: Active video converter | Country of origin: China | DisplayPort version: 1.2 | HDCP: Yes | HDCP version: 2.2 | Mac operating systems supported: Yes | Maximum refresh rate: 240 | Maximum resolution: 4096 x 2160 | Other operating systems supported: Android | Plug and Play: Yes | Product colour: Black | Refresh rate at maximum resolution: 60 | Windows operating systems supported: Yes | Certification: CE, RoHS | Compliance certificates: CE/RoHS | Weight: 71 | Package depth: 90 | Package height: 30 | Package type: Box | Package weight: 105 | Package width: 180 | Manual: Yes | Quantity per pack: 1 | Model: RVC-DPC | Units per Shipping Box: 1 | Unit Calculated Volume: 0.000486 | Unit Calculated Weight: 0.11