



CABLE DP TO HDMI 1.8M/RVD- HI14C2 AXAGON



Modelis: RVD-HI14C2

Gamintojas: AXAGON

EAN: 8595247906083

Prekės kodas: 38008

13.00€

DisplayPort -> HDMI active cable - adapter AXAGON RVD-HI14C2 to connect HDMI monitor/TV/projector to the computer with the DisplayPort output.

The smart hardware converter without the need for any installation or setup ensures high-quality transfer of image and sound with a resolution up to 4K/30Hz.

Video and audio transfer from a computer or laptop will now be easy. Compact dimensions ensures easy use even in insufficient space. It is an ideal solution - you don't need a HDMI cable and converter. With this active cable everything is integrated into one compact unit.

The cable is only one-way, i.e. DisplayPort to HDMI, not otherwise.

Input:

- DisplayPort v1.2

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- DP male connector with latch (M)
- connector latch control button

Output:

- HDMI v1.4b
- HDMI A (M) male connector

Supported resolutions:

Resolution and frequency depend on monitor and graphics adapter.

- max. 4096 x 2160 (19:10) @30Hz DCI 4K
- 3840 x 2160 (16:9) @30Hz UHD-1 4K (UHDTV)
- 3840 x 1600 (21:9) UW 4K (Ultrawide 1600p)
- 3840 x 1200 (32:10) 29:9 4K (Super ultrawide 1200p)
- 3840 x 1080 (32:9) 32:9 4K (Super ultrawide 1080p)
- 3440 x 1440 (21:9) UWQHD (Ultrawide 1440p)
- 2560 x 2048 (5:4) QSXGA
- 2560 x 1920 (4:3)
- 2560 x 1600 (16:10) WQXGA
- 2560 x 1440 (16:9) @60Hz WQHD
- 2560 x 1080 (21:9) UWFHD (Ultrawide 1080p)
- 2048 x 1536 (4:3) QXGA
- 2048 x 1152 (16:9) QWXGA
- 1920 x 1440 (4:3)
- 1920 x 1200 (16:10) WUXGA
- 1920 x 1080 (16:9) @60, 75, 100 a 120Hz Full HD/1080p
- 1856 x 1392 (4:3)
- 1792 x 1344 (4:3)
- 1680 x 1050 (16:10) WSXGA+
- 1600 x 1200 (4:3) UXGA
- 1600 x 900 (16:9) HD+
- 1536 x 864 (16:9)
- 1440 x 900 (16:10) WXGA+
- 1400 x 1050 (4:3) SXGA+

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- 1366 x 768 (16:9) HD
- 1360 x 768 (16:9) HD
- 1280 x 1024 (5:4) SXGA
- 1280 x 960 (4:3) SXGA-
- 1280 x 800 (16:10) WXGA
- 1280 x 768 (5:3) WXGA
- 1280 x 720 (16:9) HD/WXGA/720p
- 1280 x 600
- 1152 x 864 (4:3) XGA+
- 1024 x 768 (4:3) XGA
- 800 x 600 (4:3) SVGA

Other features:

- sound transfer support
- DDC (Display Data Channel) support - Intelligent setting of resolution, frequency and other parameters according to the source graphics chip
- supported modes: mirroring the primary monitor area (default setting), expanding the primary monitor area
- HPD (Hot-Plug-Detect) support - communication sequence controlling the connection / disconnection of the device while running
- HDCP 1.4 and 2.2
- support of power saving modes with spinning down controlled by a source device (PC) and a viewing device (monitor/TV)
- power supply via bus - no external power is needed
- gold-plated connectors for perfect contact and oxidation limitation
- adapter dimensions 45 x 21 x 12 mm
- total cable length incl. connector 1.8 m
- weight only 70 g

Supported operating systems:

- All versions of MS Windows, Mac OS X, Linux and other operating systems.
- It is a pure hardware converter, the transfer is provided only by a cable chip without computer participation, no drivers are installed, so the compatibility is not dependent on the operating system

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

used.

Package contains:

- DisplayPort > HDMI cable length 1.8 m,
- printed installation manual in CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / TR / BG / CN / ARA,
- packed in a cardboard box.

Summary: Axagon RVD-HI14C2 DisplayPort -> HDMI 1.4 cable 1.8m, 4K/30Hz. Cable length: 1.8 m, Connector 1: HDMI Type A (Standard), Connector 2: DisplayPort. Compliance certificates: RoHS, CE, Certification: CE, RoHS. Weight: 70 g, Width: 45 mm, Depth: 21 mm. Package width: 195 mm, Package depth: 95 mm, Package height: 30 mm. Quantity per pack: 1 pc(s) | Vendor Homepage: <https://www.axagon.eu/en/produkty/rvd-hi14c2> | Cable length: 1.8 | Cable type: Round cable | Connector 1: HDMI Type A (Standard) | Connector 1 form factor: Straight | Connector 1 gender: Male | Connector 2: DisplayPort | Connector 2 form factor: Straight | Connector 2 gender: Male | Converter type: Active video converter | Country of origin: China | DisplayPort version: 1.2 | HDCP: Yes | HDCP version: 1.4/2.2 | HDMI version: 1.4b | High Dynamic Range (HDR) technology: High Dynamic Range 10 (HDR10) | Linux operating systems supported: Yes | Mac operating systems supported: Yes | Maximum refresh rate: 120 | Maximum resolution: 4096 x 2160 | Other operating systems supported: Yes | Plug and Play: Yes | Product colour: Black | Refresh rate at maximum resolution: 30 | Supported graphics resolutions: 1024 x 768 (XGA)/1152 x 864 (XGA+)/1280 x 1024 (SXGA)/1280 x 720 (HD 720)/1280 x 768/1280 x 768 (WXGA)/1280 x 800/1280 x 800 (WXGA)/1280 x 960/1360 x 768 (WXGA)/1366 x 768/1400 x 1050 (SXGA+)/1440 x 900/1440 x 900 (WXGA+)/1600 x 1200 (UXG/800 x 600 (SVGA) | Supported video modes: 1024p/1080p/1280p/1440p/1600p/2160p/600p/720p/800p/900p/960p | Windows operating systems supported: Yes | Certification: CE, RoHS | Compliance certificates: CE/RoHS | Depth: 21 | Height: 12 | Weight: 70 | Width: 45 | Package depth: 95 | Package height: 30 | Package type: Hanging box | Package weight: 119 | Package width: 195 | Manual: Yes | Quantity per pack: 1 | Model: RVD-HI14C2 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.00054 | Unit Calculated Weight: 0.12

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903