



CABLE DISPLAY PORT 2M/BLACK 36492 LINDY



Modelis: 36492

Gamintojas: LINDY

EAN: 4002888364928

Prekės kodas: 38020

11.99€

From the Lines cable connectivity concept developed by Lindy, Black Line DisplayPort cables are fully featured, entry level high resolution connection solutions, perfect for home and small office use.

Black Line DisplayPort cables feature triple shielded construction with 30AWG copper conductors for performance and corrosion resistance. Nickel connectors and 24K gold plated contacts maintain signal integrity and reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit are supported. Black Line DisplayPort cables are also capable of transmitting 32 channel audio and Dolby® True HD. Black Line DisplayPort cables are capable of delivering 4:4:4 colour spacing for the most accurate colour representation possible.

Black Line DisplayPort cables are available in lengths from 0.5m to 3m.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Entry level DisplayPort cable for home and small office applications
- Supports UHD resolutions up to 4096x2160@60Hz 4:4:4 10bit
- Robust PVC housing, nickel connectors, 24K gold plated contacts
- Triple shielded cable, corrosion resistant copper 30AWG conductors
- DisplayPort 1.2, 4K, 3D, 21.6Gbps; 10 year warranty

Summary: Lindy 2m DisplayPort 1.2 Cable, Black Line. Cable length: 2 m, Connector 1: DisplayPort, Connector 2: DisplayPort. Certification: RoHS, REACH, UL. Cable diameter: 6 mm, Connector 1 dimensions (WxDxH): 21 x 38.9 x 13.6 mm, Connector 2 dimensions (WxDxH): 21 x 38.9 x 13.6 mm. Package type: Polybag. Quantity per pack: 1 pc(s) | Vendor Homepage: <https://www.lindy.co.uk/cables-adapters-c1/audio-video-c107/2m-displayport-1-2-cable-black-line-p11066> | AWG wire size: 30 | Cable length: 2 | Cable material: Copper | Cable shielding: Copper | Cable type: Round cable | Colour sampling: 4:4:4 | Connector 1: DisplayPort | Connector 1 form factor: Straight | Connector 1 gender: Male | Connector 2: DisplayPort | Connector 2 form factor: Straight | Connector 2 gender: Male | Connector contacts plating: Gold | Connector housing material: Acrylonitrile butadiene styrene (ABS) | Connector material: Nickel | Contact material: Phosphor bronze | Data transfer rate: 21.6 | DisplayPort version: 1.2 | Jacket material: Polyvinyl chloride (PVC) | Maximum refresh rate: 60 | Maximum resolution: 4096 x 2160 | Nominal attenuation: 300kHz-825MHz - 5dB, 825MHz-2.475GHz - 5dB, 2.475GHz-4.125GHz - 12dB, 4.125GHz-5.1GHz - 20dB | Plug and Play: Yes | Product colour: Black | Supported graphics resolutions: 4096 x 2160 | Operating temperature (T-T): -20 - 80 | Storage temperature (T-T): -25 - 85 | Certification: RoHS, REACH, UL | Bend radius (min): 48 | Cable diameter: 6 | Connector 1 dimensions (WxDxH): 21 x 38.9 x 13.6 | Connector 2 dimensions (WxDxH): 21 x 38.9 x 13.6 | Package type: Polybag | Quantity per pack: 1 | Harmonized System (HS) code: 84733080 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.000375 | Unit Calculated Weight: 0.12