



Grandstream GWN 7660 ACCESS POINT



Modelis: GWN7660

Gamintojas: GRANDSTREAM

EAN: 6947273703518

Prekės kodas: 381160

103.00€

Product colour: White | Captive portal: Yes | Total Power over Ethernet (PoE) budget: 9 W | Quality of Service (QoS) support: Yes | Number of SSID supported: 32 | Maximum transmission power (5 GHz) : 22 dBm | Fast roaming: Yes | Shooting distance: 175 m | Cable lock slot: Yes | MU-MIMO: Yes 2x2:2 | Power over Ethernet (PoE): Yes | Height: 180.4 mm | Management software: Yes | 2.4 GHz: Yes | Mounting kit: Yes | VLAN support: Yes | Reset button: Yes | Operating temperature (T-T): 0 - 40 °C | Receiver sensitivity 2.4 GHz : 802.11b: -96 dBm at 1 Mb/s, -88 dBm at 11 Mb/s | Receiver sensitivity 2.4 GHz : 802.11ax 40 MHz: -58 dBm at MCS11 | Receiver sensitivity 2.4 GHz : 802.11ax 20 MHz: -60 dBm at MCS11 | Receiver sensitivity 2.4 GHz : 802.11n 40 MHz: -70 dBm at MCS7 | QoS support : 802.11e/WMM | QoS support : TOS | Receiver sensitivity 2.4 GHz : 802.11n 20 MHz: -73 dBm at MCS7 | PoE standard: IEEE 802.3af/at | 5 GHz: Yes | Maximum data transfer rate (2.4 GHz): 573.5 Mbit/s | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Receiver sensitivity 2.4 GHz : 802.11g: -93 dBm at 6 Mb/s, -75 dBm at 54 Mb/s | Ethernet LAN (RJ-45) ports: 2 | Cloud-managed: Yes | Depth: 40.8 mm | Mounting style: Ceiling, wall | Maximum Tx power (2.4 GHz): 24 dBm | QoS support : VLAN | LED indicators: Yes | Maximum data transfer rate (5 GHz): 1201 Mbit/s | Maximum data transfer rate: 1170 Mbit/s | Supported network protocols: IPv4, IPv6, 802.1Q, 802.1p,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

802.1x, 802.11e/WMM | Width: 180.4 mm | Networking standards: IEEE 802.11a | Number of users: 256 user(s) | Receiver sensitivity 5 GHz : 802.11ac 80 MHz: -59 dBm at MCS9 | Networking standards: IEEE 802.11ac | Receiver sensitivity 5 GHz : 802.11ac 20 MHz: -67 dBm at MCS8 | Receiver sensitivity 5 GHz : 802.11ax 40 MHz: -58 dBm at MCS11 | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11r | Networking standards: IEEE 802.11k | Weight: 443 g | Suitable for outdoor use: No | Receiver sensitivity 5 GHz : 802.11n 40 MHz: -70 dBm with MCS7 | Safe start-up : Yes | Receiver sensitivity 5 GHz : 802.11ax 20 MHz: -60 dBm at MCS11 | Receiver sensitivity 5 GHz : 802.11ac: HT40: -63 dBm at MCS9 | Receiver sensitivity 5 GHz : 802.11ax 80 MHz: -56 dBm with MCS11 | Receiver sensitivity 5 GHz : 802.11n 20 MHz: -73 dBm at MCS7 | OFDMA: Y | MAC address filtering: Yes | Security algorithms: WPA2-Enterprise | Security algorithms: WPA2-AES | Network interface : Base-T 10/100/1000 with auto detection | MU-MIMO technology: Yes | Receiver sensitivity 5 GHz : 802.11a: -92 dBm at 6Mbps, -74 dBm at 54Mbps | WebGui: Yes | Security algorithms: WPA2-TKIP | Security algorithms: WEP | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Networking standards: IEEE 802.11v | Security algorithms: WPA2-PSK | Gamepad: Y

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903