

APC Smart-UPS On-Line, 5kVA, Rackmount 3U, 208V/230V, Hard wire 3-wire(2PH+G)+3-wire(H+N+E)+3-wire(H+N+G) outlets, Network Card+SmartSlot, W/ rail kit

Gamintojas: **APC** · Modelis: **SRT5KRMXLW-HW** · EAN: **731304301516** · Prekės kodas: **383252**



7 564,90 €

Kaina su PVM

Be PVM: **6 251,98 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Double-conversion (Online)
- ✓ 5 kVA 4500 W
- ✓ Waveform: Sine
- ✓ Sealed Lead Acid (VRLA)
- ✓ Rackmount Black

Aprašymas

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 5kVA on-line 3U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with hard wire 3-wire (2P+E) and 3-wire (1P+N+E) inputs, hard wire 3-wire (H+N+E), 3-wire (H+N+G) and 3-wire (2PH+G) outlets. The UPS has an embedded Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCI clusters. It has an additional SmartSlot for optional accessory card such as Dry Contact I/O card. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty.

Techninė specifikacija

Features

UPS topology	Double-conversion (Online)
Output power capacity	5 kVA

Output power	4500 W
Waveform	Sine
Input operation voltage (min)	100 V
Input operation voltage (max)	275 V
Input frequency	40 - 70 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency regulation	50/60 Hz
Surge energy rating	480 J
Efficiency	93.8%
Crest factor	3:1
Emergency Power Off (EPO)	Yes
Noise level	55 dB
Surge protection	Yes
Audible alarm(s)	Yes
Auto-restart	Yes
Ports & interfaces	
AC outlet types	Hard Wire 3-wire (2PH + G)
Power plug	Hardwire
USB port	Yes
Serial interface	Yes
Serial interface type	RJ-45
SmartSlot	Yes
SmartConnect port	No
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	845 VAh
Number of batteries supported	1
Typical backup time at full load	4 min
Typical backup time at half load	11.8 min
Battery life (max)	5 year(s)
Battery recharge time	1.5 h
Hot-swap battery	Yes
Automatic battery test	Yes
Cold start	Yes

Design

Form factor	Rackmount
Product colour	Black
Rack capacity	3U
Display type	LCD
LED indicators	Status
International Protection (IP) code	IP20

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Compliance certificates	RoHS
Certification	REACH, CE, CE Mark, CSA C22.2 No.107.3-05, EAC, EN/IEC 62040-1, EN/IEC 62040-2, FCC Part 15 Class A, IRAM, NOM, RCM, UL

Packaging content

Management card included	Yes
--------------------------	-----

Sustainability

Sustainability certificates	ENERGY STAR
-----------------------------	-------------

Weight & dimensions

Width	432 mm
Depth	719 mm
Height	130 mm
Weight	55.8 kg

Packaging data

Package width	610 mm
Package depth	960 mm
Package height	330 mm
Package weight	68 kg

Logistics data

Products per pallet	6 pc(s)
---------------------	---------

Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	8442.38
Other features	
Number of phases	3
Battery type	APCRBC140
Output connections	1x Hard Wire 3-wire (2PH + G) 1x Hard Wire 3-wire (H N + G)
Matmenys ir svoris	
Matmenys (l × p × A)	97,00cm × 63,00cm × 33,00cm
Svoris	64,50kg