Eaton 5PX2200IRT3UG2 uninterruptible power supply (UPS) Line-Interactive 2.2 kVA 2200 W

Gamintojas: **EATON** · Modelis: **5PX2200IRT3UG2** · EAN: **743172104762** · Prekės kodas: **397217**



1 320,90 €

Kaina su PVM

Be PVM: **1 091,65 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-Interactive
- ✓ 2.2 kVA 2200 W
- ✓ Waveform: Pure sine
- ✓ Rackmount/Tower Black

Aprašymas

Exceptional efficiency, manageability and energy metering capabilities for IT managers

Performance and efficiency

- Eaton 5PX Gen 2 provides Unity power factor (W=VA) capability. With 11% more power than other UPS it can protect more servers.
- Energy Star 2.0 certified, 5PX Gen2 offers best-in-class efficiency performance to reduceenergy consumption and cooling costs.
- When operating in battery mode the 5PX provides a high-quality output signal for any sensitive equipment connected, such as active PFC (power factor corrected) servers.
- Each 5PX Gen2 battery configuration provides the best size /runtime ratio.

Management and Cybersecurity

- Innovative graphical LCD display brings all operating information at first sight. It also enhances commissioning and configuration capabilities.
- 5PX Gen2 Netpack models are delivered with Eaton Gigabit network management card, which provides Dual cybersecurity certifications (UL 2900-1 & IEC 62443-4-2) and enables connection to Eaton Cyber Secured Monitoring solutions.
- Together with 5PX Gen2, Eaton Gigabit network management card allows both remote UPS settings and remote firmware upgrade to ensure easy deployment (fleet management) and reduced maintenance cost.
- 5PX Gen2 meters energy consumption right down to the managed outlet groups. kWh values can be monitored using the LCD or Eaton’s Intelligent

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Power Software.
- Eaton’s Intelligent Power Software seamlessly integrates with leading virtualization environments and cloud orchestration tools.

Availability and flexibility

- 5PX Gen2 2200VA & 3000VA are available in RT2U format (optimized for rack mounting) or RT3U (for tower installation or short-depth racks). Pedestals and rail kits are included with all models.
- 5PX Gen2 load segment control enables prioritized shutdowns of non-essential equipment to maximize battery runtime for critical devices (2 groups).
- Eaton ABM® battery management technology uses a three stage charging technique that optimizes battery health and extends lifetime by up to 50%.
- Up to 4 external hot-swappable battery modules can be added for longer power availability.

Techninė specifikacija

Features	
UPS topology	Line-Interactive
Output power capacity	2.2 kVA
Output power	2200 W
Waveform	Pure sine
Input operation voltage (min)	160 V
Input operation voltage (max)	294 V
Input frequency	47/70 Hz
Noise level	40 dB
Power protection features	Overdischarge
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler
Power plug	C20 coupler
USB port	Yes
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	1
Battery	
Hot-swap battery	Yes
Automatic battery test	Yes
Design	
Form factor	Rackmount/Tower
Product colour	Black
Rack capacity	3U

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Certificates	
Compliance certificates	CE
Certification	IEC/EN 62040-2, FCC B, CISPR22 B CB (TUV) / cTUVus / EAC / UKCA / Ukr / Cm
Packaging content	
Management card included	No
Safety regulation & standards	
Safety	IEC/EN 62040-1, UL1778, CSA22.2
Sustainability	
Sustainability certificates	ENERGY STAR
Sustainability compliance	Yes
Weight & dimensions	
Width	438 mm
Depth	483 mm
Height	129 mm
Weight	27.5 kg
Logistics data	
Harmonized System (HS) code	85078000
Other features	
Output connections	8 x IEC C13 (10A) 2 x IEC C19 (16A)
Nominal output voltage	230 V
Matmenys ir svoris	
Matmenys (I × P × A)	77,00cm × 59,00cm × 29,00cm

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Eaton

ATSAKINGAS ASMUO ES

Eaton Electric GmbH
Hein-Moeller-Str. 45849, 53115 Bonn, DE
eaton.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.