

ASUS ROG RYUJIN 240 Processor All-in-one liquid cooler 12 cm Black 1 pc(s)

Gamintojas: **ASUS** · Modelis: **90RC0030-M0UAY0** · EAN: **4718017058155** · Prekės kodas: **401122**



232,90 €

Kaina su PVM

Be PVM: **192,48 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1.77" color OLED for real-time system stats and personalized logos or animations
- ✓ Embedded microfan helps to cool VRM and M.2 area by up to 20°C
- ✓ Quality Noctua Industrial PPC PWM fans deliver high airflow and minimal noise
- ✓ ROG Vortex one-stop control center for lighting, OLED display, and cooling
- ✓ Individually addressable RGB and NCVM coating pump cover accentuates the sleek, modern aesthetics
- ✓ Styled to complement ROG motherboards, at the center stage of your build
- ✓ Reinforced, sleeved tubing for increased durability



Aprašymas

ROG Ryujin all-in-one liquid CPU cooler with color OLED, Aura Sync RGB and Noctua iPPC 2000 PWM 120mm radiator fan

ROG Ryujin is the flagship all-in-one cooler for high-end builds designed to deliver the best thermal performance. Featuring Noctua IndustrialPPC fans for cooler and quieter operation, plus an embedded fan in the pump housing for additional cooling to the VRM and M.2, ROG Ryujin keeps your system running its absolute best. Coupled with a LiveDash OLED that displays system stats or custom graphics and Aura Sync RGB lighting, ROG Ryujin is the ultimate thermal solution destined to become a vital part of your gaming rig.

COOL TO THE CORE

Noctua IndustrialPPC fan

ROG Ryujin meets the thermal challenges of the latest multi-core CPUs with industrial-grade Noctua iPPC-2000 PWM fans on the radiator that deliver high performance and low-noise operation. The 120-mm fans generate 122 CFM of airflow at 2,000 RPM yet are extremely efficient with a 29.7-dB(A) acoustic footprint that's much quieter than competing fans.

Pump embedded fan

While powerful, liquid cooling does not circulate air around the CPU socket like a traditional heatsink and fan. ROG Ryujin overcomes this limitation with a 60mm fan embedded in the pump housing that circulates air to the CPU VRMs, M.2 slot and surrounding components to dramatically reduce temperatures for improved performance and stability.

NEXT LEVEL OF CUSTOMIZATION

LiveDash OLED

ROG Ryujin is the world's first AIO cooler to feature an embedded 1.77-inch LiveDash color OLED that displays useful system information*, such as temperatures, voltages, fan speeds, or frequencies. You can also customize LiveDash to display a customized image or animation** highlighting your clan insignia or gamertag.

Complete LiveDash customizability

The LiveDash software utility lets you easily customize ROG Ryujin's LiveDash OLED display and RGB lighting effects. Select which system stats to monitor, choose personalized GIFs and images to display, and control RGB lighting from an intuitive interface that arranges settings in a step-by-step flow from top to bottom.

Subtle, striking, sleek

Infused with Aura RGB lighting in dramatic slash patterns on the shroud, Ryujin exudes a vibrant glow that highlights the CPU at the heart of your build

PERFECT

SYNCHRONIZATION

The impact of Aura RGB lighting can be further enhanced with ASUS Aura Sync, which allows harmonized lighting effects with other Aura-enabled system components and external accessories. Aura software give you complete control of lighting across all compatible devices, letting you dial in the vibe you want to display quickly and easily.

EXTENDED COMPATIBILITY

ROG Ryujin is compatible with a wide range of Intel and AMD motherboard platforms, giving you the flexibility to pair it with your choice of processor. It also comes fitted with 38cm of tubing to make mounting and routing easier.

Techninė specifikacija

Specifications	
Sandėlio grupė	Komponenten & Zubehör > Kühler/Lüfter [+4069][-1266]
Performance	
Suitable location	Processor
Type	All-in-one liquid cooler
Fan diameter	12 cm
Supported processor sockets	LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1156 (Socket H), LGA 1366 (Socket B), LGA 2011 (Socket R), LGA 2011-v3 (Socket R), LGA 2066, Socket AM4, Socket TR4

Pulse-width modulation (PWM) support	Yes
Quantity per pack	1 pc(s)
Fan speed (min)	450 RPM
Fan speed (max)	2000 RPM
Design	
Product colour	Black
Material	Aluminium, Copper, Plastic, Rubber
Radiator material	Aluminium
Number of fans	2 fan(s)
Illumination LED	Yes
Illumination colour	Blue, Green, Red
Water block material	Copper
Weight & dimensions	
Radiator width	27.2 cm
Radiator depth	12.2 cm
Radiator height	2.7 cm
Waterblock width	10 cm
Waterblock depth	10 cm
Waterblock height	7 cm
Fan dimensions (W x D x H)	120 x 120 x 25 mm
Fan thickness	2.5 cm
Packaging content	
Package type	Box
Mounting kit	Yes
Manual	Yes
Installation instruction	Yes
Other features	
Tube material	Rubber
Number of fans supported	2
Thermal grease	Yes
Noise level	29.7 dB
Logistics data	
Harmonized System (HS) code	84733080