ASUS Prime -RTX5060TI-O8G NVIDIA GeForce RTX 5060 Ti 8 GB GDDR7

Gamintojas: **ASUS** · Modelis: **90YV0MP0-M0NA00** · EAN: **4711387994207** · Prekės kodas: **401309**



911,90 €

Kaina su PVM

Be PVM: **753,64 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės


- ✓ NVIDIA GeForce RTX 5060 Ti 8 GB GDDR7
- ✓ 7680 x 4320 pikseliai 128 bitai PCI Express 5.0
- ✓ HDMI portų kiekis: 1 „DisplayPort“ kiekis: 3
- ✓ OpenGL versija: 4.6
- ✓ 1x 8-pin











Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Aprašymas

Primed for Power

Experience Primal performance with the Prime GeForce RTX 5060 Ti, an SFF-Ready Enthusiast GeForce Card featuring a 2.5-slot design for expansive compatibility, enhanced by a triple-fan setup for supreme airflow design for supreme cooling.

NVIDIA Blackwell Architecture
The Ultimate Platform for Gamers and Creators

Fifth-Gen Tensor Cores
Max AI performance with FP4 and DLSS 4

New Streaming Multiprocessors
Optimized for neural shaders

Fourth-Gen Ray Tracing Cores
Built for Mega Geometry

Build Small. Play Big.
You can pack high performance into a smaller footprint with this SFF-Ready Enthusiast GeForce card. Look for cases that are compatible with SFF-Ready Enthusiast GeForce Cards to get a sure fit and streamline your PC build.

Cooling
2.5-slot Design
The Prime RTX 5060 Ti features a 2.5 slot design with a carefully arranged layout for the shroud, heatsink and heat pipes to let the three Axial-tech fans leverage chassis side-panel ventilation and deliver optimal thermal performance.

Axial-tech Upgrades

Three tried-and-true Axial-tech fans feature a smaller hub that facilitates longer blades and a barrier ring to increase downward air pressure for lower temperatures, less noise and higher performance.

0dB Technology

All three fans come to a standstill when GPU temperatures are below 50°C, letting you play less demanding games or perform light tasks in relative silence. Fans start up again when temperatures are over 55°C, establishing a speed curve that balances performance and acoustics for work or play.

Dual Ball Fan Bearings

Different bearing types have unique pros and cons. Dual-ball bearings excel at durability and can last up to twice as long as sleeve bearing designs.

Vented Backplate

Large backplate vents significantly enhance heat dissipation, helping to keep the GPU cooler during intense tasks. This additional airflow helps ensure optimal temperatures, boosting performance, longevity and stability by defending against overheating and thermal throttling.

MaxContact Design

MaxContact is a special ASUS manufacturing process that effectively expands the surface area of the heat spreader that sits atop the GPU by 5%, compared to traditional designs. This improves temperatures by up to 2°C, in concert with an extensive heatsink array and powerful Axial-tech fans.

Unmatched Reliability

ASUS GPU Guard

ASUS GPU Guard applies adhesive to secure all four corners to reduce the risk of cracks.

Protective Backplate

The PCB is reinforced by a metal backplate that adds structural rigidity, helping to prevent flex and to protect components and trace pathways from damage.

Stainless Steel Bracket

The mounting bracket features grade 304 stainless steel, chosen for its strength and high resistance to corrosion.

Engineering

Dual BIOS

Do you prioritize low core temps or low noise levels? Performance mode lets the fans spin up to keep the card running cool all the time, and Quiet mode keeps the same power target and top-end settings while offering a less aggressive fan curve for quieter operation at moderate temperatures.

Auto−Extreme Technology

An automated manufacturing process that sets new standards in the industry by allowing all soldering to be completed in a single pass, ASUS Auto-Extreme technology reduces thermal strain on components and avoids the use of harsh cleaning chemicals, resulting in less environmental impact, lower manufacturing power consumption and a more reliable product overall.

RTX. It’s On.

The Ultimate in Ray Tracing and AI

RTX is the most advanced platform for full ray tracing and neural rendering technologies that are revolutionizing the ways we play and create. Over 700 games and applications use RTX to deliver realistic graphics and incredibly fast performance with cutting-edge AI features like DLSS Multi Frame Generation.

Creators

Your Creative AI-dvantage

NVIDIA Studio is your creative advantage. GeForce RTX 50 Series GPUs unlock transformative performance in video editing, 3D rendering, and graphic design. Experience RTX accelerations in top creative apps, world-class NVIDIA Studio drivers engineered and continually updated to provide maximum stability, and a suite of exclusive tools that harness the power of RTX for AI-assisted creative workflows.

Techninė specifikacija

Procesorius	
Grafikos procesoriaus šeima	NVIDIA
Grafikos procesorius	GeForce RTX 5060 Ti
Maksimali rezoliucija	7680 x 4320 pikseliai
CUDA	Taip
Paralelinio apdorojimo technologijos parama	Nepalaikomas
CUDA šerdys	4608
Procesoriaus laikrodžio greičio padidinimas	2617 MHz
Procesoriaus dažnis (OC režimas)	2602 MHz
Procesoriaus spartinimo laikrodžio greitis (OC režimas)	2647 MHz

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Maksimalus ekranų skaičius kiekvienai vienai vaizdo plokštei	4
Atmintis	
Diskrečiojo grafikos adapterio atmintis	8 GB
Grafikos adapterio atminties tipas	GDDR7
Atminties magistralė	128 bitai
Atminties pralaida (maks)	28 GB/s
Ryšys	
Sąsajos tipas	PCI Express 5.0
HDMI portų kiekis	1
DVI-D prievadų skaičius	0
DVI-I prievadų skaičius	0
„DisplayPort“ kiekis	3
3 „Thunderbolt“ prievadų skaičius	0
Mini HDMI portų kiekis	0
HDMI versija	2.1b
VGA (D-Sub) portų kiekis	0
„Mini DisplayPort“ kiekis	0
„DisplayPort“ versija	2.1b
USB tipo C prievadų kiekis	0
Veikimo charakteristikos	
Integruotas TV tiuneris	Ne
OpenGL versija	4.6
Dvi DVI išvestys	Ne
HDCP	Taip
HDCP versija	2.3
NPU sparta iki	759 TOPs
Padidintos spartos (OC) leidimas	Taip
Konstrukcija	
Aušinimo tipas	Aktyvus
Aušinimo technologija	ASUS Axial-tech
Ventiliatorių skaičius	3 ventiliatorius(iai / ių)
Forma	Full-Height/Full-Length (FH/FL)
Laikiklio aukštis	Full-Height (FH)
Lizdų skaičius	2,5

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Iliuminacija	Ne
Suderinama su SFF standartu	Taip
Produkto spalva	Juoda
Energijos valdymas	
Minimalus sistemos maitinimas	550 W
Papildomos maitinimo jungtys	1x 8-pin
Svoris ir matmenys	
Svoris	898 g
Ilgis	304 mm
Ilgis	50 mm
Aukštis	120 mm
Pakuotės duomenys	
Pakuotės plotis	405 mm
Pakuotės gylis	233 mm
Pakuotės aukštis	88,5 mm
Paketo svoris	1,49 kg
Pakuotės tipas	„Box“

Gamintojo ir saugos informacija

GAMINTOJAS

ASUSTeK Computer Inc
Li-Te Road 15, 112 Taipei, TW
asus.com

ATSAKINGAS ASMUO ES

ASUS France S.A.R.L.
Allee bienvenue 10, 93160 Paris, FR
channel.asus.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.