

BenQ SW240 computer monitor 61.2 cm (24.1") 1920 x 1080 pixels Full HD LED Grey

Gamintojas: **BENQ** · Modelis: **9H.LH2LB.QBE** · EAN: **4718755073830** · Prekės kodas: **402200**



890,90 €

Kaina su PVM

Be PVM: **736,28 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 61.2 cm (24.1") LED IPS
- ✓ Full HD 1920 x 1080 pixels 16:10
- ✓ 76 Hz 5 ms 250 cd/m² 1000:1
- ✓ E 18 kWh 18.1 W

Aprašymas

Accurate Colors Benefit Creators

BenQ empowers creative professionals with AQCOLOR technology to help inspire ideas and make projects come to life.

Industry Leading Color Performance

Incredible Color Space Coverage

SW240 covers 99% AdobeRGB, 95% P3, 100% sRGB. BenQ AQCOLOR technology delivers Accurate Reproduction.

Industry Leading Color Performance

Absolute Color Confidence

The 14-bit lookup table (LUT) improves color blending for precise reproduction. Delta E ≤ 2 in Adobe RGB and sRGB color spaces assures accuracy.

Industry Leading Color Performance

Hardware Calibrated for Color Accuracy

Use Palette Master Element and a calibrator to customize color settings or maintain the display's color at its optimal state.

Accuracy Guarantee

Out-of-the-Box GUARANTEE

SW240 earns Calman Verified. Creative professionals demand excellence, and BenQ delivers.

Accuracy Guarantee

Pantone Connect Premium

Go digital with BenQ, the first brand to work with Pantone on a mobile app. As an existing owner or a new purchaser of BenQ professional monitors, you get one year of free Pantone Connect Premium for digitally mobile color consistency and accuracy.

BenQ Uniformity Technology

Delivering corner-to-corner authentic colors and consistent luminescence. The display is divided into hundreds of sub-regions and rigorously fine-tuned for precision. This innovative tech assures ultra-dependable image fidelity.

Attentive Design to Optimize Your Workflows

Shading Hood

Reducing unwanted glare from ambient lighting, the shading hood is perfect for BenQ PhotoVue Monitors.

Ergonomic Design

Create in comfort with your monitor in the ideal position.

Techninė specifikacija

Specifications	
Sandėlio grupė	Peripherie & Desktop > Monitore [+2401][(-1]
Display	
Display diagonal	61.2 cm (24.1")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:10
Display technology	LED
Touchscreen	No
HD type	Full HD
Panel type	IPS
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	76 Hz
Display number of colours	1.073 billion colours
Backlight type	LED
Display brightness (typical)	250 cd/m²
Supported graphics resolutions	1920 x 1080 (HD 1080)
Contrast ratio (dynamic)	20000000:1
Viewing angle, horizontal	178°

Viewing angle, vertical	178°
Pixel pitch	0.27 x 0.27 mm
Horizontal scan range	30 - 83 kHz
Vertical scan range	50 - 76 Hz
3D	No
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Multimedia	
Built-in camera	No
Design	
Market positioning	Graphics design
Product colour	Grey
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of upstream ports	1
USB Type-A downstream ports quantity	2
DVI port	Yes
HDMI ports quantity	1
DisplayPorts quantity	1
Headphone outputs	1
Headphone connectivity	3.5 mm
HDCP	Yes
HDCP version	2.2
Card reader integrated	Yes
Compatible memory cards	SD, SDHC, SDXC
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington

Adjustable height (max)	14 cm
Pivot	Yes
Swivelling	Yes
Swivel angle range	-45 - 45°
Tilt adjustment	Yes
Tilt angle range	-5 - 20°
On Screen Display (OSD)	Yes
Power	
Energy efficiency class (SDR)	E
Energy consumption (SDR) per 1000 hours	18 kWh
Power consumption (typical)	18.1 W
Power consumption (standby)	0.3 W
Power consumption (off)	0.2 W
AC input voltage	90 - 264 V
AC input frequency	47/63 Hz
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	5 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	543.5 mm
Depth (with stand)	230.7 mm
Height (with stand)	428.5 mm
Weight (with stand)	6.7 kg
Packaging content	
Cables included	AC, DVI, USB
Quick start guide	Yes
Other features	
Country of origin	China
On/off switch	Yes
Certification	TUV GS, CE, ISO9241-307
Supplied AC adapter type	LED

Thin Client

Thin client installed	No
-----------------------	----

Logistics data

Harmonized System (HS) code	85285210
-----------------------------	----------