MSI MPG CORELIQUID K240 Liquid CPU Cooler '240mm Radiator, 2.4'' LCD display with fan, 3x 120mm ARGB PWM Fan, Center, Supports Intel and AMD Platforms, Cooled by ASETEK'

Gamintojas: **MSI** · Modelis: **9S6-6A0311-025** · EAN: **4719072810160** · Prekės kodas: **402441**



240.90€

Kaina su PVM

Be PVM: **199.09€**

In Stock

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ MSI's TORX FAN 4.0 provides supreme cooling to the radiator
- ✓ 60mm TORX FAN 3.0 within the water block provides heat dissipation to the power solutions
- ✓ 2.4" customizable LCD display
- ✓ G.I. Mode intelligently detects the temperature of the CPU to adjust the speed of the radiator fans, water block fan, and pump
- ✓ The fans' speed can be independently controlled according to different user scenarios









Aprašymas

Mighty with a purpose, the MPG CORELIQUID K Series descends. The MPG CORELIQUID K Series washes away your traditional image of a liquid cooler and blows it into a whole new reality. Stacked with powerful features and sculpted with eye-catching appearances, the MPG CORELIQUID K Series is here to set the benchmark, one game at a time.

UNRIVALED RAPID COOLING

MSI's exclusive TORX FAN 4.0 provides concentrated airflow to the radiator for the most rapid heat dissipation.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

TORX FAN 4.0

Inspired by teamwork, MSI’s exclusive TORX FAN 4.0 has two fan blades working as one with an outer ring design.

CONCENTRATED
COOLING PERFORMANCE
A 60mm TORX FAN 3.0 is placed within the water block to help dissipate heat for the M.2 SSD, CPU VRMs, and surrounding components for improved performance.

2.4” CUSTOMIZABLE LCD DISPLAY

The MPG CORELIQUID K Series comes equipped with a 2.4” LCD capable of displaying a wide range of hardware system information and customizable graphics.

EVAPORATION PROOF TUBING

MPG CORELIQUID K Series’ tubing is constructed with three layers of netted plastic with a reinforced mesh exterior.

CONTROL IN YOUR HANDS

Through MSI’s exclusive software, you can independently control all of the fans’ speed according to your preference for cooling or for silence.

THE MOST COMPLETE USER EXPERIENCE

The G.I. (Gaming Intelligence) Mode intelligently detects the temperature of the system. The radiator fans, water block fan, and pump can all have their speed adjusted according to different usage situations.

TOTAL CONTROL IN YOUR HANDS

Everything ranging from MPG CORELIQUID K Series’ fan speed to the ARGB lighting to the LCD display can be adjusted through the MSI Center.

EXTENSIVE COMPATIBILITY

Stunning yet built for flexibility, the MPG CORELIQUID K Series has been designed with a secure installation bundle with compatibility on a number of Intel and AMD motherboards.

Techninė specifikacija

Performance	
Suitable location	Processor
Type	All-in-one liquid cooler
Supported processor sockets	LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1156 (Socket H), LGA 1200 (Socket H5), LGA 1366 (Socket B), LGA 2011 (Socket R), LGA 2011-v3 (Socket R), LGA 2066, Socket AM2, Socket AM2+, Socket AM3, Socket AM3+, Socket AM4, Socket FM2, Socket FM2+
Minimum airflow (imperial)	77.4 cfm
Minimum air pressure	4.29 mmH2O
Pulse-width modulation (PWM) support	Yes
Pump noise level	20 dB

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Fan bearing technology	Double ball bearing
Quantity per pack	1 pc(s)
Fan speed (min)	0 RPM
Fan speed (max)	2500 RPM
Pump's mean time to failure (MTTF)	50000 h
Fan's mean time to failure (MTTF)	100000 h

Design

Product colour	Black
Radiator material	Aluminium
Number of fans	2 fan(s)
Illumination LED	Yes
Illumination colour	Multi
Display type	LCD

Power

Fan power consumption	3.36 W
Pump power consumption	4 W
Pump current	0.33 mA
Fan voltage	12 V
Fan current	0.28 A

Weight & dimensions

Radiator width	27.2 cm
Radiator depth	12 cm
Radiator height	2.7 cm
Tube length	40 cm
Waterblock width	9.47 cm
Waterblock depth	8.34 cm
Waterblock height	9.4 cm
Fan dimensions (W x D x H)	120 x 120 x 25 mm

Packaging content

Cables included	RGB splitter cable

Other features

Noise level	39.9 dB
Built-in display	Yes

Logistics data

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Harmonized System (HS) code	84733080

Dokumentai ir vaizdo įrašai

› Product leaflet

Gamintojo ir saugos informacija

MANUFACTURER

Micro-Star Int'l Co.
Lide St., Zhonghe Dist. No. 69, 235 New Taipei City, TW
msi.com

EU RESPONSIBLE PERSON

Mystar Computer B.V.
Science Park Eindhoven 5706, 5692 ER Son, NL
msi.com

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt