

**Monitor DELL
P2725QE 27-
inch 4K UHD IPS
100Hz Business
Display with
USB-C Hub (90W
PD), Swivel,
Pivot, Height
Adjustable
Stand, TÜV
Certified**



Modelis: DELL-P2725QE

Gamintojas: DELL

EAN: 5397184962497

Prekės kodas: 409580

484.99€

Superior 4K Clarity and Connectivity for Professional Use

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

The DELL P2725QE is a premium 27-inch monitor engineered for demanding business and professional environments requiring exceptional clarity and connectivity. Experience stunning 4K Ultra HD resolution (3840 x 2160) on a high-performance IPS panel, providing vibrant colors and wide 178° viewing angles, crucial for detailed work in photo editing, data analysis, and multitasking.

Crucially, this monitor enhances workflow efficiency with its powerful integrated connectivity hub. The USB Type-C upstream port delivers up to 90W of Power Delivery, allowing you to charge your laptop while simultaneously transmitting video, audio, and data over a single cable. The fast 100Hz refresh rate and 5ms (GTG fast) response time ensure smoother on-screen movement compared to standard 60Hz displays, reducing motion blur during fast-paced scrolling or video playback.

Exceptional Productivity and Comfort

The P2725QE is designed with long hours of use in mind, boasting TÜV 4 Star Eye Comfort certification. This includes Flicker-free technology and Low Blue Light features, minimizing eye strain. Achieve your perfect setup with full ergonomic versatility, including height adjustment (150mm), swivel (-45° to 45°), tilt (-5° to 21°), and 90-degree pivot functionality.

Key Specifications and Connectivity:

- **Stunning 4K IPS Panel:** 27-inch (68.6 cm) display offering 3840 x 2160 UHD resolution and 99% sRGB color coverage.
- **Smooth 100Hz Refresh Rate:** Provides fluid visual performance for professional tasks and video conferencing.
- **Integrated USB-C Hub:** Features 90W Power Delivery for charging connected devices, plus 3x USB Type-A and 1x USB Type-C downstream ports.
- **Extensive Connectivity:** Includes HDMI 2.1, DisplayPort 1.4, and an RJ-45 (Ethernet LAN) port for reliable network connection.
- **Certified Eye Comfort:** TÜV certified for 4 Star eye comfort, integrating Low Blue Light and Flicker-Free technology.
- **Full Ergonomics:** Adjustments for height, pivot, tilt, and swivel to ensure maximum comfort throughout the workday.

DELL is a global leader in computing and display technology, renowned for delivering reliable, high-performance, and sustainable professional solutions.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Order today from ++SHOP++ as we offer the best prices and dedicated customer support for premium business displays.

Stay productive with this 27-inch 4K monitor featuring extensive connectivity and certified by TÜV for 4 star eye comfort.

Stay productive with this 27-inch 4K monitor featuring extensive connectivity and certified by TÜV for 4 star eye comfort.

- 68.6cm (27") 4K Ultra HD 3840 x 2160 Edge LED IPS
- 8ms, 16:9, 350cd/m², 1500:1
- USB, HDMI, DisplayPort

Actual configuration might differ from illustration

Product Carbon Footprint (PCF):

1. Dell generally uses the PAIA (Product Attribute to Impact Algorithm)(<http://msl.mit.edu/projects/paia/main.html>) tool for product carbon footprint calculations.
2. Docking station related PCFs are extracted from corresponding LCAs and as such do not follow the PAIA methodology used for calculating other PCFs in this report.
3. PAIA method is developed by the Massachusetts Institute of Technology's Materials Systems Laboratory and partners.
4. All estimates of carbon footprint are uncertain. Dell Technologies reports the 5th and 95th percentile of the carbon footprint estimate to reflect this uncertainty wherever possible. (<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>)
5. Please note the emission estimate in this report is calculated using the mean value along with the standard deviation for that product model.
6. Use of default inputs (i.e. not primary data) and assumptions on location of use and other fields can introduce a standard deviation which must be taken into account while completing the calculations.
7. Please note, PAIA uses the ecoinvent Database (<https://ecoinvent.org/the-ecoinvent-database/>) whenever primary data is not made available for calculations.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsijyant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

8. For client and commercial end user computing products, minimum configurations were assumed for calculations. For Server and Storage products, typical configurations or ENERGY STAR (<https://www.energystar.gov/products>) configurations were used for calculations.
9. Use Phase emissions were calculated based on the location of use as "Europe" i.e. the Use Phase emissions are not specific to a single country / location.
10. The report does provide an option for a total emissions number for manufacturing, transport and end of life while leaving the use phase emissions out, in case the customer uses their own calculation methodology for use phase emissions.
11. The lifetime usage assumption at the product family level is as follows: Desktop, Notebook - 4 years, Display - 5 years and Servers - 4 years.
12. For detailed assumptions please refer to the product datasheets in the Dell Technologies reports (<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>).
13. The results from the PAIA tool are liable to change over time as the methodology is improved and datasets are updated. The PAIA version used to calculate emissions has been indicated with each record in the report.
14. Metrics used: The units for global warming potential are in kgCO₂-equivalent or MT (metric ton) CO₂-equivalent (CO₂e).
15. Beginning in June 2024, the data dashboard now incorporates PCF values computed using the Dell PCF calculator. It's important to note that the default location utilized for these calculations shown on the data dashboard is Europe. To access PCF values calculated for the USA and China locales, please refer to the Product PCF PDF document on Dell.com.

Summary: DELL Pro Plus P2725QE. Display diagonal: 68.6 cm (27"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black, Silver | Vendor Homepage: <https://www.dell.com/en-uk/shop/> | Anti-glare screen: Yes | Backlight type: Edge LED | Contrast ratio (typical): 1500:1 | Digital horizontal frequency: 30 - 227 | Digital vertical frequency: 48 - 100 | Display brightness (typical): 350 | Display diagonal: 27 | Display number of colours: 1.07 billion colours | Display resolution: 3840 x 2160 | Display technology: LCD | HD type: 4K Ultra HD | High Dynamic Range (HDR) supported: No | LED backlight: Yes | Maximum refresh rate: 100 | Native aspect ratio: 16:9 | Panel type: IPS | Pixel density: 163 | Pixel pitch: 0.1554 x 0.1554 | Response time: 8 | Response time (fast): 5 | Response time measurement type: GTG (Gray to Gray) |

Screen shape: Flat | sRGB coverage (typical): 99 | Supported graphics resolutions: 1024 x 768 (XGA)/1152 x 864 (XGA+)/1280 x 1024 (SXGA)/1280 x 720 (HD 720)/1600 x 900/1920 x 1080 (HD 1080)/2560 x 1440/3840 x 2160/640 x 480 (VGA)/720 x 400/800 x 600 (SVGA) | Supported video modes: 1080p/2160p/480p/576p/720p | Surface hardness: 3H | Touchscreen: No | Viewable size, horizontal: 596.74 | Viewable size, vertical: 335.66 | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | AMD FreeSync: No | Flicker-free technology: Yes | Low Blue Light technology: Yes | NVIDIA G-SYNC: No | Built-in camera: No | Built-in speaker(s): No | Detachable stand: Yes | Feet colour: Silver | Front bezel colour: Black | Market positioning: office | Product colour: Black,Silver | Built-in USB hub: Yes | DisplayPort version: 1.4 | DisplayPorts quantity: 1 | HDCP: Yes | HDCP version: 2.3 | HDMI: Yes | HDMI ports quantity: 1 | HDMI version: 2.1 | Headphone out: No | Number of USB Type-C upstream ports quantity: 1 | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | USB Power Delivery (USB PD): Yes | USB Power Delivery up to: 90 | USB Type-A downstream ports quantity: 3 | USB Type-C DisplayPort Alternate Mode: Yes | USB Type-C downstream ports quantity: 1 | USB upstream port type: USB Type-C | Ethernet LAN: Yes | Wi-Fi: No | Adjustable height (max): 150 | Cable lock slot: Yes | Cable lock slot type: Kensington | Cable management: Yes | Height adjustment: Yes | LED indicators: Yes | On Screen Display (OSD): Yes | Panel mounting interface: 100 x 100 | Pivot: Yes | Pivot angle: -90 - 90 | Plug and Play: Yes | Swivel angle range: -45 - 45 | Swivelling: Yes | Tilt adjustment: Yes | Tilt angle range: -5 - 21 | VESA mounting: Yes | Wall mountable: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Energy consumption (SDR) per 1000 hours: 26 | Energy efficiency class (HDR): Not available | Energy efficiency class (SDR): F | Energy efficiency scale: A to G | Power consumption (max): 200 | Power consumption (off): 0.3 | Power consumption (standby): 0.3 | Power consumption (typical): 19.6 | Power supply type: Internal | Non-operating altitude: 5000 - 12191 | Operating altitude: 0 - 5000 | Operating relative humidity (H-H): 10 - 80 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -20 - 60 | Bezel width (bottom): 13.02 | Bezel width (side): 7.88 | Bezel width (top): 7.88 | Depth (with stand): 192.16 | Depth (without stand): 49.99 | Height (with stand): 535.7 | Height (without stand): 356.55 | Weight (with stand): 6230 | Weight (without stand): 4620 | Width (with stand): 612.5 | Width (without stand): 612.5 | Package weight: 9020 | Cables included: AC/DisplayPort/USB Type-A to USB Type-C/USB Type-C to USB Type-C | Power adapter included: No | Remote control included: No | Stand included: Yes | Stylus included: No | Doesn't contain: Arsenic/Mercury/PVC/BFR | Sustainability certificates: ENERGY STAR/TCO | Carbon emissions, end-of-life (kg of CO2e): 6.095 | Carbon emissions, energy usage (kg of CO2e): 124.285 | Carbon emissions, logistics (kg of CO2e): 16.96 | Carbon emissions, manufacturing (kg of CO2e): 117.395 | PAIA

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

version: GaBi version 1, 2024 | Total carbon footprint (kg of CO2e): 265 | Compliance certificates: RoHS | RJ-45 ports quantity: 1 | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/2173572/fiches?language=EN> | Energy efficiency class: F | EPREL Registration Number: 2173572 | EPREL Version Number: 2 | Model: P2725QE | Unit Calculated Volume: 0.05134/0.0535 | Product Net Weight: 6.6 | Unit Calculated Weight: 9.05

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903