
ASUS PRIME B760M-A D4-CSM Intel B760 LGA 1700 „micro ATX“

Gamintojas: **ASUS** · Modelis: **90MB1D00-M1EAYC** · EAN: **4711081984061** · Prekės kodas: **433183**



124,90 €

Kaina su PVM

Be PVM: **103,22 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Intel LGA 1700 „Intel® Celeron®“, Intel® Pentium® Gold, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9
- ✓ PC „micro ATX“ Intel B760 7.1 kanalai
- ✓ DDR4-SDRAM 4 DIMM Maksimali vidinė atmintis: 128 GB
- ✓ HDD & SSD M.2, SATA III RAID palaikymas Palaikomų saugojimo tvarkyklių skaičius: 6
- ✓ BIOS tipas: UEFI AMI 256 Mbit
- ✓ 2.5 Gigabit Ethernet











Aprašymas

B760M-A D4-CSM

ASUS Prime series motherboards are expertly engineered to unleash the full potential of 13th Gen Intel® Core™ Processors. Boasting a robust power design, comprehensive cooling solutions and intelligent tuning options, PRIME B760M-A D4-CSM provides users and PC DIY builders with a range of performance optimizations via intuitive software and firmware features.

FLEXIBILITY

Comprehensive controls form the foundation of the ASUS PRIME series. The PRIME B760 motherboard packs flexible tools to tune every aspect of your system, enabling performance tweaks to perfectly match the way you work to maximize productivity.

Intelligent Control

ASUS Intelligent Control makes your PC smart. Along with taking care of complex tuning and dynamically optimizing essential aspects of your system, it offers intelligently simplified options for newcomers to PC DIY, as well as more comprehensive features for seasoned veterans.

All-Around Energy Efficiency

The Power Saving function contains several settings can easily optimize power consumption and maximize energy savings. You can enable a CPU power limit, darken Aura lighting, and set the fan profile to a power saving mode. You can also toggle the Power Saver plan that is built into Microsoft Windows.

Flexible Air- and Liquid-Cooling Controls

ASUS Fan Xpert 2+ software provides comprehensive control over fans and all-in-one (AiO) coolers. Whether cooling with air or water, an Auto-Tuning mode intelligently configures all parameters with a single click. There’s also an Extreme Quiet mode that reduces chassis fan speeds to below the default minimum to keep your system whisper-quiet when performing light tasks. Fans, AiO coolers can also be controlled via the UEFI BIOS.

Precise Digital Power Control

The Digi+ voltage-regulator module (VRM) delivers real-time control over voltage droop, automatically switching frequency and power-efficiency settings. It also allows you to fine-tune your CPU for ultimate stability and performance.

UEFI BIOS

The renowned ASUS UEFI BIOS provides everything you need to configure, tweak and tune your system. It offers intelligently simplified options for PC DIY beginners, as well as comprehensive features for seasoned veterans.

Advanced Tuning for Serious Tweakers

An intuitive Advanced mode offered via the UEFI lets you take complete control. A built-in search feature makes it easy to find options, and various advanced functions let you intelligently make nuanced adjustments so you can dial in performance just the way you want.

Search Function

Quickly and easily find the option or setting you need.

ASUS User Profile

Port configuration settings between different BIOS versions or share them with friends.

Quick and Simple Setup

EZ mode displays vital settings and stats and also offers guided wizards, drag-and-drop functionality, and one-click application of important settings — all to help you get your rig up and running in no time.

Intuitive Graphical Fan Control

Fine-tune individual fan settings simply by dragging a curve with the mouse.

Aura On/Off Mode (Stealth)

Easily enable or disable Aura RGB lighting or every onboard LED, for a subdued aesthetic touch.

COOLING

PRIME B760 series are engineered with multiple onboard heatsinks and an array of hybrid fan headers to ensure your rig stays cool and stable under intense workloads.

M.2 Heatsink

M.2 heatsink wards off throttling that can occur with M.2 storage during sustained transfers. The heatsink is held in place by captive screws, and these removable captive screws help reduce risk of drops or loss during heatsink removal.

VRM Heatsink and Thermal Pad

VRM heatsink and thermal pad improve heat transfer from the MOSFETs and chocks for better cooling performance.

Cooler by Design

PRIME B760 series features comprehensive cooling controls that are configurable via Fan Xpert 2+ software or via the UEFI BIOS.

Multiple Temperature Sources

Each header can dynamically reference three thermal sensors. Fan Xpert 2+ allows you to map the temperature of supported ASUS graphics cards to optimize cooling for GPU- and CPU-intensive tasks.

Smart Protection

A dedicated integrated circuit protects each fan header from overheating and overcurrent.

4-Pin PWM/DC Fan

Each onboard header supports auto-detection of PWM or DC fans.

PERFORMANCE

The PRIME B760 series are built to handle the high core counts and bandwidth demands of 13th Gen Intel® Core™ Processors. ASUS B760 motherboard provides all the fundamentals to boost daily productivity, so your system will be ready for action with stable power, intuitive cooling and flexible data transfer options.

Robust Power Design

Stable power is essential to extract every last bit of performance out of Intel® processors. The PRIME B760M-A D4 is geared to cater to the demands of these high-core-count CPUs.

ProCool Connector

Proprietary connectors augment the motherboard's link to the PSU with 8 pin connectors that pass 12 volts of power directly to the processors. Each jack features solid pins that can handle more current than hollow-pin connectors.

Six-Layer PCB Design

Multiple PCB layers optimize heat management for critical components, providing more headroom to push CPUs beyond stock speeds.

Memory
DDR4 Support
Improvements to trace routing design provide the latest Intel® processors with enhanced access to memory bandwidth. ASUS OptiMem II technology carefully maps memory signal pathways across different PCB layers to reduce path distance, and it adds shielding zones that significantly reduce crosstalk.

ASUS OptiMem II

Revisions to the motherboard’s trace routing provide the latest processors with unrestricted access to memory bandwidth. ASUS OptiMem II technology carefully maps memory signal pathways across different PCB layers to reduce vias and adds shielding zones that significantly reduce crosstalk.

Benefits of ASUS OptiMem II:
- Improved memory stability and compatibility
- Allows lower memory latencies at equivalent voltages
- Improved memory frequency margin

Storage
Two M.2 Slots (up to 64 Gbps)
The PRIME B760 motherboard offers a total of two M.2 slots that support data-transfer speeds of up to 64 Gbps via PCIe 4.0, enabling quicker boot-up and app load times with OS or application drives.

Connectivity
PCIe 4.0 Slot
The PRIME B760 motherboard is designed specifically for 13th and 12th Gen Intel® CPUs and offer PCIe 4.0 connectivity for the latest GPUs.

USB 3.2 Gen 1 Type-C®

Numerous USB ports support high-end rigs loaded with peripherals, including front USB Type-C® connectors with fast USB 3.2 Gen 1 for transmission speeds of up to 5 Gbps.

Realtek 2.5 Gb Ethernet

Realtek 2.5 Gb Ethernet reduces CPU overhead and offers exceptionally high TCP and UDP throughput for faster, smoother data transfers.

LANGuard

ASUS LANGuard is a hardware-level network protection feature that integrates advanced signal-coupling technology and premium anti-EMI surface-mounted capacitors to improve throughput and ensure a more reliable connection.

Combined onboard features deliver elevated audio

Intelligent design and premium hardware create audio quality unlike anything you’ve ever experienced.

Audio Shielding

Audio shielding ensures precision analog/digital separation and greatly reduced multi-lateral interference.

Dedicated Audio PCB Layers

Separate layers for left and right tracks ensures both channels deliver consistent, equal quality.

Premium Audio Capacitors

Provides warm, natural, and immersive sound with exceptional clarity and fidelity.

Aura Sync
Outshine the Competition
A well-tuned enthusiast system deserves a matching aesthetic. ASUS Aura offers full RGB lighting control with a variety of functional presets for the built-in RGB LEDs as well as strips and devices connected to the onboard RGB headers — and it can all be synced with an ever-growing portfolio of Aura-capable hardware.

Addressable Gen 2 Headers

Three Addressable Gen 2 headers are capable of detecting the number of LEDs on second-gen addressable RGB devices, allowing the software to automatically tailor lighting effects to specific devices. The new headers also offer backward-compatibility with existing Aura RGB gear.

Armoury Crate

Within a single intuitive interface, Armoury Crate offers easily customized Aura Sync RGB settings for every compatible device in your arsenal , plus controls for an ever-growing family of ASUS products, including keyboard and mouse preferences. Armoury Crate also integrates product registration and a news feed so that you never miss updates of interest to the ASUS community.

Techninė specifikacija

Procesorius	
Procesoriaus gamintojas	Intel
Procesoriaus lizdas	LGA 1700
Procesorių suderinamumas	„Intel® Celeron®“, Intel® Pentium® Gold, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9
Palaikomi procesoriaus lizdai	LGA 1700
Atmintis	
Palaikomi atminties tipai	DDR4-SDRAM
Atminties angų skaičius	4
Maksimali vidinė atmintis	128 GB
Atminties angų tipas	DIMM
Atminties kanalai	Dviejų kanalų
ECC suderinamumas	Ne-ECC
Palaikomi atminties laikrodžio greičiai	2133,2400,2666,2800,2933,3000,3200,3333,3400,3466,3600,3733,4000,4266,4400,4600,4800,5000,5066,5333 MHz
Palaikomas atmintinės taktinis dažnis (didžiausias)	5333 MHz

Nebuferizuota atmintis	Taip
Duomenų laikymo valdikliai	
Palaikomi saugojimo kaupiklių sąsajos	M.2, SATA III
Palaikomi saugojimo kaupiklių tipai	HDD & SSD
Palaikomų saugojimo tvarkyklių skaičius	6
RAID palaikymas	Taip
RAID lygiai	0, 1, 5, 10
Grafika	
Paralelinio apdorojimo technologijos parama	Nepalaikomas
Vidinis I/O	
USB 2.0 jungtys	2
USB 3.2 (3.1 1 kart.) jungtys	3
USB 3.2 (3.1 2 kart.) jungtys	0
SATA III jungčių skaičius	4
S/PDIF out jungtis	Taip
Priekinio skydelio audio jungtis	Taip
ATX maitinimo jungtis	Taip
CPU fan jungtis	Taip
Šasi fenų jungčių skaičius	2
EPS maitinimo jungtis (8-kaisčiai)	Taip
COM jungčių skaičius	1
TPM jungtis	Taip
12 V maitinimo jungtis	Taip
RGB LED kontaktų pagrindas	Taip
Galinė panelė I/O jungtys	
USB 2.0 portų kiekis	4
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	0
USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius	0
USB 3.2 2 kart. (3.1 2 kart.) A tipo prievadų skaičius	2
USB 3.2 2 kart. (3.1 2 kart.) C tipo prievadų skaičius	0

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Ethernet LAN (RJ-45) portų kiekis	1
VGA (D-Sub) portų kiekis	0
HDMI portų kiekis	2
DVI-D prievadų skaičius	0
PS/2 portų kiekis	1
HDMI versija	2.1
„DisplayPort“ kiekis	1
„DisplayPort“ versija	1.4
Ausinių išvestys	3
Mikrofonas, line-in jack	Taip

Tinklas

„Wi-Fi“	Ne
Ethernet LAN jungtis	Taip
Eterneto sąsajos tipas	2.5 Gigabit Ethernet
„Wi-Fi“ standartas	Nepasiekiama

Savybės

Taikoma	PC
Motininės plokštės formos faktorius	„micro ATX“
Motininės plokštės sisteminio valdiklio šeima	Intel
Pagrindinės plokštės lustas	Intel B760
Garso išvesties kanalai	7.1 kanalai
Palaikomos „Windows“ operacinės sistemos	Windows 10 x64, Windows 11

Plėtotės lizdas

PCI „Express“ x1 (3.x kart.) angos	1
„PCI Express x16“ (4 kartos) lizdai	3
M.2 (M) angų skaičius	2

BIOS

BIOS tipas	UEFI AMI
BIOS atminties dydis	256 Mbit

Svoris ir matmenys

Plotis	244 mm
Ilgis	244 mm

Pakuotės turinys

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Pridėti kabeliai	SATA
Matmenys ir svoris	
Matmenys (I × P × A)	26,00cm × 27,00cm × 5,00cm
Svoris	1,04kg

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

ASUSTeK Computer Inc
Li-Te Road 15, 112 Taipei, TW
asus.com

ATSAKINGAS ASMUO ES

ASUS France S.A.R.L.
Allee bienvenue 10, 93160 Paris, FR
channel.asus.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt