TP-Link Omada AX3000 Ceiling Mount WiFi 6 Access Point

Gamintojas: **TP-LINK** · Modelis: **EAP653** · EAN: **4897098685235** · Prekės kodas: **433256**



104.89€

Kaina su PVM

Be PVM: **86.69€**

In Stock



Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Ultra-Fast WiFi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 2402 Mbps on 5 GHz totals 2976 Mbps WiFi speeds.†
- ✓ High-Efficiency WiFi 6: More connected devices can enjoy faster speeds
- ✓ Centralized Cloud Management: Omada SDN integration manages the whole network locally or from the cloud via web UI or Omada app
- ✓ 160 MHz Channel: Double the data at peak transmission times on a single stream with HE160.‡
- ✓ Seamless Roaming: Video streams and voice calls are unaffected as users move between locations.§
- ✓ Omada Mesh: Enables wireless connectivity between access points for extended range and flexible deployment.§
- ✓ PoE+ Powered: Supports both 802.3at PoE+ and DC (DC adapter sold separately) power supply for flexible installations
- ✓ Ultra-Slim Design: Φ160 mm × 33.6 mm elegant design brings more agility








Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903



Aprašymas

Power up Your Business with New-Era Business WiFi 6

WiFi 6 brings faster speeds, lower lag, less interference, and higher capacity.

Seamless Integration into Omada SDN

The Omada Software Defined Networking (SDN) platform integrates network devices, including access points, switches, and routers. It provides 100% centralized cloud management and creates a highly scalable network controlled from a single interface.

Auto Channel Selection and Power Adjustment
to Optimize Overall Performance*
Provides powerful wireless performance while significantly reducing WiFi interference by automatically adjusting the channel settings and transmission power levels of neighboring APs in the same network.

Easy Deployment & Higher Performance by Omada Mesh§
Easy Pairing, Less Wiring
With Mesh technology, Omada EAPs save you from extra wires by wirelessly extending your WiFi signal further and more flexibly to hard-to-wire areas.

Optimized Network Performance

Intelligent self-organization optimizes the best path between EAPs while self-healing ensures you stay online even when one AP is disrupted.

Always Stay Smooth with Fast Roaming§

Ensures customers to enjoy uninterrupted streaming when moving around by switching clients automatically to the access points with the optimal signal.

Ultra-Slim Design Brings More Agility

Exceptional performance with compact design ensures simple WiFi installation while saving space. The elegant appearance makes EAP653 perfectly blend into any modern office, hotel, classroom, or café.

Techninė specifikacija

Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	2976 Mbit/s

Maximum data transfer rate (2.4 GHz)	574 Mbit/s
Maximum data transfer rate (5 GHz)	2402 Mbit/s
Ethernet LAN data rates	10,100,1000 Mbit/s
Frequency band	2.4 - 5 GHz
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11h
Cabling technology	10/100/1000Base-T(X)
Number of users	250 user(s)
Automatic channel selection	Yes
Automatic channel scanning	Yes
MIMO	Yes
MIMO type	Multi User MIMO
Spread spectrum method	OFDMA
Fit AP mode features	Mesh networking
VLAN support	Yes
Rate limiting	Yes
Flow control support	Yes
Band steering	Yes
Airtime Fairness (ATF)	Yes
Quality of Service (QoS) support	Yes
BeamForming	Yes
Transmitting power (CE)	27 dBm
Transmitting power (FCC)	22 dBm
Security	
Security algorithms	HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA, WPA2, WPA3
MAC address filtering	Yes
Management features	
Web-based management	Yes
Syslog	Yes
Firmware upgradeable	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
USB 2.0 ports quantity	0
DC-in jack	Yes
Power	

Power over Ethernet (PoE)	Yes
DC voltage range	12 V
Design	
Placement	Ceiling, Wall
Product colour	White
Reset button	Yes
LED indicators	Yes
Antenna	
Antenna type	Internal
Weight & dimensions	
Width	160 mm
Depth	160 mm
Height	33.6 mm
Packaging data	
Package type	Box
Packaging content	
Quantity per pack	1 pc(s)
Mounting kit	Yes
Quick start guide	Yes
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%
Matmenys ir svoris	
Matmenys (I × P × A)	25.00cm × 23.00cm × 6.00cm
Svoris	0.75kg

Dokumentai ir vaizdo įrašai

- User manual
- Product leaflet

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

MANUFACTURER

TP-Link

EU RESPONSIBLE PERSON

TP-Link Deutschland GmbH
Niederkasseler Lohweg 175, 40547 Düsseldorf, DE
tp-link.com

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.