Zebra ZD230 etikečių spausdintuvas Perkėlimas terminiu būdu 203 x 203 DPI 152 mm/sec Vielinis Ethernet LAN jungtis

Gamintojas: **ZEBRA** · Modelis: **ZD23042-30EC00EZ** · EAN: **8596375234338** · Prekės kodas: **433616**



292,90 €

Kaina su PVM

Be PVM: **242,07 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Perkėlimas terminiu būdu
- ✓ 203 x 203 DPI
- ✓ Didžiausias spausdinimo plotis: 10,4 cm Spausdinimo greitis: 152 mm/sec
- ✓ Įdiegti brūkšniniai kodai: 1D, 2D, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Duomenų matrica, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, PDF417, POSTNET, QR Code, UPC-A, UPC-E
- ✓ Ryšio technologija: Vielinis
- ✓ USB prievadas Ethernet LAN jungtis
- ✓ 1,1 kg








Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Aprašymas

Not all printers are created equally, especially basic models. To reduce costs, value printers are often constructed using less expensive components and fewer features. Many fail to perform under more demanding duty cycles, create delays and downtime for repairs, and require replacement after only a few years of use. Instead of conserving budget, customers are left with greater expense and hassle. Zebra does it differently. Meet the exception. The ZD230 desktop printer gives you extra features and reliable operation at an affordable price—both at the point of purchase and across the entire lifecycle. Engineered with Zebra quality, it boasts a dual wall construction. And, it offers wireless connectivity for networked, remote printing. Built to last for years, the ZD230 provides an outstanding return on your investment.

Just the Features You Need

This 4-inch printer produces labels quickly, up to 6” per second, to keep your workflows moving. Increased memory allows you to store more fonts and graphics. A single LED indicator and single button for feed/pause make it easy to operate and identify printer status. Choose from direct thermal or thermal transfer models, and add an optional factory-installed peeler or cutter. The ZD230 features a core set of Print DNA software applications, powered by Link-OS Basic, to deliver a cost-effective and dependable print experience. It is ideal for use in transportation and logistics, light manufacturing, retail and healthcare applications to print a variety of tickets, tags, passes, labels and receipts.

Backed by Zebra’s Worldwide Service and Support

Access support quickly anywhere around the globe through Zebra’s trusted network of more than 10,000 partners. Avoid costly repairs and downtime with an affordable service plan that’s tailored to the coverage you need for your desktop printer. Zebra’s OneCare SV provides the right level of service at the right price. It gives you two years of coverage for normal wear and tear, double the standard warranty coverage, priority turnaround times at the depot and more—all for a tiny fraction of the cost of a single repair.

Consistently Exceptional Zebra Certified Supplies

Printing supplies can impact everything from printhead lifespan to operational efficiency. That’s why we design, produce and rigorously pretest our own line of thermal printing supplies to ensure consistent, optimised performance in your Zebra printer—and peace of mind for you. For industry-leading quality, service and thermal printing expertise, choose Zebra Certified Supplies.

The ZD230 gives you more. The quality and reliability you expect from Zebra, along with the extra features you need. And, it helps you conserve costs now, and for years to come. Gain your competitive edge with Zebra.

Get Printing Quickly

The ZD230 is simple to install and begin printing – right out of the box. Easily replace legacy printers using ZPL, EPL or non- Zebra command languages. USB, Ethernet, Wi-Fi and Bluetooth® connectivity options enable universal interoperability. The ZD230 can accommodate a 300 M ribbon roll to lengthen the time between media changes. And, Zebra’s OpenACCESS™ clamshell design expedites media replacement. It’s also ENERGY STAR® qualified to reduce your operational expenses.

Techninė specifikacija

Spausdinimo greitis	
Spausdinimo technologija	Perkėlimas terminiu būdu
Spalva	Ne
Maksimali rezoliucija	203 x 203 DPI
Spausdinimo greitis	152 mm/sec
Didžiausias spausdinimo plotis	10,4 cm

Popieriaus tiekimas	
Kaspino plotis	10,9 cm
Juostos ilgis	300 m
Maksimalus etiketės plotis	11,2 cm
Maksimalus etiketės ilgis	0,991 m
Maksimalus rulono diametras	12,7 cm
Ruošinio storis	0.08 - 0.1905 mm
Palaikomas popieriaus plotis	25.4 - 112 mm
Šerdies skersmuo	1,27 cm
Ryšys	
Ryšio technologija	Vielinis
Ethernet LAN jungtis	Taip
„Wi-Fi“	Ne
USB prievadas	Taip
Bluetooth	Ne
USB 2.0 portų kiekis	1
Veikimo charakteristikos	
Puslapio aprašymo kalbos	EZPL, XML, ZPL II
Vidinė atmintis	128 MB
Flash atmintis	256 MB
Įdiegti brūkšniniai kodai	1D, 2D, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Duomenų matrica, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, PDF417, POSTNET, QR Code, UPC-A, UPC-E
Šriftų skaičius	23
Sertifikavimas	IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus, CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM
Konstrukcija	
Produkto spalva	Juoda
Ekranas	Ne
Įmontuotas ekranas	Ne
Energijos valdymas	
AC įėjimo įtampa	100 - 240 V
AC įėjimo dažnis	50 - 60 Hz
Aplinkos sąlygos	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Darbo santykinės drėgmės diapazonas	10 - 90%
Sandėliavimo santykinis drėgmės diapazonas	5 - 95%
Darbo temperatūros diapazonas (TT)	4,4 - 41 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 60 °C
Svoris ir matmenys	
Plotis	197 mm
Ilgis	267 mm
Aukštis	191 mm
Svoris	1,1 kg
Pakuotės duomenys	
Kiekis pakuotėje	1 vnt
Pakuotės turinys	
Pridėti kabeliai	AC
Logistikos duomenys	
Darniosios sistemos (DS) kodas	84433210
Techninė informacija	
Tvarumo sertifikatai	ENERGY STAR
Matmenys ir svoris	
Svoris	3,48kg

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Zebra

ATSAKINGAS ASMUO ES

Zebra Technologies
Borupvang 3, Ballerup, DK
zebra.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.