iiyama TF1515MC-B2 kompiuterio monitorius 38,1 cm (15") 1024 x 768 pikseliai XGA LED Lietimui jautrus ekranas Juoda

Gamintojas: **IIYAMA** · Modelis: **TF1515MC-B2** · EAN: **4948570116751** · Prekės kodas: **436985**



449,90 €

Kaina su PVM

Be PVM: **371,82 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 38,1 cm (15") Juoda
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekrano forma: Plokščias
- ✓ Maksimalus atnaujinimo dažnis: 75 Hz Reakcijos laikas: 8 ms
- ✓ 1024 x 768 pikseliai XGA Skydo tipas: TN
- ✓ Energijos vartojimo efektyvumo klasė (SDR): E ErP CB, CE, cULus, EAC, REACH, RoHS, WEEE


















Aprašymas

The ProLite TF1515MC-B2 (15 inch) uses PCAP touch technology and is built into an eye-catching bezel with edge-to-edge glass. Thanks to a glass overlay covering the screen and a rugged bezel, it guarantees high durability and scratch-resistance, making it perfect for kiosk and high use public facing applications. Equipped with a foam seal finish it supports seamless integration into kiosks and provides IP65 rating resulting in dust and water resistance from the front. Landscape, portrait and face-up orientation ensures flexible mounting possibilities in almost any installation. For ease of integration, the TF1515MC-B2 can be equipped with optional external mounting brackets (OMK2-1) making it an ideal solution for kiosk integrators, industrial environments, control rooms and interactive multimedia.

Techninė specifikacija

Display	
Display diagonal	38.1 cm (15")
Display resolution	1024 x 768 pixels
Native aspect ratio	4:3
Display technology	LED
Touchscreen	Yes
HD type	XGA
Panel type	TN
Response time	8 ms
Screen shape	Flat
Contrast ratio (typical)	800:1
Maximum refresh rate	75 Hz
Display number of colours	16.2 million colours
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	350 cd/m²
Display brightness	315 cd/m²
Aspect ratio	4:3
Viewing angle, horizontal	160°
Viewing angle, vertical	150°
Pixel pitch	0.297 x 0.297 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Horizontal scan range	31.4 - 60 kHz
Viewable size, horizontal	30.4 cm
Viewable size, vertical	22.8 cm
Display diagonal (metric)	38 cm
Surface hardness	7H
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Windows operating systems supported	Yes
Linux operating systems supported	Yes
Multimedia	
Built-in camera	No
Built-in microphone	No
Design	
Product colour	Black
Front bezel colour	Black
Glass thickness	6 mm
Ports & interfaces	
HDMI	Yes
USB Touch port	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Number of OSD languages	7
Plug and Play	Yes
LED indicators	Yes
Power	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Energy efficiency class (SDR)	E
Energy consumption (SDR) per 1000 hours	10 kWh
Power consumption (typical)	16 W
Power consumption (standby)	1.2 W
Power consumption (off)	1.2 W
AC adapter output voltage	12 V
Power supply type	External
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Width (with stand)	364 mm
Depth (with stand)	41.5 mm
Height (with stand)	291 mm
Weight (with stand)	2.9 kg
Width (without stand)	364 mm
Depth (without stand)	291 mm
Height (without stand)	41.5 mm
Weight (without stand)	2.9 kg
Packaging data	
Package width	460 mm
Package depth	175 mm
Package height	470 mm
Package weight	4.6 kg
Packaging content	
Cables included	AC, USB, HDMI, DisplayPort
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP
Other features	
International Protection (IP) code	IP65
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

AC adapter included	Yes
Display viewable area (HxV)	304.1 x 228.1 mm
Placement supported	Horizontal/Vertical
Brightness	315 cd/m²
Packaging content	AC adapter, Touch Panel Driver Disk (CD-ROM), external control pad
Active display area (W x H)	304.1 x 228.1 mm
Weight	2.9 kg
Height	291 mm
Width	364 mm
Depth	41.5 mm
Compliance certificates	CB, CE, cULus, EAC, REACH, RoHS, WEEE
Certification	CB, CE, TÜV-Bauart, EAC, cULus
User controls	picture (contrast, brightness, H.position, V.position, H.size, phase, clock, auto adjust), advanced (colour temperature, sharpness), OSD (OSD timeout, OSD position, OSD H.position, OSD V.position, touch switch), option (reset, language, source select, display mode, factory)
Touch method	stylus, finger, glove (latex)
Control panel	menu,scroll up/ brightness, scroll down/ contrast, select, power

Logistics data


Products per pallet	44 pc(s)
Pallet net width	86 cm
Pallet net length	12 cm
Pallet net height	97 cm
Harmonized System (HS) code	85285210

Matmenys ir svoris

Matmenys (I × P × A)	46,00cm × 41,00cm × 18,00cm
Svoris	5,20kg


Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Energijos efektyvumas ir ekologinis projektavimas



Energijos efektyvumo klasė **E** A–G

- Energijos etiketė
- Gaminio informacijos lapas
- EPREL duomenų bazė



Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International
Wijkermeerstraat 8, 2131 HA Hoofddorp, NL
iiyama.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt