

Digital Signage Display AG Neovo PM-3202, 32" Full HD Monitor, Slim Bezel, 16/7 Operation



Modelis: PM322011M0000

Gamintojas: AG NEOVO

EAN: 4710739597028

Prekės kodas: 437093

508.99€

Digital Signage Display AG Neovo PM-3202: Professional 32" Full HD Monitor

The AG Neovo PM-3202 is a highly reliable 32-inch Full HD (1920x1080) digital signage flat panel designed for demanding commercial environments. Featuring a slim bezel and 350 cd/m² brightness, this display ensures crystal-clear visibility, making it perfect for retail, hospitality, corporate meeting areas, or medical offices. Optimized for extended use, the PM-3202 uses a high-quality VA panel

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

technology and supports 16/7 operation.

Unmatched Reliability and Commercial Features

Built for continuous operation, this display integrates patented technology and essential connectivity to simplify content delivery and maintenance.

- **Full HD VA Panel:** Enjoy superb image quality with a 1920 x 1080 resolution, a high typical contrast ratio of 4000:1, and wide 178° horizontal and vertical viewing angles.
- **16/7 Operational Reliability:** Engineered to perform reliably for 16 hours a day, 7 days a week, making it suitable for standard commercial schedules.
- **Patented Anti-Burn-in™ Technology:** AG Neovo's proprietary technology actively prevents image ghosting and burn-in, significantly extending the lifespan and performance of the display.
- **Integrated Content Scheduler:** Use the built-in OSD menu scheduler and USB 2.0 playback functionality to easily manage and broadcast content based on time, day, or input source via the included remote control.
- **Enhanced Image Clarity:** Features embedded image enhancer capabilities including 3D Deinterlace and Noise Reduction to ensure visual clarity even in demanding, busy environments.
- **Black-Level Alignment:** Easily adjust the brightness level in dark image areas using the remote control.

Connectivity and Management

- **Versatile Inputs:** Includes 3 HDMI 2.0 input ports, RS-232 interface for external control, and Ethernet LAN (RJ-45) support (up to 1000 Mbit/s) for network connectivity.
- **Audio Capability:** Features built-in speakers (2) with 20 W RMS rated power.
- **Remote Management:** Utilize the free PID Command & Ctrl Software for remote monitoring, colour calibration, temperature checks, and easy video wall display management.
- **Easy Installation:** Supports VESA mounting interfaces (100 x 100 mm and 200 x 200 mm).

AG NEOVO specializes in designing and manufacturing professional-grade display solutions known for their durability, superior performance, and patented protection technologies tailored for commercial and demanding environments.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Order today from ++SHOP++ as we offer the best digital signage solutions and dedicated customer support.

The new PM-3202 32-inch 1080P slim bezel digital signage display is given the easy-to-use content scheduler with USB playback, 1920×1080 Full HD resolution with an Anti-Burn-in™ Technology, 350 nits brightness, and 16/7 operation. The PM-3202 slim bezel display is ideal for digital signage applications in any commercial setting, including restaurants, retail stores, medical offices, corporate meeting areas or hotels.

FULL HD VISIBILITY FOR COMMERCIAL USE

The PM-3202 slim bezel display combines Full HD 1920×1080 resolution, 350 nits of brightness, and 16/7 commercial operation times to easily deliver business messaging and boost customer engagement.

INTEGRATED CONTENT SCHEDULER

The built-in integrated scheduler in the OSD menu allows you to easily broadcast content based on different input sources, time, and day by IR remote control.

EMBEDDED IMAGE ENHANCER

The embedded image enhancer features a 3D Deinterlace and Noise Reduction to solve image issues - offering crystal clarity to the most demanding environments.

BLACK-LEVEL ALIGNMENT

Black-level setting - easily adjust the level of brightness from the dark area of the images by remote control.

PATENTED ANTI-BURN-IN TECHNOLOGY

To combat the effects of traditional LCD burn-in or ghosting, AG Neovo utilises its patented Anti-Burn-in™ Technology to prevent image burn-in and assure the extended life span for displays.

VERSATILE CONNECTIVITY FOR MULTIMEDIA PLAYBACK

This 32-inch slim bezel digital signage display integrates diverse connectivity, including HDMI, VGA,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

RS232, RJ45 to connect external devices. In addition, the display supports USB playback functionality and users can directly playback multimedia content via a LAN connection.

FREE PID COMMAND & CTRL SOFTWARE

PID Command & Ctrl provides intuitive user interfaces for remote management via laptops and mobile devices and offers easy creation on video wall displays. The software also has simple colour calibration, temperature check, IR/key locking options, and time on usage monitoring for daily maintenance.

Power consumption (typical): 42 W | DVI port: No | Display brightness: 350 cd/m² | Microphone in: Yes | Display technology: TFT | Panel mounting interface: 100 x 100 mm | Pixel pitch: 0.364 x 0.364 mm | On Screen Display (OSD): Yes | USB version: 2.0 | HDMI version: 2.0 | Panel type: VA | Wi-Fi: No | VESA mounting: Yes | USB port: Yes | HDMI ports quantity: 3 | Warnings: Unplug the monitor from the power source before cleaning. | RS-232 interface: Yes | Computer system: No | Haze rate: 2% | Touchscreen: No | Built-in processor: No | Ethernet LAN: Yes | Power consumption (standby): 0.5 W | LED backlighting type: LED | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Panel mounting interface: 200 x 200 mm | Remote (IR) input: 1 | Vertical scan range: 48 - 85 Hz | Contrast ratio (typical): 4000:1 | Remote control included: Yes | HDMI input ports quantity: 3 | Noise reduction: Yes | Purpose: Universal | Built-in speaker(s): Yes | Operating hours (hours/days): 16/7 | Number of built-in speakers: 2 | Surface hardness: 3H | Power adapter included: Yes | Product design: Digital signage flat panel | RMS rated power: 20 W | Horizontal scan range: 28 - 92 kHz | Energy efficiency class (SDR): G | USB ports quantity: 1 | Cables included: HDMI | Product colour: Black | Storage temperature (T-T): 20 - 80 °C | Viewing angle, horizontal: 178° | HD type: Full HD | Response time: 5 ms | AC input voltage: 100 - 240 V | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 10 | Display number of colours: 16.7 million colours | Storage relative humidity (H-H): 10 - 90% | Display resolution: 1920 x 1080 pixels | Ethernet LAN (RJ-45) ports: 1 | AC input frequency: 50 - 60 Hz | Quick start guide: Yes | Operating relative humidity (H-H): -20 - 60% | Power consumption (off): 0.3 W | Display diagonal: 81.3 cm (32") | Ethernet LAN data rates: 1000 Mbit/s | Viewing angle, vertical: 178°

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903