

AG Neovo 65-Inch 4K Commercial Display

Gamintojas: **AG NEOVO** · Modelis: **PD65Q011M000** · EAN: **4710739596854** · Prekės kodas: **437299**



2 382,90 €

Kaina su PVM

Be PVM: **1 969,34 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4K UHD 3840 x 2160 resolution
- ✓ 700 nits high brightness panel offers clear images in bright areas
- ✓ Anti-Burn-in technology prevents image ghosting
- ✓ Intel SDM slot ready for easy media player/IPC integration
- ✓ IR/ RS232/ RJ45 connection for easy control and management



Aprašymas

The PD-65Q 65-inch 4K commercial display features its 700 nits high brightness, suitable for use in different semi-outdoor environments, such as airport terminals, control rooms, and shopping malls. It integrates a full slate of input sources, including an embedded USB playback function, various I/O ports, and Intel® SDM slot. It allows you to broadcast multimedia content horizontally or vertically and it can meet different kinds of digital signage solutions as well as video wall installations.

700 nits High Brightness

The PD-65Q commercial display features 4K UHD, 10-bit colour depth, and 178-degree viewing angle for brilliant colour performance. Besides that, the PD-Series adopts a 700 nits brightness commercial-grade panel to deliver clear, bright, and detailed imagery even in the daylight or bright indoor environments.

IPS Panel for 24/7 Use

Designed for 24/7 operation, the display is produced to meet the highest standard of IPS panel technology and take advantage of superior components to ensure a long product lifetime in demanding environments.

Landscape/Portrait Capability

This commercial-grade display is signage-friendly and can perfectly fit either in a landscape or in a portrait mode to experience complete screen orientation flexibility and fulfill the need in different scenarios.

Optional Intel® SDM Capability

The built-in SDM slot is designed for Intel® smart display module, which is ready to deliver a powerful smart signage functionality for more user-friendly applications.

Patented Anti-Burn-in™ Technology

To combat the effects of traditional LCD burn-in or ghosting, AG Neovo utilises its patented Anti-Burn-in Technology to prevent image burn-in and assure the extended life span for displays.

DisplayPort/IR/RS232 Daisy Chain Functionality

With DisplayPort daisy chain functionality, the video and audio can be delivered to multiple AG Neovo's large format displays using DisplayPort cables, and it saves a significant amount of time. IR/RS232 loop-through capability provides a convenient single point of control for multi-display installation.

Embedded Image Enhancer

The embedded image enhancer features a 3D Comb Filter, 3D Deinterlace, and Noise Reduction to solve image issues – offering crystal clarity to the most demanding environments.

Integrated Content Scheduler

The built-in integrated scheduler in the OSD menu allows you to easily broadcast content based on source, time, and day by IR remote control.

PID Command & Ctrl Software

PID Command & Ctrl provides intuitive user interfaces for remote management via laptops and mobile devices and offers easy creation on video wall displays. The software also has simple colour calibration, temperature check, IR/key locking options, and time on usage monitoring for daily maintenance.

Techninė specifikacija

Specifications

Sandėlio grupė Large Format Displays [+292][[-2]

Display

Display diagonal	163.8 cm (64.5")
Display technology	LCD
Display resolution	3840 x 2160 pixels
Display brightness	700 cd/m²

HD type	4K Ultra HD
Touchscreen	No
Panel type	IPS
LED backlight	Yes
Response time	5 ms
Contrast ratio (typical)	1200:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Pixel pitch	0.372 x 0.372 mm
Number of displays	1
Horizontal scan range	31 - 92 kHz
Vertical scan range	48 - 85 Hz
Haze rate	25%
Surface hardness	2H
Colour gamut	72%

Ports & interfaces

HDMI ports quantity	3
DVI port	Yes
DisplayPorts quantity	2
USB port	Yes
HDMI version	2
DVI-I ports quantity	1
DisplayPorts in	1
DisplayPorts out	1
USB ports quantity	2
USB version	2
Ethernet LAN (RJ-45) ports	1
RS-232 interface	Yes
Infrared data port	Yes
Remote (IR) input	1
Remote (IR) output	1
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)

Audio

Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	10 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal/Vertical
Panel mounting interface	400 x 400 mm
Anti-glare screen	Yes
Performance	
Purpose	Commercial
Operating hours (hours/days)	24/7
Power	
Power consumption (standby)	0.5 W
Power consumption (off)	0 W
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	199 kWh
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G
Computer system	
Computer system	No
Built-in processor	No
Weight & dimensions	
Display width	1462.3 mm
Display depth	93.4 mm
Display height	837.3 mm
Display weight	27.8 kg
Packaging data	
Package width	1580 mm
Package depth	151 mm
Package height	1050 mm

Package weight	33.9 kg
Packaging content	
Remote control included	Yes
Batteries included	Yes
Cables included	AC, HDMI
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 90%
Certificates	
Certification	FCC CE LVD ICES-003(Issue 7) WEEE RoHS REACH
Logistics data	
Harmonized System (HS) code	85285210
Network	
Ethernet LAN	Yes
Wi-Fi	No
Features	
Wall mountable	Yes
Technical details	
Compliance certificates	RoHS
I/O ports	SDM Slot
Other features	
Quick start guide	Yes
Audio input	1
Audio output	1
RS-232 input ports	1
RS-232 output ports	1
Matmenys ir svoris	
Matmenys (I × P × A)	159,00cm × 106,00cm × 16,00cm
Svoris	32,00kg