

Monitorius DELL P2425DE 24



colių QHD Verslo

Ekranas

2560x1440 IPS

100Hz su 90W

USB-C

Koncentratoriumi

Modelis: P2425DE

Gamintojas: DELL

EAN: 5397184962466

Prekės kodas: 438412

309.99€

DELL P2425DE 24 colių QHD Monitorius: Didesnis

Produktyvumas ir Komfortas

DELL P2425DE Pro Plus monitorius sukurtas reikiams profesionalioms darbo aplinkoms, siūlantis aukštos raiškos, sklandaus veikimo ir išskirtinio jungiamumo derinį. Šis ekranas, turintis ryškią 23,8

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

colio (24") Quad HD (2560 x 1440) raiškos IPS matricą, pateikia 1,77 karto daugiau detalių nei standartinis Full HD, užtikrindamas puikų aiškumą dirbant su lentelėmis, grafika ir atliekant kelias užduotis vienu metu.

Turėdamas TÜV 4 žvaigždučių akių komforto sertifikatą, P2425DE naudoja „Flicker-free“ (nemirgančio vaizdo) ir „Low Blue Light“ (sumažintos mėlynos šviesos) technologijas, kurios padeda sumažinti akių nuovargį ilgų darbo sesijų metu. Reaguojantis 100 Hz atnaujinimo dažnis ir 5 ms (GTG) greitas atsako laikas suteikia pastebimai sklandesnę žiūrėjimo patirtį, palyginti su tradiciniais 60 Hz ekranais.

Nepriekaištingas Jungiamumas ir Maitinimo Tiekimas

Paverskite savo stalą supaprastinta darbo vieta, naudodami integruotą USB-C koncentratorių. Vienas USB-C laidas perduoda duomenis, vaizdo signalą ir užtikrina įspūdingą maitinimo tiekimą, todėl šis monitorius yra puikus prijungimo (docking) sprendimas nešiojamiems kompiuteriams.

- **QHD Raiška (2560x1440):** Mėgaukitės aukščiausia detalizacija ir dideliu ekrano plotu efektyviam darbui.
- **Integruotas 90W USB-C Maitinimo Tiekimas (PD):** Įkraukite prijungtą nešiojamą kompiuterį tiesiogiai, išlaikydami tvarkingą darbo vietą.
- **Didelės Spartos Jungtys:** Yra patikimas USB 3.2 Gen 1 koncentratorius, HDMI 2.1, DisplayPort 1.4 ir specialus RJ-45 Ethernet prievadas stabiliam tinklo ryšiui.
- **IPS Matricos Technologija:** Platus 178° žiūrėjimo kampas ir pastovios, tikslios spalvos (99% sRGB aprėptis).
- **100 Hz Atnaujinimo Dažnis:** Užtikrina sklandų judesio aiškumą, svarbų slenkant turinį ir žiūrint dinamišką vaizdą.
- **Išplėstinė Ergonomika:** Lengvai reguliuokite žiūrėjimo padėtį sukant, paverčiant, pasukant (portreto režimas) ir reguliuojant aukštį iki 150 mm.
- **Sertifikuotas Akių Komfortas:** TÜV 4 žvaigždučių sertifikatas garantuoja komfortą, sumažinant mirgėjimą ir mėlynos šviesos spinduliavimą.

Dizainas ir Tvarumas

Matini paviršius ir anti-glare danga sumažina atspindžius, užtikrindama produktyvumą net ryškioje aplinkoje. Sukurtas atsižvelgiant į tvarumą, P2425DE atitinka griežtus aplinkosaugos standartus,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsilygiant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

įskaitant ENERGY STAR ir TCO, ir yra pagamintas be kenksmingų medžiagų, tokių kaip arsenas, gyvsidabris, PVC ar BFR.

DELL yra visame pasaulyje pripažintas kompiuterinių technologijų lyderis, vertinamas už patikimą, novatoriškų ir didelio našumo IT sprendimų, pritaikytų verslui ir įmonėms, tiekimą.

Užsisakykite šiandien iš ++SHOP++, nes siūlome geriausias kainas ir profesionalų klientų aptarnavimą jūsų verslo technologijų poreikiams.

Stay productive with this 23.8-inch QHD monitor featuring extensive connectivity, and certified by TÜV for 4 star eye comfort.

Stay productive with this 23.8-inch QHD monitor featuring extensive connectivity, and certified by TÜV for 4 star eye comfort.

- 61.0cm (24") Quad HD 2560 x 1440 Edge LED IPS
- 8ms, 16:9, 250cd/m², 1500:1
- USB, HDMI, DisplayPort

Actual configuration might differ from illustration

Product Carbon Footprint (PCF):

1. Dell generally uses the PAIA (Product Attribute to Impact Algorithm)(<http://msl.mit.edu/projects/paia/main.html>) tool for product carbon footprint calculations.
2. Docking station related PCFs are extracted from corresponding LCAs and as such do not follow the PAIA methodology used for calculating other PCFs in this report.
3. PAIA method is developed by the Massachusetts Institute of Technology's Materials Systems Laboratory and partners.
4. All estimates of carbon footprint are uncertain. Dell Technologies reports the 5th and 95th percentile of the carbon footprint estimate to reflect this uncertainty wherever possible. (<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>)
5. Please note the emission estimate in this report is calculated using the mean value along with the standard deviation for that product model.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

6. Use of default inputs (i.e. not primary data) and assumptions on location of use and other fields can introduce a standard deviation which must be taken into account while completing the calculations.
 7. Please note, PAIA uses the ecoinvent Database (<https://ecoinvent.org/the-ecoinvent-database/>) whenever primary data is not made available for calculations.
 8. For client and commercial end user computing products, minimum configurations were assumed for calculations. For Server and Storage products, typical configurations or ENERGY STAR (<https://www.energystar.gov/products>) configurations were used for calculations.
 9. Use Phase emissions were calculated based on the location of use as "Europe" i.e. the Use Phase emissions are not specific to a single country / location.
 10. The report does provide an option for a total emissions number for manufacturing, transport and end of life while leaving the use phase emissions out, in case the customer uses their own calculation methodology for use phase emissions.
 11. The lifetime usage assumption at the product family level is as follows: Desktop, Notebook - 4 years, Display - 5 years and Servers - 4 years.
 12. For detailed assumptions please refer to the product datasheets in the Dell Technologies reports (<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>).
 13. The results from the PAIA tool are liable to change over time as the methodology is improved and datasets are updated. The PAIA version used to calculate emissions has been indicated with each record in the report.
 14. Metrics used: The units for global warming potential are in kgCO₂-equivalent or MT (metric ton) CO₂-equivalent (CO₂e).
 15. Beginning in June 2024, the data dashboard now incorporates PCF values computed using the Dell PCF calculator. It's important to note that the default location utilized for these calculations shown on the data dashboard is Europe. To access PCF values calculated for the USA and China locales, please refer to the Product PCF PDF document on Dell.com.
- Summary: DELL Pro Plus P2425DE. Display diagonal: 61 cm (24"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black | Vendor Homepage: <https://www.dell.com/en-uk/shop/dell-pro-24-plus-qhd-usb-c-hub-monitor-p2425de/apd/210-brdm/monitors-monitor-accessories> | Anti-glare screen: Yes | Backlight type: Edge LED | Contrast

ratio (typical): 1500:1 | Digital horizontal frequency: 30 - 150 | Digital vertical frequency: 48 - 100 | Display brightness (typical): 250 | Display diagonal: 24 | Display number of colours: 16.7 million colours | Display resolution: 2560 x 1440 | Display technology: LCD | HD type: Quad HD | LED backlight: Yes | Maximum refresh rate: 100 | Native aspect ratio: 16:9 | Panel type: IPS | Pixel density: 123 | Pixel pitch: 0.2058 x 0.2058 | Response time: 8 | Response time (fast): 5 | Response time measurement type: GTG (Gray to Gray) | Screen shape: Flat | sRGB coverage (typical): 99 | Supported video modes: 1080i/1080p/1440p/480p/576p/720p | Surface hardness: 3H | Touchscreen: No | Viewable size, horizontal: 526.85 | Viewable size, vertical: 296.35 | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | AMD FreeSync: No | Flicker-free technology: Yes | Low Blue Light technology: Yes | NVIDIA G-SYNC: No | Built-in camera: No | Built-in speaker(s): No | Market positioning: office | Product colour: Black | Built-in USB hub: Yes | DisplayPort out quantity: 1 | DisplayPort version: 1.4 | DisplayPorts quantity: 1 | HDCP: Yes | HDCP version: 1.4 | HDMI: Yes | HDMI ports quantity: 1 | HDMI version: 2.1 | Headphone out: No | Number of USB Type-C upstream ports quantity: 1 | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | USB Power Delivery (USB PD): Yes | USB Power Delivery up to: 90 | USB Type-A downstream ports quantity: 3 | USB Type-C DisplayPort Alternate Mode: Yes | USB Type-C downstream ports quantity: 1 | USB upstream port type: USB Type-C | Ethernet LAN: Yes | Adjustable height (max): 150 | Cable lock slot: Yes | Cable lock slot type: Kensington | Height adjustment: Yes | LED indicators: Yes | On Screen Display (OSD): Yes | Panel mounting interface: 100 x 100 | Pivot: Yes | Pivot angle: -90 - 90 | Plug and Play: Yes | Swivel angle range: -45 - 45 | Swivelling: Yes | Tilt adjustment: Yes | Tilt angle range: -5 - 21 | VESA mounting: Yes | Wall mountable: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Energy consumption (SDR) per 1000 hours: 17 | Energy efficiency class (HDR): Not available | Energy efficiency class (SDR): E | Energy efficiency scale: A to G | Power consumption (max): 185 | Power consumption (off): 0.3 | Power consumption (standby): 0.3 | Power consumption (typical): 16.5 | Power supply type: Internal | Non-operating altitude: 5000 - 12191 | Operating altitude: 0 - 5000 | Operating relative humidity (H-H): 10 - 80 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -20 - 60 | Depth (with stand): 181.54 | Depth (without stand): 49.74 | Height (with stand): 496.55 | Height (without stand): 315.25 | Weight (with stand): 5250 | Weight (without stand): 3780 | Width (with stand): 538.7 | Width (without stand): 538.7 | Package weight: 7570 | Cables included: AC/DisplayPort/USB Type-A to USB Type-C/USB Type-C to USB Type-C | DisplayPort cable length: 1.8 | Stand included: Yes | Doesn't contain: Arsenic/Mercury/PVC/BFR | Sustainability certificates: ENERGY STAR/TCO | Carbon emissions, end-of-life (kg of CO2e): 5.236 | Carbon emissions, energy usage (kg of CO2e): 80.971 | Carbon emissions,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

logistics (kg of CO2e): 14.212 | Carbon emissions, manufacturing (kg of CO2e): 86.394 | PAIA version: GaBi version 1, 2024 | Total carbon footprint (kg of CO2e): 187 | Compliance certificates: RoHS | RJ-45 ports quantity: 1 | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/2151603/fiches?language=EN> | Energy efficiency class: E | EPREL Registration Number: 2151603 | EPREL Version Number: 1 | Model: P2425DE | Unit Calculated Volume: 0.0402518 | Product Net Weight: 5.61 | Unit Calculated Weight: 6.8

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903