



Ubiquiti UniFi Pro HD 24 PoE Managed L2/L3 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE) 1U Grey

Modelis: USW-Pro-HD-24-PoE

Gamintojas: UBIQUITI

EAN: 810084696606

Prekės kodas: 455365

961.99€

Power over Ethernet (PoE) power per port: 15.4 W | DHCP features: DHCP snooping | Form factor: 1U | Power over Ethernet 4PPoE (PoE++) ports quantity: 24 | Compliance certificates: Industry Canada (IC) | Compliance certificates: Federal Communications Commission (FCC) | Throughput: 115 Gbit/s | Reset button: Yes | Switch layer: L2/L3 | Compliance certificates: CE | Display type: LCM | Switching capacity: 230 Gbit/s | Power connector: AC/DC | Height: 44 mm | DHCP features: DHCP guarding | Networking standards: IEEE 802.1x | Total Power over Ethernet (PoE) budget: 600 W | Cables included: Power | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 22 | AC input frequency: 50/60 Hz | DHCP features: DHCP server | Jumbo frames support: Yes | Power supply

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

included: Yes | Packet buffer memory: 2 MB | Operating temperature (T-T): -5 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Power consumption (max): 60 W | DHCP features: DHCP relay | Forwarding rate: 171 Mpps | Weight: 6.2 kg | Rate limiting: Yes | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | 10G Ethernet (copper) ports quantity: 2 | LED indicators: Speed | Loop protection: Yes | LED indicators: Status | Redundant power supply (RPS) support: Yes | Housing material: SGCC | AC input voltage: 100 - 240 V | LED indicators: Link | Switch type: Managed | SFP+ module slots quantity: 4 | 10G support: Yes | Product colour: Grey | Number of VLANs: 1000 | Rack mount kit: Yes | Quality of Service (QoS) support: Yes | Static route: Yes | Rack mounting: Yes | 2.5G Ethernet (copper) ports quantity: 22 | Port mirroring: Yes | Width: 442.4 mm | IGMP snooping: Yes | Power over Ethernet (PoE): Yes | MAC address table: 32000 entries | Power source: AC/DC/PoE | Flow control support: Yes | Broadcast storm control: Yes | IPv4 routes: 12000 | Stackable: Yes | Virtual LAN features: Voice VLAN | Depth: 400 mm | Multicast support: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903