

iiyama TN6505A-B1AG Signage Display Interactive flat panel 163.8 cm (64.5") 500 cd/m² 4K Ultra HD Black Touchscreen

Gamintojas: IIYAMA CONSIGNMENT · Modelis: TN6505A-B1AG · EAN: 4948570127061 · Prekės kodas: 456279



1 242,90 €

Kaina su PVM

Be PVM: 1 027,19 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Indoor Interactive flat panel Black
- ✓ Ethernet LAN
- ✓ 163.8 cm (64.5") 3840 x 2160 pixels 500 cd/m²
- ✓ Built-in speaker(s)
- ✓ Touchscreen 5 ms



Aprašymas

The ProLite TN6505A-B1AG is a large-format professional touch display, without an operating system, designed for environments where security, reliability and control are non-negotiable. Despite its minimalist structure, the TN6505A is exceptionally easy to use: simply connect your source and it works. The responsive multi-touch panel, 4K UHD resolution and high brightness deliver a precise and professional experience for collaboration, presentations and interactive applications. Built-in annotation allows users to write directly on the screen with a pen, marking up presentations or any on-screen content in real time for clear and effective communication. The TN6505A is the ideal choice for banks, courts, defence organisations, IT departments, universities and other high-security or compliance-driven environments where simplicity, transparency and trust are essential.

Techninė specifikacija

Specifications

Sandėlio grupė	Displays > Lcd Large Format [+85][-122]
Display	
Display diagonal	163.8 cm (64.5")
Display resolution	3840 x 2160 pixels
Display brightness	500 cd/m²
HD type	4K Ultra HD
Touchscreen	Yes
Panel type	IPS
Touchscreen technology	Infrared
Native aspect ratio	16:9
Response time	5 ms
Contrast ratio (typical)	1200:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Active display area (W x H)	1428.5 x 803.5 mm
Display diagonal (metric)	163.9 cm
Horizontal scan range	30 - 135 kHz
Haze rate	25%
Surface hardness	7H
Glass thickness	3.2 mm
Ports & interfaces	
HDMI ports quantity	2
DisplayPorts quantity	1
USB port	Yes
HDMI input ports quantity	2
VGA (D-Sub) input ports	1
USB ports quantity	1
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)
USB connector type	USB Type-C, USB Type-B
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	2
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	65 W
USB Type-C DisplayPort Alternate Mode	Yes
Ethernet LAN (RJ-45) ports	2
PC Audio in	Yes

RS-232C	Yes
Remote (IR) output	1
PC Audio out	Yes
OPS module slot	Yes
Audio Return Channel (ARC)	Yes
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
Design	
Product design	Interactive flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal
Screen shape	Flat
Panel mounting interface	600 x 400 mm
Anti-glare screen	Yes
Positioning accuracy	1 mm
Performance	
Purpose	Education
Picture-in-Picture	Yes
On Screen Display (OSD)	Yes
Number of OSD languages	8
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Japanese, Dutch, Russian
Power	
Power consumption (typical)	146 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	146 kWh
Energy efficiency scale	A to G
Weight & dimensions	
Display width	1489.1 mm

Display depth	118.6 mm
Display height	911.8 mm
Display weight	41.1 kg
Width	1489.1 mm
Depth	118.6 mm
Height	911.8 mm
Weight	41.1 kg

Packaging content

Cables included	AC, HDMI, RS-232
-----------------	------------------

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C

Network

Ethernet LAN	Yes
--------------	-----

Technical details

OPS slot	1
Sustainability certificates	ErP
Compliance certificates	CB, CE, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE
Audio in (mini jack)	Yes
User controls	Color temp., image mode (including eye protection mode), sound mode, no signal standby (Off / 1 min. / 3 min. / 5 min. / 15 min. / 30 min.), meeting mode, time scheduler, key lock, PIP & PBP, brightness / contrast.

Other features

Brightness	450 cd/m ²
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Power supply type	Internal

Matmenys ir svoris

Matmenys (I × P × A)	162,00cm × 102,00cm × 18,00cm
Svoris	50,00kg