



Zyxel XGS2220-54FP Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE)



Modelis: XGS2220-54FP-EU0101F

Gamintojas: ZYXEL

EAN: 4718937625130

Prekės kodas: 457994

1,507.99€

AC input frequency: 50 - 60 Hz | Weight: 5 kg | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | AC input voltage: 100 - 240 V | Warnings: Follow the safety guidelines for electrical current. | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3an | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3bt | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.1ab | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3ae | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.1w |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Storage relative humidity (H-H): 10 - 90% | DHCP features: DHCP relay | Switch layer: L3 | Operating temperature (T-T): -20 - 50 °C | DHCP features: DHCP server | Packet buffer memory: 2 MB | Routing entries: 64 | Installed SFP+ modules quantity: 4 | Flash memory: 64 MB | MAC address table: 32000 entries | Power source: AC | GARP VLAN Registration Protocol (GVRP): Yes | Jumbo frames support: Yes | 10G support: Yes | Total Power over Ethernet (PoE) budget: 960 W | Power over Ethernet (PoE): Yes | Width: 441 mm | Basic switching RJ-45 Ethernet ports quantity: 48 | Depth: 330 mm | Heat dissipation: 195.43 BTU/h | Rack mounting: Yes | Mean time between failures (MTBF): 298.735 h | Internal memory: 1024 MB | Multicast Listener Discovery (MLD) snooping: MLD v1/v2 | Height: 44 mm | Switching capacity: 216 Gbit/s | Switch type: Managed | Forwarding rate: 161 Mpps | 10G Ethernet (copper) ports quantity: 2 | ARP inspection: Yes | IGMP snooping: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | IGMP proxy: Yes | Power consumption (max): 1161.6 W | Authentication type: IEEE 802.1x, RADIUS, TACACS+ | Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Power over Ethernet (PoE) ports quantity: 50