

AG Neovo SC-2203 computer monitor 54.5 cm (21.4") 1920 x 1080 pixels Full HD LCD Black

 Gamintojas: **AG NEOVO TECHNOLOGY** · Modelis: **SC223011E0000** · EAN: **4710739598148** · Prekės kodas: **458489**


220,90 €

Kaina su PVM

 Be PVM: **182,56 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Full HD 1920 x 1080 resolution
- ✓ Anti-Burn-in™ Technology Prevents image ghosting
- ✓ Versatile connectivity: VGA, HDMI, Composite (BNC) inputs
- ✓ Composite (BNC) passive loop-through output port
- ✓ Quick Image settings: CCTV Mode, Gamma Selection, Black-level Adjustment, Contrast Enhancer
- ✓ Designed and developed for continuous 24/7 operation



Aprašymas

22" Full HD LCD Display for Video Surveillance

Essential LCD Display for Video Surveillance

The SC-2203 is a 22-inch surveillance monitor designed for high-demand security environments, supporting continuous 24/7 operation. Equipped with a Full HD VA panel and offering a 178°/178° viewing angle, this monitor delivers consistent color and clarity from any perspective. With a brightness of 280 cd/m² and a dynamic contrast ratio of 20,000,000:1, it provides superior clarity and detail display. The three-sided frameless design not only modernizes setups but also facilitates seamless multi-monitor configurations, making it ideal for comprehensive surveillance systems. This monitor supports a variety of connectivity options, including HDMI, VGA, and BNC, accommodating both modern digital and traditional analog systems.

Higher Cost Performance

Designed with long-hour monitoring in mind, you can expect a reduction in system maintenance efforts and consequentially higher cost performance. The SC-2203 is commercial grade and meant to work 24/7, 365 days a year. Static images that would otherwise cause screen burn-in are gone with AG Neovo's patented Anti-Burn-in technology. Expect prolonged life for LCD screens.

Versatile Connectivity With Bnc And Hdmi Inputs

This 22-inch surveillance monitor with BNC Connector supports both analogue and digital video inputs. Easily connect to various video surveillance equipment with HDMI, VGA and BNC in/out ports. BNC port allows connecting CCTV cameras directly to the monitor. With this bezel less security monitor, there is no need for a DVR/converter to get straight to instant monitoring.

Perfect Match To CCTV Images

There is a special pre-configured CCTV Mode that maximises image clarity in low-light footage. Quickly fine-tune your video footage with adjustments for sharpness, saturation, contrast, brightness, and more. Don't waste time testing and re-adjusting constantly, this product already has it all figured out!

Enhanced Gamma Selection

Offering an enhanced gamma selection makes for amazing visual optimization. Improve the light, shadow, and colour balance quality of your videos with ease.

Missing Details In Dark Scenes Is A Thing Of The Past

More detail from black-level adjustment means improved visibility of dark images.

Multiple Monitor Setups Made Easy

With VESA 100 x 100mm, the SC-2203 is compatible with AG Neovo's mounting portfolio of desk and wall mounts. Whether you're looking for a dual, quad, or more monitor set-up, AG Neovo is a one-stop-shop for creating ergonomic workstations in a control room.

Enhanced Viewing

Broad 178° horizontal and vertical viewing angles maintain superior visibility across multi-monitor setups.

Techninė specifikacija

Specifications	
Sandėlio grupė	Displays > Led Small Format [+95][-216]
Display	
Display diagonal	54.5 cm (21.4")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LCD
Touchscreen	No
HD type	Full HD
Panel type	TN
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	20000000:1

Display number of colours	16.7 million colours
Display brightness (typical)	280 cd/m²
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.248 x 0.248 mm
Digital horizontal frequency	30 - 85 kHz
Digital vertical frequency	48 - 75 Hz
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	4 W
Design	
Market positioning	Business
Product colour	Black
Ports & interfaces	
Built-in USB hub	No
HDMI	Yes
Headphone out	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
HDMI version	1.4
Headphone outputs	1
Headphone connectivity	3.5 mm
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	No
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	-5 - 15°
Power	
Energy efficiency class (SDR)	E

Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	15.6 kWh
Power consumption (typical)	16 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
AC input frequency	50/60 Hz
AC adapter output voltage	100 - 240 V
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 85%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	491.8 mm
Depth (with stand)	167.4 mm
Height (with stand)	373.8 mm
Weight (with stand)	2.6 kg
Width (without stand)	491.8 mm
Depth (without stand)	44.9 mm
Height (without stand)	289.5 mm
Weight (without stand)	2.3 kg
Packaging data	
Package width	555 mm
Package depth	110 mm
Package height	373 mm
Package weight	3.6 kg
Package type	Box
Packaging content	
Cables included	AC, Audio (3.5mm), VGA
Quick start guide	Yes
Other features	
Compliance certificates	CE, EAC, Low Voltage Directive (LVD), REACH, RoHS, UKCA, WEEE

Matmenys ir svoris

Matmenys (I × P × A)	56,00cm × 38,00cm × 11,00cm
----------------------	-----------------------------

Svoris	3,70kg
--------	--------