



Keenetic Challenger SE AX3000 Mesh Wi-Fi 6 Multi- Gigabit Router/Extender with Two 2.5 Gigabit Ethernet Ports

Modelis: KN-3911-01-EU

Gamintojas: KEENETIC

EAN: 4897082922254

Prekės kodas: 461629

123.99€

VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Supported protocols: EoIP, IP-IP, GRE | Antennas quantity: 5 | Processor manufacturer: MediaTek | Schedule access: Yes | Wi-Fi standards: Wi-Fi 6 (802.11ax) | AC input frequency: 50/60 Hz | Antenna design: Internal | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Weight: 385 g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Product colour: White | AC adapter included: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Number of users: 256 user(s) | Parental control: Yes | Cables included: LAN (RJ-45) | Internal memory type: DDR4 | Ethernet LAN data rates: 1000 Mbit/s | WAN connection type: RJ-45, WISP | Quick start guide: Yes | Processor cores: 2 | Processor model: MediaTek MT7981B | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | WLAN data transfer rate (second band): 2402 Mbit/s | Ethernet LAN data rates: 100 | DHCP client: Yes | Number of guest networks (2.4 GHz): 7 | USB port: No | IGMP snooping: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Processor frequency: 1300 MHz | DC-in jack: Yes | Intelligent Mesh technology: Yes | VPN server: OpenVPN | Network address translation (NAT): Yes | Bandwidth control: Yes | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Ethernet LAN: Yes | SIM card slot: No | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 2 | Ethernet LAN data rates: 2500 | Traffic statistics: Yes | Backup function: Yes | Captive portal: Yes | Policy-based routing: Yes | 3G/4G USB modem compatibility: No | AC input voltage: 100 - 240 V | Depth: 170 mm | Output current: 1.5 A | Operating relative humidity (H-H): 20 - 95% | MU-MIMO technology: Yes | IPv4 & IPv6 features: IPv6 Telnet | Number of products included: 1 pc(s) | Web-based setup wizard: Yes | Guest access: Yes | Width: 170 mm | Output voltage: 12 V | DSL WAN: No | IPv4 & IPv6 features: IPv6 SSH | Ethernet LAN interface type: 2.5 Gigabit Ethernet | Quality of Service (QoS) support: Yes | MIMO: Yes | DoS attack prevention: Yes | Number of guest networks (5 GHz): 7 | LED indicators: LAN, Power, WLAN | Firewall: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Power source type: AC | Height: 42 mm | Product type: Tabletop router | Command-line interface (CLI): Yes | Networking standards: IEEE 802.11k | Ethernet WAN: Yes | Built-in processor: Yes | Cabling technology: 10/100/1000/2500Base-T | Internal memory: 512 MB | Wall mountable: Yes | Number of data streams: 3x3 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11ax | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Flash memory: 128 MB | Port forwarding: Yes | Firewall security: SPI | Universal Plug and Play (UPnP): Yes | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | System event log: Yes | WLAN data transfer rate (first band): 300 Mbit/s | Networking standards: IEEE 802.11v | Mobile operating systems supported: iOS | WPS push button: Yes | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Networking standards: IEEE 802.11a | Security algorithms: WPA3-Enterprise | Security algorithms: OWE | Dynamic DNS (DDNS): Yes | Security algorithms: WPA2-Enterprise | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Cloud-managed: Yes | WLAN data transfer rate (max): 3000 Mbit/s | WireGuard: Yes | Security algorithms: WPA-PSK | Networking standards: IEEE 802.11ac | SSID-based VLAN assignment: Yes | Mobile operating systems supported: Android | DHCP server: Yes | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Housing material: Plastic | USSD request support: Yes | PPPoE/PPTP/L2TP pass-through: Yes | IntelliQoS: Yes | Internet connection backup: Yes | WireGuard throughput: 460 Mbit/s | IPoE/PPPoE data rate: 4800

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Mbit/s | Ping check: Yes | UDP-to-HTTP proxy: Yes | AdGuard ad blocker: Yes | Routing table: DHCP |
HTTPS security for access via KeenDNS: Yes | Cloudflare DNS: Yes | Routing table: Manual | Direct or
cloud access via KeenDNS: Yes | L2TP/PPTP data rate: 2400 Mbit/s

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903