



Keenetic Racer AX3000 Mesh Wi-Fi 6 Gigabit Router/Extender with Two Gigabit Ethernet Ports

Modelis: KN-4010-01-EU

Gamintojas: KEENETIC

EAN: 4897082921905

Prekės kodas: 461630

95.99€

VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Supported protocols: EoIP, IP-IP, GRE | Weight: 324 g | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Wi-Fi standards: Wi-Fi 4 (802.11n) | Antennas quantity: 2 | Processor frequency: 1300 MHz | Quick start guide: Yes | Cabling technology: 10/100/1000Base-T(X) | Security algorithms: WPA3-Enterprise | Number of users: 256 user(s) | DSL WAN: No | WLAN data transfer rate (max): 3000 Mbit/s | Processor cores: 2 | Processor model: MediaTek MT7981B | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Security algorithms: WPA3-PSK | IGMP snooping: Yes | Width: 160 mm | Built-in processor: Yes | Universal Plug and Play (UPnP): Yes | Ethernet WAN: Yes | AC adapter included: Yes | Quality of

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Service (QoS) support: Yes | Cables included: LAN (RJ-45) | Height: 45 mm | Product type: Tabletop router | Depth: 118 mm | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Ethernet LAN: Yes | Internal memory: 512 MB | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Operating relative humidity (H-H): 20 - 95% | Backup function: Yes | Ethernet LAN (RJ-45) ports: 2 | Number of products included: 1 pc(s) | Operating temperature (T-T): 0 - 40 °C | Security algorithms: WPA2-Enterprise | Security algorithms: WPA-PSK | Security algorithms: OWE | Internal memory type: DDR4 | Security algorithms: WPA2-PSK | System event log: Yes | Security algorithms: WEP | Output voltage: 12 V | USB port: No | LED indicators: LAN, Power, WLAN | Access Control List (ACL): Yes | Mobile operating systems supported: iOS | Flash memory: 128 MB | Output current: 1 A | Power source type: AC | Firewall security: SPI | Ethernet LAN interface type: Gigabit Ethernet | Mobile operating systems supported: Android | DHCP server: Yes | Processor manufacturer: MediaTek | Wi-Fi Multimedia (WMM)/(WME): Yes | IPv4 & IPv6 features: IPv6 SSH | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Antenna design: External | Schedule access: Yes | Policy-based routing: Yes | IPv4 & IPv6 features: IPv6 Telnet | Bandwidth control: Yes | Number of guest networks (2.4 GHz): 7 | Intelligent Mesh technology: Yes | Number of guest networks (5 GHz): 7 | MU-MIMO technology: Yes | Internet connection backup: Yes | IPoE/PPPoE data rate: 1800 Mbit/s | L2TP/PPTP data rate: 900 Mbit/s | WireGuard throughput: 460 Mbit/s | DDoS protection: Yes | Command-line interface (CLI): Yes | Product colour: White | Networking standards: IEEE 802.11r | Captive portal: Yes | Cloud-managed: Yes | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11a | MIMO: Yes | DHCP client: Yes | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN data rates: 100 | Networking standards: IEEE 802.11k | Networking standards: IEEE 802.11v | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11ax | Network address translation (NAT): Yes | Traffic statistics: Yes | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Web-based management: Yes | MAC address filtering: Yes | AC input frequency: 50/60 Hz | AC input voltage: 100 - 240 V | 3G/4G USB modem compatibility: No | Web-based setup wizard: Yes | WPS push button: Yes | WLAN data transfer rate (second band): 2402 Mbit/s | SSID-based VLAN assignment: Yes | Automatic channel selection: Yes | Parental control: Yes | WLAN data transfer rate (first band): 300 Mbit/s | Firewall: Yes | SIM card slot: No | Cloudflare DNS: Yes | IntelliQoS: Yes | Port forwarding: Yes | DoS attack prevention: Yes | WAN connection type: RJ-45, WISP | USSD request support: Yes | Guest access: Yes | Dynamic DNS (DDNS): Yes | WireGuard: Yes | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | Routing table: DHCP | PPPoE/PPTP/L2TP pass-through: Yes | HTTPS security for access via KeenDNS: Yes | AdGuard ad blocker: Yes | UDP-to-HTTP proxy: Yes | Ping check: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903