

Allied Telesis AT-x230-28GP-50 Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey

Gamintojas: **ALLIED TELESIS** · Modelis: **AT-X230-28GP-50** · EAN: **767035204093** · Prekės kodas: **465418**



1 126,90 €

Kaina su PVM

Be PVM: **931,32 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L3 Web-based management
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 24
- ✓ 10G support
- ✓ MAC address table: 16000 entries Switching capacity: 56 Gbit/s
- ✓ Access Control List (ACL)
- ✓ Rack mounting Stackable
- ✓ Power over Ethernet (PoE)

Aprašymas

The Allied Telesis x230-28GP features 24 10/100/1000T PoE+ ports with 4 SFP Gigabit uplink ports. Its full feature-set and Power over Ethernet Plus (PoE+) are ideal for applications at the network edge. The AT-x230-28GP supports today's converged networks with Gigabit Ethernet to the desktop, while powering VoIP phones, wireless access points, and IP security cameras.

Techninė specifikacija

Management features

Switch type	Managed
Switch layer	L3
Quality of Service (QoS) support	Yes
Web-based management	Yes
ARP inspection	Yes
System event log	Yes

MIB support	Y
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP module slots quantity	4
Network	
Networking standards	IEEE 802.11ad, IEEE 802.1AX, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	Yes
Port mirroring	Yes
Full duplex	Yes
Policy-based routing	Yes
Flow control support	Yes
Link aggregation	Yes
Spanning tree protocol	Yes
VLAN support	Yes
Data transmission	
MAC address table	16000 entries
Switching capacity	56 Gbit/s
Throughput	41.7 Mpps
Packet buffer memory	1.5 MB
Security	
DHCP features	DHCP server, DHCPv6 relay, DHCPv6 server, DHCP client
Access Control List (ACL)	Yes
IGMP snooping	Yes
Security algorithms	802.1x RADIUS
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Stackable	Yes

Product colour	Grey
LED indicators	Yes
Performance	
Memory type	DDR-SDRAM
Internal memory	256 MB
Flash memory	64 MB
Noise level	42 dB
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	520 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	24
Total Power over Ethernet (PoE) budget	370 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-25 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3048 m
Heat dissipation	303 BTU/h
Weight & dimensions	
Width	440 mm
Depth	290 mm
Height	44 mm
Weight	4.7 kg
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Matmenys (I × P × A)	53,00cm × 43,00cm × 15,00cm
Svoris	6,52kg