



TP-Link Omada 52-Port Gigabit L2+ Managed Switch with 48- Port PoE+

Modelis: TL-SG3452P

Gamintojas: TP-LINK

EAN: 6935364006273

Prekės kodas: 466586

638.99€

Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Do not open the case or try to repair it yourself. | Warnings: Ensure the unit is adequately ventilated during operation. | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Console port: RJ-45/Micro-USB | Cloud-managed: Yes | Forwarding rate: 77.38 Mpps | Link aggregation: Yes | Loop protection: Yes | Access Control List (ACL): Yes | Switch type: Managed | Active link detection: Yes | Rate limiting: Yes | Store-and-forward: Yes | IP routing: Yes | Virtual LAN features: Protocol-based VLAN | Virtual LAN features: MAC address-based VLAN | Virtual LAN features: Tagged VLAN | MIB support: Yes | Management protocols: SNMPv1/v2c/v3, SNTp | Spanning tree protocol: Yes | Jumbo frames: 9000 | Switch layer: L2/L3 | Virtual LAN features: Private VLAN | BPDU filtering/protection: Yes | Head-of-line (HOL) blocking: Yes | Power over Ethernet plus (PoE+) ports quantity: 48 | System event log: Yes | Static route: Yes | Virtual LAN features: Voice VLAN | GARP VLAN Registration

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Protocol (GVRP): Yes | Quick start guide: Yes | ARP inspection: Yes | Networking standards: IEEE 802.1p | Number of static routes: 48 | Web-based management: Yes | Networking standards: IEEE 802.1D | Reset button: Yes | Broadcast storm control: Yes | Networking standards: IEEE 802.3x | Policy-based routing: Yes | AC input frequency: 50/60 Hz | Authentication: MAC-based authentication, Port-based authentication | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | SSH/SSL support: Yes | Flow control support: Yes | Product colour: Black | Ethernet LAN data rates: 10,100,1000 Mbit/s | Storage relative humidity (H-H): 5 - 90% | AC input voltage: 100 - 240 V | LED indicators: Yes | Power supply included: Yes | Cables included: AC | Height: 44 mm | Power consumption (max): 464.2 W | Operating relative humidity (H-H): 10 - 90% | Power connector: AC-in jack | Total Power over Ethernet (PoE) budget: 384 W | Operating temperature (T-T): 0 - 40 °C | Package type: Box | Manual: Yes | Power over Ethernet (PoE) power per port: 30 W | Width: 440 mm | DHCP features: DHCPv6 client | DHCP features: DHCP server | Packet buffer memory: 12 MB | Multicast support: Yes | Port mirroring: Yes | Power source: AC | DHCP features: DHCP snooping | Rack mounting: Yes | VLAN support: Yes | Heat dissipation: 1584.08 BTU/h | Power over Ethernet (PoE): Yes | IGMP snooping: Yes | Form factor: 1U | DHCP features: DHCPv6 snooping | MAC address table: 16000 entries | Switching capacity: 104 Gbit/s | Password protection: Yes | Depth: 330 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | DHCP features: DHCP client | DHCP features: DHCP relay | Number of VLANs: 4000 | 10G support: No | Number of fans: 3 fan(s) | Jumbo frames support: Yes | Basic switching RJ-45 Ethernet ports quantity: 48 | SFP module slots quantity: 4

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903