



TP-Link Omada ES208GP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) DIN rail Black



Modelis: ES208GP

Gamintojas: TP-LINK

EAN: 1210002609708

Prekės kodas: 466653

72.00€

Networking standards: IEEE 802.3bt | Networking standards: IEEE 802.3at | Web-based management: Yes | Product colour: Black | LED indicators: Yes | Input current: 1.31 A | Ethernet LAN data rates: 10,100,1000 Mbit/s | Compliance certificates: RoHS | Compliance certificates: CE | Operating temperature (T-T): 0 - 40 °C | Quick start guide: Yes | Compliance certificates: Federal Communications Commission (FCC) | Networking standards: IEEE 802.3af | Power over Ethernet (PoE) type supported: PoE+ | Switch layer: L2 | DC input voltage: 53 V | Link aggregation: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Jumbo frames: 15000 | Cloud-managed: Yes | Forwarding rate: 11.904 Mpps | Power over Ethernet plus (PoE+) ports quantity: 8 | Loop protection: Yes | Transmission distance (max): 0.25 km | Switch type: Managed | Auto-negotiation: Yes | Virtual LAN features: Tagged VLAN | Virtual LAN features: Port-based VLAN | Virtual LAN features: MTU VLAN | Store-and-forward: Yes | Broadcast storm control: Yes | Flow control support: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Form factor: DIN rail | Jumbo frames support: Yes | Storage temperature (T-T): -40 - 70 °C | Number of VLANs: 4000 | Power source: DC | Port mirroring: Yes | Switching capacity: 16 Gbit/s | Cables included: Power | Packet buffer memory: 0.5 MB | Auto MDI/MDI-X: Yes | IGMP snooping: Yes | Width: 158 mm | Power over Ethernet (PoE): Yes | Height: 25.4 mm | Storage relative humidity (H-H): 5 - 90% | Total Power over Ethernet (PoE) budget: 64 W | 10G support: No | Rack mounting: Yes | DHCP features: DHCP client | MAC address table: 8000 entries | Multicast support: Yes | Depth: 100.7 mm | Quality of Service (QoS) support: Yes | Operating relative humidity (H-H): 10 - 90% | Basic switching RJ-45 Ethernet ports quantity: 8 | VLAN support: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903