

Zyxel GS-1900-24 v2 Managed L2 Gigabit Ethernet (10/100/1000) 1U Black

Gamintojas: ZYXEL · Modelis: GS1900-24-EU0102F · EAN: 4718937621231 · Prekės kodas: 476414



152,90 €

Kaina su PVM

Be PVM: 126,36 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Start up button
- ✓ VLAN
- ✓ QoS
- ✓ Link aggregation



Aprašymas

Near silent operation

The GS1900 Series includes both fan-less and built-in smart fan models. The smart fan is designed to automatically adjust speed based on device temperature. You can barely hear the sound while the switch is operating. It is ideal for your office environment.

Intelligent PoE+ powers more devices

PoE models (8HP/10HP/24EP/24HPv2/48HPv2) come with default PoE consumption mode which delivers only the actual power required by your networked devices, reserves the rest and optimizes its power budget. That means a single switch can power more APs, IP cameras and VoIP phones, ensuring a better ROI for your business. All of them support the IEEE 802.3at providing a maximum of 30W per port.

Speedy Gigabit performance—built for SMBs

The GS1900 is a series of switches with full non-blocking bandwidth of up to 1 Gbps per port. An ideal upgrade from an unmanaged switch, it's a great choice for SMBs that want to enjoy high-speed business network applications at full wired non-blocking speed.

Easy and intuitive management

The Smart Managed GS1900 Series switch feature with web-based interface to manage advanced functions such as VLAN, QoS, IGMP Snooping, Link Aggregation (LAG), IPv6 and DoS prevention easily. Also, the user-friendly wizard helps to walk through setup, configuration and even advanced settings quickly.

Techninė specifikacija

Specifications	
Sandėlio grupė	[NES] NETWORK SWITCHES [+71][-364]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
System event log	Yes
MIB support	RFC 1213 MIB II, RFC 2819 RMON (group 1, 2, 3, 9), RFC 1215, RFC 1493
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP module slots quantity	2
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support	No
Port mirroring	Yes
Full duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Spanning tree protocol	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
MAC address auto-learning supported	Yes
VLAN support	Yes
Virtual LAN features	Tagged VLAN, VLAN Identifier (VLAN ID), Voice VLAN
Data transmission	

MAC address table	8000 entries
Switching capacity	52 Gbit/s
Forwarding rate	39 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	0.525 MB

Security

DHCP features	DHCP client
IGMP snooping	Yes
Security algorithms	802.1x RADIUS
MAC address filtering	Yes
Static port security	Yes
SSH/SSL support	Yes
Password protection	Yes
Authentication type	RADIUS, TACACS+

Design

Rack mounting	Yes
Stackable	Yes
Form factor	1U
Product colour	Black
Reset button	Yes
LED indicators	Yes

Performance

Mean time between failures (MTBF)	432.673 h
-----------------------------------	-----------

Power

Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	16 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 95%
Storage relative humidity (H-H)	10 - 95%
Heat dissipation	55 BTU/h
Weight & dimensions	
Width	440 mm
Depth	131 mm
Height	44 mm
Weight	2.09 kg
Packaging content	
Cables included	AC
Rack mount kit	Yes
Packaging data	
Package type	Box
Package width	561 mm
Package depth	217 mm
Package height	82 mm
Package weight	2.85 kg
Certificates	
Certification	EMC ■ CE, FCC, C-Tick, Class A (GS1900-24/24EP/24HPv2/48/ 48HPv2) ■ CE, FCC, C-Tick, Class B (GS1900-8/8HP/10HP/16/24E) ■ BSMI CNS13438 • Safety ■ LVD EN60950-1 ■ BSMI CNS14336-1 ■ CB IEC60950-1 (GS1900-8HP/10HP/16/24E/24) • RoHS compliant
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Matmenys (I × P × A)	9,00cm × 22,00cm × 56,00cm
Svoris	2,67kg