



**Monitorius DELL
UltraSharp
U2424HE 23.8"
FHD IPS 120Hz
su USB-C
jungčių centru
(90W PD),
Ergonomiškas**

Modelis: DELL-U2424HE

Gamintojas: DELL TECHNOLOGIES

EAN: 5397184821428

Prekės kodas: 476897

362.00€

DELL UltraSharp U2424HE 23.8" IPS Monitorius Produktyvumui

DELL UltraSharp U2424HE monitorius yra sukurtas maksimaliam profesionaliam produktyvumui ir vizualiam komfortui užtikrinti. Turėdamas pažangią IPS matricą, Full HD (1920x1080) raišką ir

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

sklandų 120 Hz atnaujinimo dažnį, šis ekranas pateikia aiškius, skystus vaizdus, idealiai tinkančius intensyviai kasdieniam darbui. Monitorius turi TÜV Rheinland 4 žvaigždučių akių komforto sertifikatą ir naudoja mažos mėlynos šviesos („Low Blue Light“) bei mirgėjimą šalinančias („Flicker-Free“) technologijas, užtikrindamas minimalų akių nuovargį dirbant ilgas valandas.

Sklandi Jungtis ir Galios Tiekimas (Hub)

Šis monitorius veikia kaip galingas produktyvumo centras, supaprastinantis jūsų darbo vietos valdymą. Integruotas USB 3.2 Gen 2 šakotuvas (hub) užtikrina didelės spartos duomenų perdavimą, o USB Type-C jungtis tiekia net iki 90 W galios. Tai leidžia vienu kabeliu įkrauti suderinamą nešiojamąjį kompiuterį ir perduoti vaizdo/duomenų signalus, žymiai sumažinant netvarką ant stalo. Be to, įmontuota Gigabit Ethernet (RJ-45) jungtis garantuoja stabilų ir patikimą tinklo ryšį.

Pagrindinės Savybės ir Specifikacijos:

- **Vaizdo Kokybė:** 23.8 colio IPS matrica su Full HD (1920 x 1080) raiška, 16:9 kraštinių santykiu ir 178° plačiais matymo kampais.
- **Padidintas Sklandumas:** 120 Hz maksimalus atnaujinimo dažnis užtikrina sklandesnį slinkimą ir didesnę judesio aiškumą nei standartiniai 60 Hz ekranai.
- **Aukščiausias Komfortas:** TÜV 4 žvaigždučių sertifikuotos akių komforto funkcijos, įskaitant nuolat įjungtą mažo mėlynos šviesos lygio technologiją ir mirgėjimo nebuvimą.
- **Maitinimo Centras:** USB Type-C jungtis su 90W galios tiekimu (PD) ir DisplayPort Alt Mode.
- **Gausios Jungtys:** Apima HDMI 1.4, DisplayPort 1.4 (įv./išv.), 4x USB Type-A, 1x USB Type-C prievadą ir Gigabit Ethernet (RJ-45).
- **Pilna Ergonomika:** Sukurtas optimaliam pozicionavimui su pasukimo (Swivel), sukiojimo (Pivot 90° portretiniam režimui), aukščio reguliavimo (150 mm) ir pakreipimo funkcijomis.
- **Spalvų Tikslumas:** 100% sRGB ir 85% DCI-P3 aprėptis užtikrina ryškių ir tikslų spalvų atkūrimą profesionalioms užduotims.

DELL yra visame pasaulyje pripažintas technologijų lyderis, siūlantis inovatyvius ir patikimus kompiuterinius sprendimus. Jie ypač žinomi dėl aukštos kokybės UltraSharp serijos monitorių, skirtų verslo ir profesionaliems naudotojams, kuriems reikalingas tikslumas ir komfortas.

Užsisakykite šiandien iš ++SHOP++, nes siūlome geriausias kainas ir greitą visų DELL UltraSharp monitorių pristatymą.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

Experience improved visual comfort, peak productivity and extensive connectivity with this hub monitor certified by TÜV for 4-star eye comfort.

Experience improved visual comfort, peak productivity and extensive connectivity with this hub monitor certified by TÜV for 4-star eye comfort.

- 60.5cm (23.8") Full HD 1920 x 1080 Edge LED IPS
- 8ms, 16:9, 250cd/m², 1000:1
- USB, HDMI, DisplayPort

Actual configuration might differ from illustration

Product Carbon Footprint (PCF):

1. Dell generally uses the PAIA (Product Attribute to Impact Algorithm)(<http://msl.mit.edu/projects/paia/main.html>) tool for product carbon footprint calculations.
2. Docking station related PCFs are extracted from corresponding LCAs and as such do not follow the PAIA methodology used for calculating other PCFs in this report.
3. PAIA method is developed by the Massachusetts Institute of Technology's Materials Systems Laboratory and partners.
4. All estimates of carbon footprint are uncertain. Dell Technologies reports the 5th and 95th percentile of the carbon footprint estimate to reflect this uncertainty wherever possible. (<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>)
5. Please note the emission estimate in this report is calculated using the mean value along with the standard deviation for that product model.
6. Use of default inputs (i.e. not primary data) and assumptions on location of use and other fields can introduce a standard deviation which must be taken into account while completing the calculations.
7. Please note, PAIA uses the ecoinvent Database (<https://ecoinvent.org/the-ecoinvent-database/>) whenever primary data is not made available for calculations.
8. For client and commercial end user computing products, minimum configurations were assumed for calculations. For Server and Storage products, typical configurations or ENERGY STAR (<https://www.energystar.gov/products>) configurations were used for calculations.
9. Use Phase emissions were calculated based on the location of use as "Europe" i.e. the Use Phase

emissions are not specific to a single country / location.

10. The report does provide an option for a total emissions number for manufacturing, transport and end of life while leaving the use phase emissions out, in case the customer uses their own calculation methodology for use phase emissions.

11. The lifetime usage assumption at the product family level is as follows: Desktop, Notebook - 4 years, Display - 5 years and Servers - 4 years.

12. For detailed assumptions please refer to the product datasheets in the Dell Technologies reports (<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>).

13. The results from the PAIA tool are liable to change over time as the methodology is improved and datasets are updated. The PAIA version used to calculate emissions has been indicated with each record in the report.

14. Metrics used: The units for global warming potential are in kgCO₂-equivalent or MT (metric ton) CO₂-equivalent (CO₂e).

15. Beginning in June 2024, the data dashboard now incorporates PCF values computed using the Dell PCF calculator. It's important to note that the default location utilized for these calculations shown on the data dashboard is Europe. To access PCF values calculated for the USA and China locales, please refer to the Product PCF PDF document on Dell.com.

Summary: DELL UltraSharp U2424HE. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Black, Silver | Vendor Homepage: <https://www.dell.com/en-uk/shop/> | Anti-glare screen: Yes | Backlight type: Edge LED | Colour gamut: 85 | Colour gamut standard: DCI-P3 | Contrast ratio (typical): 1000:1 | Display brightness (typical): 250 | Display diagonal: 23.8 | Display diagonal (metric): 60.47 | Display number of colours: 16.7 million colours | Display resolution: 1920 x 1080 | Display technology: LCD | HD type: Full HD | High Dynamic Range (HDR) supported: No | Horizontal scan range: 31 - 135 | Maximum refresh rate: 120 | Native aspect ratio: 16:9 | Panel type: IPS | Pixel density: 92.53 | Pixel pitch: 0.2745 x 0.2745 | Response time: 8 | Response time (fast): 5 | Screen shape: Flat | sRGB coverage (typical): 100 | Supported graphics resolutions: 1024 x 768 (XGA)/1152 x 864 (XGA+)/1280 x 1024 (SXGA)/1280 x 720 (HD 720)/1600 x 900/1920 x 1080 (HD 1080)/640 x 480 (VGA)/720 x 400/720 x 480/800 x 600 (SVGA) | Supported video modes: 1080i/1080p/480p/576p/720p | Surface hardness: 3H | Touchscreen: No | Vertical scan range: 48 - 120 | Viewable size diagonal: 604.7 | Viewable size,

horizontal: 527.04 | Viewable size, vertical: 296.46 | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | AMD FreeSync: No | Flicker-free technology: Yes | Low Blue Light technology: Yes | NVIDIA G-SYNC: No | Built-in camera: No | Built-in speaker(s): No | Feet colour: Silver | Front bezel colour: Black | Market positioning: Business | Product colour: Black,Silver | AC (power) in: Yes | Built-in USB hub: Yes | DisplayPort version: 1.4 | DisplayPorts quantity: 2 | HDCP: Yes | HDCP version: 1.4 | HDMI: Yes | HDMI ports quantity: 1 | HDMI version: 1.4 | Headphone out: Yes | Microphone in: No | Number of USB Type-C upstream ports quantity: 2 | PC Audio in: No | USB hub version: 3.2 Gen 2 (3.1 Gen 2) | USB Power Delivery (USB PD): Yes | USB Power Delivery up to: 90 | USB Type-A downstream ports quantity: 4 | USB Type-C DisplayPort Alternate Mode: Yes | USB Type-C downstream ports quantity: 1 | USB upstream port type: USB Type-C | Wi-Fi: No | Adjustable height (max): 150 | Cable lock slot: Yes | Cable lock slot type: Kensington | Height adjustment: Yes | On Screen Display (OSD): Yes | Panel mounting interface: 100 x 100 | Pivot: Yes | Pivot angle: -90 - 90 | Swivel angle range: -45 - 45 | Swivelling: Yes | Tilt adjustment: Yes | Tilt angle range: -5 - 21 | VESA mounting: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Energy consumption (SDR) per 1000 hours: 15 | Energy efficiency class (HDR): Not available | Energy efficiency class (SDR): D | Energy efficiency scale: A to G | European Product Registry for Energy Labelling (EPREL) code: 1585563 | Input current: 2.2 | Power consumption (max): 210 | Power consumption (off): 0.3 | Power consumption (standby): 0.5 | Power consumption (typical): 14.5 | Power supply type: Internal | Non-operating altitude: 5000 - 12192 | Operating altitude: 0 - 5000 | Operating relative humidity (H-H): 10 - 80 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -20 - 60 | Bezel width (bottom): 8.95 | Bezel width (side): 5.8 | Bezel width (top): 5.8 | Depth (with stand): 181.75 | Depth (without stand): 49.1 | Height (with stand): 496.53 | Height (without stand): 311.21 | Weight (with stand): 5550 | Weight (without stand): 3980 | Width (with stand): 538.64 | Width (without stand): 538.64 | Package weight: 8450 | Cables included: AC/DisplayPort/USB Type-A to USB Type-C | DisplayPort cable length: 1.8 | Power adapter included: Yes | Quick start guide: Yes | Remote control included: No | Stand included: Yes | Stylus included: No | Doesn't contain: PVC/BFR | Sustainability certificates: ENERGY STAR/TCO | Sustainability compliance: Yes | Carbon emissions, end-of-life (kg of CO2e): 6.99 | Carbon emissions, energy usage (kg of CO2e): 108.8 | Carbon emissions, logistics (kg of CO2e): 40.69 | Carbon emissions, manufacturing (kg of CO2e): 381.12 | PAIA version: 1.3.2, 2022 | Total carbon emissions, standard deviation (kg of CO2e): 122 | Total carbon emissions, w/o use phase (kg of CO2e): 426.2 | Total carbon footprint (kg of CO2e): 535 | Compliance certificates: RoHS | Ethernet LAN (RJ-45) ports: 1 | Heavy metals free: Hg (mercury) | Data Sheet (Link):

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

<https://eprel.ec.europa.eu/api/product/1585563/fiches?language=EN> | Energy efficiency class: D | EPREL Registration Number: 1585563 | EPREL Version Number: 2 | Model: U2424HE | Included Accessories: tand Riser, Stand Base, Quick setup guide Safety, Environmental and Regulatory Information, Factory calibration report; 1 x Power cable 1 x DisplayPort 1.4 cable - 1.8 m 1 x USB Type-C to USB Type-C Gen 2 cable - 1 m 1 x USB Type-A to USB Type-C Gen 2 cable - 1 m | Unit Calculated Volume: 0.04334 | Product Net Weight: 5.91 | Unit Calculated Weight: 8.5