

DELL UltraSharp U2725QE computer monitor 68.6 cm (27") 3840 x 2160 pixels 4K Ultra HD LCD Black, Silver

Gamintojas: **DELL TECHNOLOGIES** · Modelis: **DELL-U2725QE** · EAN: **5397184923405** · Prekės kodas: **476899**



672,91 €

Kaina su PVM

Be PVM: **556,12 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 68.6cm (27") 4K Ultra HD 3840 x 2160 Edge LED IPS
- ✓ 8ms, 16:9, 450cd/m², 3000:1
- ✓ USB, HDMI, DisplayPort



Aprašymas

A 27" monitor featuring the world's first enhanced IPS Black with 3000:1 contrast ratio with enhanced eye comfort from improved ComfortView Plus, an ambient light sensor and 120Hz refresh rate.

Techninė specifikacija

Specifications

Sandėlio grupė

[TFT] FLAT PANEL DISPLAYS [+108][-363]

Display

Display diagonal

68.6 cm (27")

Display resolution	3840 x 2160 pixels
Native aspect ratio	16:9
Display technology	LCD
Touchscreen	No
HD type	4K Ultra HD
Panel type	IPS
Response time	8 ms
Screen shape	Flat
Contrast ratio (typical)	3000:1
Maximum refresh rate	120 Hz
Display number of colours	1.07 billion colours
LED backlight	Yes
Backlight type	Edge LED
Display brightness (peak)	600 cd/m²
Display brightness (typical)	450 cd/m²
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800 (WXGA), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1440, 3840 x 2160
Supported video modes	480p, 576p, 720p, 1080p, 2160p
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Response time (fast)	5 ms
Pixel pitch	0.1554 x 0.1554 mm
Pixel density	163 ppi
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Viewable size diagonal	68.5 cm
Digital horizontal frequency	30 - 275 kHz
Digital vertical frequency	48 - 120 Hz
Display diagonal (metric)	68.47 cm
High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	DisplayHDR 600
Surface hardness	3H
sRGB coverage (typical)	100%

DCI-P3 coverage	99%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	No
Built-in camera	No
Design	
Market positioning	Office
Product colour	Black, Silver
Front bezel colour	Black
Detachable stand	Yes
Feet colour	Silver
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 2 (3.1 Gen 2)
USB upstream port type	USB Type-C
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	5
USB Type-C downstream ports quantity	2
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	120 W
HDMI ports quantity	1
DisplayPorts quantity	1
DisplayPort out quantity	1
DisplayPort out version	1.4
DisplayPort version	1.4
Thunderbolt 4 ports quantity	2
Headphone connectivity	3.5 mm

HDCP	Yes
HDCP version	2.2
Network	
Ethernet LAN	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Cable management	Yes
Cable lock slot type	Kensington
Adjustable height (max)	15 cm
Pivot	Yes
Pivot angle	-90 - 90°
Swivelling	Yes
Swivel angle range	-45 - 45°
Tilt adjustment	Yes
Tilt angle range	-5 - 21°
On Screen Display (OSD)	Yes
Power	
Energy efficiency class (SDR)	F
Energy efficiency class (HDR)	G
Energy consumption (SDR) per 1000 hours	25 kWh
Energy consumption (HDR) per 1000 hours	44 kWh
Power consumption (typical)	25.4 W
Power consumption (standby)	0.5 W
Power consumption (max)	325 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	4 A
Energy efficiency scale	A to G
Operational conditions	

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m
Non-operating altitude	5000 - 12192 m
Weight & dimensions	
Width (with stand)	612.4 mm
Depth (with stand)	189 mm
Height (with stand)	535.7 mm
Weight (with stand)	6.74 kg
Width (without stand)	612.4 mm
Depth (without stand)	55.6 mm
Height (without stand)	353.5 mm
Weight (without stand)	5.22 kg
Bezel width (side)	7.85 mm
Bezel width (top)	7.85 mm
Bezel width (bottom)	1 cm
Packaging data	
Package width	819.9 mm
Package depth	154.9 mm
Package height	454.9 mm
Package weight	9.73 kg
Packaging content	
Stand included	Yes
Cables included	AC, DisplayPort, Thunderbolt, USB Type-A to USB Type-C
DisplayPort cable length	1.8 m
Sustainability	
Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	Arsenic, Mercury, PVC/BFR
Carbon footprint	
Total carbon footprint (kg of CO2e)	289
Carbon emissions, manufacturing (kg of CO2e)	138.72
Carbon emissions, logistics (kg of CO2e)	18.21

Carbon emissions, energy usage (kg of CO2e)	124.85
Carbon emissions, end-of-life (kg of CO2e)	7.23
PAIA version	GaBi version 1, 2024
Other features	
RJ-45 ports quantity	1
Compliance certificates	RoHS
Matmenys ir svoris	
Matmenys (l × p × A)	82,00cm × 15,00cm × 45,00cm
Svoris	10,20kg