

Zyxel USG-LITE 60AX wired router 2.5 Gigabit Ethernet White

Gamintojas: ZYXEL · Modelis: USGLITE60AX-EU0101F · EAN: 4718937637706 · Prekės kodas: 479161



197,90 €

Kaina su PVM

Be PVM: 163,55 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Get the Highlights
- ✓ USG LITE 60AX
- ✓ Security
- ✓ Subscription-free ransomware protection
- ✓ 2.5 GbE
- ✓ Dual 2.5 GbE mGig connectivity
- ✓ Nebula
- ✓ Intelligent cloud management
- ✓ WiFi 6
- ✓ Blazingly Fast WiFi 6



Aprašymas

Speed. Safety. Simplicity.
Built-in WiFi 6 & Ransomware Protection

Techninė specifikacija

Specifications

Sandėlio grupė

[ROU] ROUTERS [+33][-87]

WAN connection

Ethernet WAN	Yes
DSL WAN	No
SIM card slot	No
3G/4G USB modem compatibility	No
SFP WAN	No
Network	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Ethernet interface type	2.5 Gigabit Ethernet
Cabling technology	10/100/1000Base-T(X)
Ethernet LAN data rates	10,100,1000,2500 Mbit/s
Forwarding rate	2000 Mpps
Switching capacity	2 Gbit/s
Throughput	2 Gbit/s
VLAN support	Yes
Port forwarding	Yes
Auto MDI/MDI-X	Yes
Policy-based routing	Yes
Concurrent connections	20000
Number of users	10 user(s)
Management features	
Web-based management	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	5
Protocols	
DHCP client	Yes
DHCP server	Yes
Security	
Security algorithms	WPA2
Firewall	Yes
Guest access	Yes
VPN tunnels quantity	5
Technical details	
Introduction month	June
Introduction year	2024

Warranty period	2 year(s)
Packaging content	
AC adapter included	Yes
Cables included	LAN (RJ-45)
Manual	Yes
Quick start guide	Yes
Quick installation guide	Yes
User Guide on CD-ROM	No
Bundled software	License free Ransomware & Cybersecurity
Features	
Built-in processor	Yes
Processor manufacturer	Qualcomm
Processor frequency	2000 MHz
Storage media	Flash
Flash memory	512 MB
Internal memory	1000 MB
Design	
Product colour	White
Housing material	Polycarbonate (PC)
Rack mounting	No
Wall mountable	No
LED indicators	Power
On/off switch	Yes
Built-in display	No
Touchscreen	No
Country of origin	Taiwan
Power	
Power consumption (max)	31 W
Power source type	DC
Redundant power supply (RPS) support	No
AC input voltage	110 - 240 V
Output voltage	12 V
Output current	3 A
Power over Ethernet (PoE)	No

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-30 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	161.7 mm
Depth	65 mm
Height	229 mm
Weight	707 g

Packaging data

Package width	259 mm
Package depth	266 mm
Package height	73 mm
Package tare weight	1.17 kg
Package weight	1.48 kg
Package type	Box

Logistics data

Shipping (inner) case height	7.3 cm
Shipping (inner) case net weight	1.48 kg
Products per shipping (inner) case	1 pc(s)
Master (outer) cases per pallet (air)	24 pc(s)
Products per pallet (air)	240 pc(s)
Pallet gross length	120 cm
Pallet gross width	80 cm
Pallet height (air)	2.2 m
Master (outer) cases per pallet (sea)	24 pc(s)
Products per pallet (sea)	240 pc(s)
Pallet height (sea)	2.2 m

Matmenys ir svoris

Matmenys (l × P × A)	27,00cm × 26,00cm × 7,00cm
Svoris	1,14kg