

Philips 55BDL4511D/00 Signage Display Digital A-board 139.7 cm (55") 500 cd/m² 4K Ultra HD Black 24/7

Gamintojas: **PHILIPS** · Modelis: **55BDL4511D/00** · EAN: **8712581778668** · Prekės kodas: **479172**



968,90 €

Kaina su PVM

Be PVM: **800,74 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Indoor Digital A-board Black
- ✓ Ethernet LAN
- ✓ 139.7 cm (55") 3840 x 2160 pixels 500 cd/m²
- ✓ Built-in speaker(s) 20 W
- ✓ 8 ms



Aprašymas

Operate, monitor and maintain with CMND & Control

Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

FailOver ensures content is always playing

From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs ensuring content keeps playing even if the primary source goes down. Simply set a list of alternate inputs to be sure

your business is always on.

SmartPower for energy saving

The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

Schedule what you want, when you want with SmartPlayer

Turn your USB into a true cost effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display. Create your playlist and schedule your content via the on screen menu, and enjoy your own created playlists anytime, anywhere.

ADS wide-view panel display

Be seen from any angle with ADS wide-view technology. Advanced Super Dimension Switch delivers faster on-display picture processing for smoother content transitions, remarkable image accuracy, and superior colour reproduction with 180 degree viewing.

Optional OPS Slot

Open Pluggable Specification is an industry standard slot in to which you can add an OPS-compatible media player. This gives you the ability to upgrade or change your hardware whenever you need. Turning your display in to an all-in-one digital signage solution has become simplicity personified.

Techninė specifikacija

Display	
Display diagonal	139.7 cm (55")
Display resolution	3840 x 2160 pixels
Display brightness	500 cd/m ²
HD type	4K Ultra HD
Touchscreen	No
Panel type	VA
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	5000:1
Contrast ratio (dynamic)	500000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Pixel pitch	0.315 x 0.315 mm
Display diagonal (metric)	138.7 cm
Panel life	50000 h
Haze rate	25%

Ports & interfaces

HDMI ports quantity	3
DVI port	Yes
DisplayPorts quantity	2
USB port	Yes
HDMI version	2
HDMI input ports quantity	2
HDMI output ports quantity	1
DVI-I ports quantity	1
DisplayPorts in	1
DisplayPorts out	1
USB ports quantity	2
USB version	2
Ethernet LAN (RJ-45) ports	1
Audio (L/R) in	1
Audio (L/R) out	1
RS-232C	Yes
Remote (IR) input	1
Remote (IR) output	1
OPS module slot	Yes

Audio

Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W

Design

Product design	Digital A-board
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal/Vertical
Panel mounting interface	400 x 400 mm
Bezel width (bottom)	1.39 cm
Bezel width (side)	1.39 cm
Bezel width (top)	1.39 cm

Performance

Purpose	Commercial
Operating hours (hours/days)	24/7

Power

Power consumption (typical)	135 W
Power consumption (standby)	0.5 W
Power consumption (sleep)	0.5 W
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	136 kWh
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G

Computer system

Video formats supported	H.263, H.264, H.265, MPEG
Audio formats supported	AAC, HE-AAC
Image formats supported	BMP, JPG, PNG

Weight & dimensions

Display width	1241.8 mm
Display depth	63.6 mm
Display height	712.6 mm
Display weight	16.6 kg

Packaging content

Remote control included	Yes
Batteries included	Yes
Cables included	AC, DisplayPort, IR sensor, RS-232

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	0 - 60 °C
Storage relative humidity (H-H)	5 - 95%

Logistics data

Harmonized System (HS) code	85285210
-----------------------------	----------

Network

Ethernet LAN	Yes
--------------	-----

Matmenys ir svoris	
Matmenys (l × p × A)	10,00cm × 10,00cm × 10,00cm
Svoris	1,00kg