



**Monitorius DELL
P2725D 27 colių
QHD
(2560x1440)
Verslo klasės
100Hz IPS
Matinis, su USB
šakotuvu,
Ergonominis
Stovas
Juodas/Sidabrinis**

Modelis: DELL-P2725D

Gamintojas: DELL TECHNOLOGIES

EAN: 5397184962473

Prekės kodas: 482042

337.99€

DELL P2725D 27 colių QHD Profesionalus Monitorius

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

DELL P2725D monitorius yra meistriškai sukurtas siekiant padidinti verslo produktyvumą ir užtikrinti išskirtinį vizualinį komfortą visos darbo dienos metu. Su ryškia 27 colių IPS matrica ir Quad HD (2560x1440) raiška, šis ekranas pateikia aiškias detales ir gyvas, nuoseklias spalvas (99% sRGB aprėptis), puikiai tinkančias darbui su keliomis užduotimis ir profesionalioms programoms.

Šis monitorius, sertifikuotas TÜV Rheinland® 4 žvaigždučių akių komforto lygiu, turi „Flicker-free“ (nemirksėjimo) technologiją ir mažai mėlynos šviesos spinduliavimo funkcijas, minimalizuojančias akių įtampą dirbant ilgą laiką. Aukštas 100 Hz atnaujinimo dažnis užtikrina sklandesnį vaizdą, palyginti su standartiniais 60 Hz ekranais, pagerindamas vizualinę patirtį naršant dokumentus ar tvarkant sudėtingas lenteles.

Pagrindinės savybės našumui ir komfortui:

- **Itin Aiški QHD Raiška:** 27 colių IPS matrica su 2560 x 1440 raiška suteikia didelę ekrano erdvę ir puikų aiškumą.
- **Sklandus Vaizdas:** 100 Hz maksimalus atnaujinimo dažnis ir greitas 5 ms (GTG) reakcijos laikas sumažina judesio susiliejamą.
- **Aukščiausias Akių Komfortas:** TÜV Rheinland 4 žvaigždučių sertifikatas, apimantis integruotą mažai mėlynos šviesos ir nemirksėjimo technologiją, sumažinančią akių nuovargį.
- **Pažangi Ergonomika:** Universalus stovas leidžia visiškai pritaikyti monitorių, įskaitant pasukimą ($\pm 45^\circ$), vartymą ($\pm 90^\circ$), pakreipimą (nuo -5° iki 21°) ir aukščio reguliavimą (iki 150 mm).
- **Integruotas Ryšys:** Turi integruotą USB 3.2 Gen 1 šakotuvą su keliais prievadais (įskaitant USB Type-C pasrovinį), HDMI 2.1 ir DisplayPort 1.4, užtikrinant sklandų prisijungimą prie visų jūsų periferinių įrenginių.
- **Platūs Matymo Kampai:** IPS technologija suteikia $178^\circ/178^\circ$ matymo kampus, užtikrinančius spalvų vientisumą iš beveik bet kurios pozicijos.

Prijungimas ir Dizainas

Sukurtas šiuolaikinei darbo vietai, P2725D komplektuojamas su vidiniu maitinimo šaltiniu ir patikimomis jungčių galimybėmis, užtikrinančiomis tvarkingą darbo vietą. Monitorius pasižymi elegantiška Juodos ir Sidabro spalvų estetika ir palaiko VESA tvirtinimą (100x100) lanksčiam montavimui.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

DELL yra visame pasaulyje pripažintas lyderis aukštos kokybės kompiuterijos ir ekranų sprendimuose, įsipareigojęs teikti patikimas, novatoriškas technologijas, pritaikytas profesionaliai ir verslo aplinkai. DELL monitoriai teikia pirmenybę vartotojų produktyvumui ir tvarumui, turėdami tokius sertifikatus kaip ENERGY STAR ir TCO.

Užsisakykite šiandien iš ++SHOP++, nes siūlome geriausias kainas ir garantuojame originalius DELL produktus.

Certified by TÜV Rheinland® for 4-star eye comfort, this 27-inch QHD monitor offers enhanced productivity with visual comfort.

Certified by TÜV Rheinland® for 4-star eye comfort, this 27-inch QHD monitor offers enhanced productivity with visual comfort.

- 68.6cm (27") Quad HD 2560 x 1440 Edge LED IPS
- 8ms, 16:9, 350cd/m², 1500:1
- USB, HDMI, DisplayPort

Actual configuration might differ from illustration

Product Carbon Footprint (PCF):

1. Dell generally uses the PAIA (Product Attribute to Impact Algorithm)(<http://msl.mit.edu/projects/paia/main.html>) tool for product carbon footprint calculations.
2. Docking station related PCFs are extracted from corresponding LCAs and as such do not follow the PAIA methodology used for calculating other PCFs in this report.
3. PAIA method is developed by the Massachusetts Institute of Technology's Materials Systems Laboratory and partners.
4. All estimates of carbon footprint are uncertain. Dell Technologies reports the 5th and 95th percentile of the carbon footprint estimate to reflect this uncertainty wherever possible. (<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>)
5. Please note the emission estimate in this report is calculated using the mean value along with the standard deviation for that product model.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

6. Use of default inputs (i.e. not primary data) and assumptions on location of use and other fields can introduce a standard deviation which must be taken into account while completing the calculations.
7. Please note, PAIA uses the ecoinvent Database (<https://ecoinvent.org/the-ecoinvent-database/>) whenever primary data is not made available for calculations.
8. For client and commercial end user computing products, minimum configurations were assumed for calculations. For Server and Storage products, typical configurations or ENERGY STAR (<https://www.energystar.gov/products>) configurations were used for calculations.
9. Use Phase emissions were calculated based on the location of use as "Europe" i.e. the Use Phase emissions are not specific to a single country / location.
10. The report does provide an option for a total emissions number for manufacturing, transport and end of life while leaving the use phase emissions out, in case the customer uses their own calculation methodology for use phase emissions.
11. The lifetime usage assumption at the product family level is as follows: Desktop, Notebook - 4 years, Display - 5 years and Servers - 4 years.
12. For detailed assumptions please refer to the product datasheets in the Dell Technologies reports (<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>).
13. The results from the PAIA tool are liable to change over time as the methodology is improved and datasets are updated. The PAIA version used to calculate emissions has been indicated with each record in the report.
14. Metrics used: The units for global warming potential are in kgCO₂-equivalent or MT (metric ton) CO₂-equivalent (CO₂e).
15. Beginning in June 2024, the data dashboard now incorporates PCF values computed using the Dell PCF calculator. It's important to note that the default location utilized for these calculations shown on the data dashboard is Europe. To access PCF values calculated for the USA and China locales, please refer to the Product PCF PDF document on Dell.com.

Summary: DELL Pro Plus P2725D. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black, Silver | Vendor Homepage: <https://www.dell.com/en-uk/shop/> | Anti-glare screen: Yes | Backlight type: Edge LED | Contrast ratio (typical): 1500:1 | Digital horizontal frequency: 30 - 151 | Digital vertical frequency: 48

- 100 | Display brightness (typical): 350 | Display diagonal: 27 | Display number of colours: 16.7 million colours | Display resolution: 2560 x 1440 | Display technology: LCD | HD type: Quad HD | High Dynamic Range (HDR) supported: No | LED backlight: Yes | Maximum refresh rate: 100 | Native aspect ratio: 16:9 | Panel type: IPS | Pixel density: 109 | Pixel pitch: 0.2331 x 0.2331 | Response time: 8 | Response time (fast): 5 | Response time measurement type: GTG (Gray to Gray) | Screen shape: Flat | sRGB coverage (typical): 99 | Supported graphics resolutions: 1024 x 768 (XGA)/1152 x 864 (XGA+)/1280 x 1024 (SXGA)/1280 x 720 (HD 720)/1600 x 900/1920 x 1080 (HD 1080)/2560 x 1440/640 x 480 (VGA)/720 x 400/800 x 600 (SVGA) | Supported video modes: 1080p/480p/576p/720p | Surface hardness: 3H | Touchscreen: No | Viewable size, horizontal: 596.74 | Viewable size, vertical: 335.66 | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | AMD FreeSync: No | Flicker-free technology: Yes | Low Blue Light technology: Yes | NVIDIA G-SYNC: No | Built-in camera: No | Built-in speaker(s): No | Detachable stand: Yes | Feet colour: Silver | Front bezel colour: Black | Market positioning: office | Product colour: Black,Silver | Built-in USB hub: Yes | DisplayPort version: 1.4 | DisplayPorts quantity: 1 | HDCP: Yes | HDCP version: 1.4 | HDMI: Yes | HDMI ports quantity: 1 | HDMI version: 2.1 | Headphone out: No | Number of USB Type-B upstream ports quantity: 1 | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | USB Type-A downstream ports quantity: 3 | USB Type-C downstream ports quantity: 1 | USB upstream port type: USB Type-B | Wi-Fi: No | Adjustable height (max): 150 | Cable lock slot: Yes | Cable lock slot type: Kensington | Cable management: Yes | Height adjustment: Yes | LED indicators: Yes | On Screen Display (OSD): Yes | Panel mounting interface: 100 x 100 | Pivot: Yes | Pivot angle: -90 - 90 | Plug and Play: Yes | Swivel angle range: -45 - 45 | Swivelling: Yes | Tilt adjustment: Yes | Tilt angle range: -5 - 21 | VESA mounting: Yes | Wall mountable: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Energy consumption (SDR) per 1000 hours: 19 | Energy efficiency class (HDR): Not available | Energy efficiency class (SDR): E | Energy efficiency scale: A to G | Power consumption (max): 75 | Power consumption (off): 0.3 | Power consumption (standby): 0.3 | Power consumption (typical): 18.8 | Power supply type: Internal | Non-operating altitude: 5000 - 12191 | Operating altitude: 0 - 5000 | Operating relative humidity (H-H): 10 - 80 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -20 - 60 | Bezel width (bottom): 13.02 | Bezel width (side): 7.88 | Bezel width (top): 7.88 | Depth (with stand): 192.16 | Depth (without stand): 49.99 | Height (with stand): 535.7 | Height (without stand): 356.55 | Weight (with stand): 5880 | Weight (without stand): 4280 | Width (with stand): 612.5 | Width (without stand): 612.5 | Package weight: 8670 | Cables included: AC/DisplayPort/USB Type-A to USB Type-B | DisplayPort cable length: 1.8 | Power adapter included: No | Remote control included: No | Stand included: Yes | Stylus

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

included: No | Doesn't contain: Arsenic/Mercury/PVC/BFR | Sustainability certificates: ENERGY STAR/TCO | Carbon emissions, end-of-life (kg of CO2e): 8.61 | Carbon emissions, energy usage (kg of CO2e): 92.19 | Carbon emissions, logistics (kg of CO2e): 16.17 | Carbon emissions, manufacturing (kg of CO2e): 93.03 | PAIA version: GaBi version 1, 2024 | Total carbon footprint (kg of CO2e): 210 | Compliance certificates: RoHS | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/2173550/fiches?language=EN> | Energy efficiency class: E | EPREL Registration Number: 2173550 | EPREL Version Number: 1 | Model: P2725D | Unit Calculated Volume: 0.0538313 | Product Net Weight: 6.27 | Unit Calculated Weight: 8.65