

Zyxel XGS1935-52HP Managed L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE)

Gamintojas: **ZYXEL** · Modelis: **XGS1935-52HP-EU0101F** · EAN: **4718937636419** · Prekės kodas: **482351**



772,90 €

Kaina su PVM

Be PVM: **638,76 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 10 GbE Uplinks
- ✓ NebulaFlex base free of charge
- ✓ PoE+ up to 375W
- ✓ Advanced Function, Static Routing, VLAN, QoS, IGMP Snooping, LAG, IPv6
- ✓ Silent Operation with smart fan



Aprašymas

Using 10GbE Uplink Switch With Reasonable Price

With Gigabit connectivity plus four 10GbE uplinks, the XGS1935 Series is an ideal option for those who need basic functions, easier management, and a more reasonable price to upgrade their networks and ensure network efficiency for continuous business productivity.

Manage It Your Way!

The support of NebulaFlex allows you to easily switch network management modes between standalone, and our license-free Nebula cloud management platform. Nebula provides both intuitive web interface and mobile App to deliver a streamlined experience for installation and management of your network, without additional cost for a software or hardware controller.

Web-managed with advanced features

You can configure and manage advanced features like static routing, VLAN, QoS, IGMP Snooping, Link Aggregation, IPv6 and DoS prevention through

an intuitive built-in Web-based browser. Moreover, the friendly step-by-step intuitive wizard helps avoiding multiple complicated configuration pages for quick set up with few clicks in the matter of minutes.

Powering more devices intelligently

The PoE models XGS1935-28HP and XGS1935-52HP are designed with compact dimensions and support PoE+ delivering 30W per port, making them ideal for dense PoE deployments. With a 375W high-power budget, they can meet the demands of power-hungry devices. Additionally, the power consumption mode improves budget efficiency for a better ROI, allowing more PD devices to be connected within the system.

Silent, and reliable operation

This Series is built with smart fan designed to automatically adjust speeds based on the device temperature, offering near silent operation and stable connection for your daily work.

Built with nature in mind

The XGS1935 series is built with a more compact chassis, reducing packaging by up to 36% and weight by up to 22% compared to the previous XGS1930 series. These efforts have resulted in a 48% increase in units per pallet and a reduced carbon footprint.

Techninė specifikacija

Specifications	
Sandėlio grupė	[NES] NETWORK SWITCHES [+74][-362]
Management features	
Switch type	Managed
Switch layer	L2/L3
Quality of Service (QoS) support	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	48
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP+ module slots quantity	4
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	Yes
VLAN support	Yes
Data transmission	
MAC address table	16000 entries
Switching capacity	176 Gbit/s
Forwarding rate	130.9 Mpps

Jumbo frames support	Yes
Jumbo frames	9000
Security	
DHCP features	DHCP Option 82, DHCP client, DHCP relay, DHCPv6 client
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Performance	
Internal memory	512 MB
Flash memory	32 MB
Mean time between failures (MTBF)	562941 h
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	470.1 W
Power protection features	Surge protection
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Total Power over Ethernet (PoE) budget	375 W
Operational conditions	
Operating temperature (T-T)	-20 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 95%
Storage relative humidity (H-H)	10 - 95%
Heat dissipation	324.495 BTU/h
Weight & dimensions	
Width	440 mm
Depth	270 mm
Height	43 mm
Weight	5.64 kg
Packaging data	

Package width	508 mm
Package depth	394 mm
Package height	90 mm
Package weight	12.4 kg
Matmenys ir svoris	
Matmenys (l × p × A)	52,00cm × 40,00cm × 10,00cm
Svoris	5,76kg