



# CARD READER POCKET SMARTCARD/USB- C CRE-SMPC AXAGON

Modelis: CRE-SMPC

Gamintojas: AXAGON

EAN: 8595247907851

Prekės kodas: 48506

---

## 13.99€

---

Foldable pocket Smart card / ID card reader AXAGON CRE-SMPC PocketReader with USB-C 480Mbps interface. It is especially suitable as an ID card reader for use with mobile phones that have an USB-C input. The modern reversible USB-C connector makes the reader easy to use, eliminating the need for the correct orientation of the connector when connecting to a computer or phone.

The card reader supports all common contact Smart card formats, chip cards and other cards, including contact bank payment cards or contact electronic ID cards \*. The reader is compatible with most national applications for eID (electronic ID cards).

Compatibility with all common OS such as Windows, Linux, macOS, iOS and Android, allows wide use on desktops and laptops as well as smartphones and tablets.

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

The smart LED indication lights up shortly after the activity change, then turns off and doesn't bother the user with unnecessary light. The foldable design and compact size make this reader one of the smallest Smart Card readers on the market. The integrated loop allows you to hang it e.g. on keys, so you can always have it with you and it will not interfere.

#### Input:

- USB-C 480Mbps CCID protocol.
- Backward compatible with USB 1.1.
- Connection to a computer, phone or tablet via USB 2.0 type C male connector.

#### Card reader:

- 1 slot supports ATM / CAC / ID / IC / SIS cards.
- Supports ISO 7816 Class A, B and C contact Smart cards (5V, 3V and 1.8V).
- Supports ISO 7816, EMV 4.1 (EMV 2000 level 1) standards.
- Supports protocols T=0 and T=1, I2C, SLE 4432/42 (S=10), SLE 4418/28 (S=9).
- PC/SC 2.0 PC Smart Card standard support.
- Microsoft Smart Card for Windows support.
- Supports I2C cards SLE4418, SLE4428, SLE4432, SLE4442, SLE4436, SLE5536, SLE6636, AT88SC1608, AT45D041.
- Microsoft WHQL USB Smart Card Reader compliant.
- FIPS 201 standard compliant.

#### Other features:

- Microsoft USB-CCID driver compatible.
- Plug and Play support.
- Microsoft USB-CCID driver compatible.
- Support power saving mode, automatic switching to power saving mode.
- Powering the reader via USB bus (bus-power).
- A LED indicates computer USB port connection (steady) and data transfer (flashing).
- LED indicators lights up shortly after the activity change, then turns off and doesn't bother.
- Dimension 52 x 20 x 16 mm.
- Weight 9 g.

#### Supported OS:

- MS Windows 7 / 8 / 8.1 / 10 / 11 and later, macOS, Linux, iOS and Android.
  - to work with a Smart card, it is necessary to install a suitable application on the connected device.
- \* Note: The reader only supports contact cards that have visible contacts on the surface. The card without contacts is therefore RFID and cannot be used in the reader.

#### Package contains:

- USB-C Smart Card Reader,
- key hinge,
- multilingual manual CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / BG / CN / TR / ARA,
- packed in a cardboard box with a hanging hole.

Summary: Axagon CRE-SMPC USB-C Smart card/ID card PocketReader. Interface: USB Type-C.

Product colour: Black. Weight: 9 g | Vendor Homepage: <https://www.axagon.eu/en/produkty/cre-smpc> | Application area: Access control, Banking & payments, Healthcare | Easy to use: Yes | Plug and Play: Yes | Product type: Universal smart card reader | SIM card support: No | Built-in display: No | Country of origin: China | Housing material: Plastic | LED indicators: Yes | Placement supported: Indoor | Product colour: Black | Bluetooth: No | Interface: USB Type-C | Near Field Communication (NFC): No | Supported protocols: T=0 und T=1, I2C, SLE 4432/42 (S=10), SLE 4418/28 (S=9) | External power adapter: No | Operating voltage: 5 | Power source: USB | Compliance certificates: CE/RoHS | Manual: Yes | Warranty period: 2 | Linux operating systems supported: Yes | Mac compatibility: Yes | Mac operating systems supported: Yes | Other operating systems supported: Yes | Windows operating systems supported: Yes | Depth: 16 | Height: 20 | Weight: 9 | Width: 52 | Certification: CE, RoHS | Package depth: 100 | Package height: 20 | Package type: Box | Package weight: 37 | Package width: 125 | Quick installation guide: Yes | Smart card included: No | Model: CRE-SMPC | Units per Shipping Box: 150 | Unit Calculated Volume: 0.0002551 | Unit Calculated Weight: 0.041